



416F38425CLR Information

www.mebe.nemem

For Reference Only

Part Number 416F38425CLR

Manufacturer CTS-Frequency Controls

Category Crystals, Oscillators, Resonators

Crystals

Description CRYSTAL 38.400 MHZ 12PF SMT

Package 4-SMD, No Lead

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









416F38425CLR Specifications

Manufacturer Part Number Manufacturer Category Crystals, Oscillators, Resonators Crystals Package 4-SMD, No Lead Series 416 Type MHz Crystal Frequency 520ppm Frequency Stability Frequency Tolerance Load Capacitance ESR (Equivalent Series Resistance) Operating Mode Operating Temperature Coperating Type Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 416 CTS-Frequency Controls Crystals A-SMD, No Lead Crystals A-SMD, No Lead Size / Dimension CTS-Frequency Controls 4-SMD, No Lead Size / Dimension		
Category Crystals Oscillators, Resonators Crystals Package 4-SMD, No Lead Series 416 Type MHz Crystal Frequency 38.4MHz Frequency Stability ±50ppm Frequency Tolerance ±20ppm Load Capacitance 12pF ESR (Equivalent Series Resistance) 200 Ohm Operating Mode Fundamental Operating Temperature -20°C ~ 70°C Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.063" L x 0.047" W (1.60mm x 1.20mm)	Manufacturer Part Number	416F38425CLR
Crystals Package 4-SMD, No Lead Series 416 Type MHz Crystal Frequency 38.4MHz Frequency Stability ±50ppm Frequency Tolerance ±20ppm Load Capacitance 12pF ESR (Equivalent Series Resistance) 200 Ohm Operating Mode Fundamental Operating Temperature -20°C ~ 70°C Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.063" L x 0.047" W (1.60mm x 1.20mm)	Manufacturer	CTS-Frequency Controls
Package 4-SMD, No Lead Series 416 Type MHz Crystal Frequency 38.4MHz Frequency Stability ±50ppm Frequency Tolerance ±20ppm Load Capacitance 12pF ESR (Equivalent Series Resistance) 200 Ohm Operating Mode Fundamental Operating Temperature -20°C ~ 70°C Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.063" L x 0.047" W (1.60mm x 1.20mm)	Category	Crystals, Oscillators, Resonators
Series 416 Type MHz Crystal Frequency 38.4MHz Frequency Stability ±50ppm Frequency Tolerance ±20ppm Load Capacitance 12pF ESR (Equivalent Series Resistance) 200 Ohm Operating Mode Fundamental Operating Temperature -20°C ~ 70°C Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.063" L x 0.047" W (1.60mm x 1.20mm)		Crystals
Type MHz Crystal Frequency 38.4MHz Frequency Stability ±50ppm Frequency Tolerance ±20ppm Load Capacitance 12pF ESR (Equivalent Series Resistance) 200 Ohm Operating Mode Fundamental Operating Temperature -20°C ~ 70°C Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.063" L x 0.047" W (1.60mm x 1.20mm)	Package	4-SMD, No Lead
Frequency Stability ±50ppm Frequency Tolerance ±20ppm Load Capacitance 12pF ESR (Equivalent Series Resistance) 200 Ohm Operating Mode Fundamental Operating Temperature -20°C ~ 70°C Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.063" L x 0.047" W (1.60mm x 1.20mm)	Series	416
Frequency Stability ±50ppm Frequency Tolerance ±20ppm Load Capacitance 12pF ESR (Equivalent Series Resistance) 200 Ohm Operating Mode Fundamental Operating Temperature -20°C ~ 70°C Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.063" L x 0.047" W (1.60mm x 1.20mm)	Type	MHz Crystal
Frequency Tolerance ±20ppm Load Capacitance 12pF ESR (Equivalent Series Resistance) 200 Ohm Operating Mode Fundamental Operating Temperature -20°C ~ 70°C Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.063" L x 0.047" W (1.60mm x 1.20mm)	Frequency	38.4MHz
Load Capacitance 12pF ESR (Equivalent Series Resistance) 200 Ohm Operating Mode Fundamental Operating Temperature -20°C ~ 70°C Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.063" L x 0.047" W (1.60mm x 1.20mm)	Frequency Stability	±50ppm
ESR (Equivalent Series Resistance) Operating Mode Fundamental Operating Temperature -20°C ~ 70°C Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.063" L x 0.047" W (1.60mm x 1.20mm)	Frequency Tolerance	±20ppm
Operating Mode Operating Temperature -20°C ~ 70°C Ratings Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension Ones are the surface of the s	Load Capacitance	12pF
$ \begin{array}{llllllllllllllllllllllllllllllllllll$	ESR (Equivalent Series Resistance)	200 Ohm
Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.063" L x 0.047" W (1.60mm x 1.20mm)	Operating Mode	Fundamental
Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.063" L x 0.047" W (1.60mm x 1.20mm)	Operating Temperature	-20°C ~ 70°C
Package / Case 4-SMD, No Lead Size / Dimension 0.063" L x 0.047" W (1.60mm x 1.20mm)	Ratings	-
Size / Dimension 0.063" L x 0.047" W (1.60mm x 1.20mm)	Mounting Type	Surface Mount
	Package / Case	4-SMD, No Lead
	Size / Dimension	0.063" L x 0.047" W (1.60mm x 1.20mm)
Height - Seated (Max) 0.018" (0.45mm)	Height - Seated (Max)	0.018" (0.45mm)
Report errors?		Report errors?

416F38425CLR Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

416F38425CLR Payment Methods



















416F38425CLR Shipping Methods













If you have any question about 416F38425CLR, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com