



416F40623CTT Information



For Reference Only

Part Number 416F40623CTT

Manufacturer CTS-Frequency Controls

Category Crystals, Oscillators, Resonators

Crystals

Description CRYSTAL 40.610 MHZ 6PF SMT

Package 4-SMD, No Lead

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









416F40623CTT Specifications

Manufacturer Part Number 416F40623CTT Manufacturer CTS-Frequency Controls Category Crystals, Oscillators, Resonators Package 4-SMD, No Lead Series 416 Type MHz Crystal Frequency 40.61MHz Frequency Stability ±30ppm Frequency Tolerance ±20ppm Load Capacitance 6pF ESR (Equivalent Series Resistance) 100 Ohm Operating Mode Fundamental Operating Temperature -20°C ~ 70°C Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.063" L x 0.047" W (1.60mm x 1.20mm) Height - Seated (Max) 0.018" (0.45mm)	•	
Category Crystals, Oscillators, Resonators Package 4-SMD, No Lead Series 416 Type MHz Crystal Frequency 40.61MHz Frequency Stability ±30ppm Frequency Tolerance ±20ppm Load Capacitance 6pF ESR (Equivalent Series Resistance) 100 Ohm Operating Mode Fundamental Operating Temperature -20°C ~ 70°C Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.063" L x 0.047" W (1.60mm x 1.20mm)	Manufacturer Part Number	416F40623CTT
Package 4-SMD, No Lead Series 416 Type MHz Crystal Frequency 40.61MHz Frequency Stability ±30ppm Frequency Tolerance ±20ppm Load Capacitance 6pF ESR (Equivalent Series Resistance) 100 Ohm Operating Mode Fundamental Operating Temperature -20°C ~ 70°C Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.063" L x 0.047" W (1.60mm x 1.20mm)	Manufacturer	CTS-Frequency Controls
Package 4-SMD, No Lead Series 416 Type MHz Crystal Frequency 40.61MHz Frequency Stability ±30ppm Frequency Tolerance ±20ppm Load Capacitance 6pF ESR (Equivalent Series Resistance) 100 Ohm Operating Mode Fundamental Operating Temperature -20°C ~70°C Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.063" L x 0.047" W (1.60mm x 1.20mm)	Category	Crystals, Oscillators, Resonators
Series 416 Type MHz Crystal Frequency 40.61MHz Frequency Stability ±30ppm Frequency Tolerance ±20ppm Load Capacitance 6pF ESR (Equivalent Series Resistance) 100 Ohm Operating Mode Fundamental Operating Temperature -20°C ~70°C Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.063" L x 0.047" W (1.60mm x 1.20mm)		Crystals
Type MHz Crystal Frequency 40.61MHz Frequency Stability ±30ppm Frequency Tolerance ±20ppm Load Capacitance 6pF ESR (Equivalent Series Resistance) 100 Ohm Operating Mode Fundamental Operating Temperature -20°C ~ 70°C Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.063" L x 0.047" W (1.60mm x 1.20mm)	Package	4-SMD, No Lead
Frequency Stability ±30ppm Frequency Tolerance ±20ppm Load Capacitance 6pF ESR (Equivalent Series Resistance) 100 Ohm Operating Mode Fundamental Operating Temperature -20°C ~ 70°C Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.063" L x 0.047" W (1.60mm x 1.20mm)	Series	416
Frequency Stability ±30ppm Frequency Tolerance ±20ppm Load Capacitance 6pF ESR (Equivalent Series Resistance) 100 Ohm Operating Mode Fundamental Operating Temperature -20°C ~ 70°C Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.063" L x 0.047" W (1.60mm x 1.20mm)	Туре	MHz Crystal
Frequency Tolerance ±20ppm Load Capacitance 6pF ESR (Equivalent Series Resistance) 100 Ohm Operating Mode Fundamental Operating Temperature -20°C ~ 70°C Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.063" L x 0.047" W (1.60mm x 1.20mm)	Frequency	40.61MHz
Load Capacitance 6pF ESR (Equivalent Series Resistance) 100 Ohm Operating Mode Fundamental Operating Temperature -20°C ~ 70°C Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.063" L x 0.047" W (1.60mm x 1.20mm)	Frequency Stability	±30ppm
ESR (Equivalent Series Resistance) Operating Mode Fundamental Operating Temperature -20°C ~ 70°C Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 100 Ohm Fundamental -20°C ~ 70°C -20°C ~ 70	Frequency Tolerance	±20ppm
Operating ModeFundamentalOperating Temperature $-20^{\circ}\text{C} \sim 70^{\circ}\text{C}$ Ratings-Mounting TypeSurface MountPackage / Case 4-SMD , No LeadSize / Dimension $0.063^{\circ}\text{L} \times 0.047^{\circ}\text{W} (1.60\text{mm} \times 1.20\text{mm})$	Load Capacitance	6pF
Operating Temperature -20°C ~ 70°C Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.063" L x 0.047" W (1.60mm x 1.20mm)	ESR (Equivalent Series Resistance)	100 Ohm
Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.063" L x 0.047" W (1.60mm x 1.20mm)	Operating Mode	Fundamental
Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.063" L x 0.047" W (1.60mm x 1.20mm)	Operating Temperature	-20°C ~ 70°C
Package / Case 4-SMD, No Lead Size / Dimension 0.063" L x 0.047" W (1.60mm x 1.20mm)	Ratings	-
Size / Dimension 0.063" L x 0.047" W (1.60mm x 1.20mm)	Mounting Type	Surface Mount
	Package / Case	4-SMD, No Lead
Height - Seated (Max) 0.018" (0.45mm)	Size / Dimension	0.063" L x 0.047" W (1.60mm x 1.20mm)
	Height - Seated (Max)	0.018" (0.45mm)
Report errors?		Report errors?

416F40623CTT Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

416F40623CTT Payment Methods



















416F40623CTT Shipping Methods













If you have any question about 416F40623CTT, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com