



416F40635ASR Information



For Reference Only

Part Number 416F40635ASR

Manufacturer CTS-Frequency Controls

Category Crystals, Oscillators, Resonators

Crystals

Description CRYSTAL 40.610 MHZ SERIES SMT

Package 4-SMD, No Lead

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









416F40635ASR Specifications

Manufacturer Part Number 416F40635ASR Manufacturer CTS-Frequency Controls Category Crystals, Oscillators, Resonators Crystals Crystals Package 4-SMD, No Lead Series 416 Type MHz Crystal Frequency 40.61MHz Frequency Stability ±50ppm Frequency Tolerance ±30ppm Load Capacitance Series ESR (Equivalent Series Resistance) 100 Ohm Operating Mode Fundamental Operating Temperature -10°C ~ 60°C Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead		
Category Crystals, Oscillators, Resonators Crystals Package 4-SMD, No Lead Series 416 Type MHz Crystal Frequency 40.61MHz Frequency Stability Frequency Tolerance Load Capacitance ESR (Equivalent Series Resistance) Operating Mode Operating Temperature Ratings Mounting Type Surface Mount Package / Case Crystals, Oscillators, Resonators Crystals Crystals Oscillators, Resonators Absoluted Funda 100 Crystals 4-SMD, No Lead	Manufacturer Part Number	416F40635ASR
Crystals Package 4-SMD, No Lead Series 416 Type MHz Crystal Frequency 40.61MHz Frequency Stability ±50ppm Frequency Tolerance ±30ppm Load Capacitance Series ESR (Equivalent Series Resistance) 100 Ohm Operating Mode Fundamental Operating Temperature -10°C ~ 60°C Ratings Mounting Type Surface Mount Package / Case 4-SMD, No Lead	Manufacturer	CTS-Frequency Controls
Package 4-SMD, No Lead Series 416 Type MHz Crystal Frequency 40.61MHz Frequency Stability ±50ppm Frequency Tolerance ±30ppm Load Capacitance Series ESR (Equivalent Series Resistance) 100 Ohm Operating Mode Fundamental Operating Temperature -10°C ~ 60°C Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead	Category	Crystals, Oscillators, Resonators
Series 416 Type MHz Crystal Frequency 40.61MHz Frequency Stability ±50ppm Frequency Tolerance ±30ppm Load Capacitance Series ESR (Equivalent Series Resistance) 100 Ohm Operating Mode Fundamental Operating Temperature -10°C ~ 60°C Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead		Crystals
Type MHz Crystal Frequency 40.61MHz Frequency Stability ±50ppm Frequency Tolerance ±30ppm Load Capacitance Series ESR (Equivalent Series Resistance) 100 Ohm Operating Mode Fundamental Operating Temperature -10°C ~ 60°C Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead	Package	4-SMD, No Lead
Frequency Stability ±50ppm Frequency Tolerance ±30ppm Load Capacitance Series ESR (Equivalent Series Resistance) 100 Ohm Operating Mode Fundamental Operating Temperature -10°C ~ 60°C Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead	Series	416
Frequency Stability ± 50 ppm Frequency Tolerance ± 30 ppm Load Capacitance Series ESR (Equivalent Series Resistance) 100 Ohm Operating Mode Fundamental Operating Temperature -10° C $\sim 60^{\circ}$ C Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead	Туре	MHz Crystal
Frequency Tolerance ±30ppm Load Capacitance Series ESR (Equivalent Series Resistance) 100 Ohm Operating Mode Fundamental Operating Temperature -10°C ~ 60°C Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead	Frequency	40.61MHz
Load Capacitance ESR (Equivalent Series Resistance) Operating Mode Operating Temperature -10°C ~ 60°C Ratings - Mounting Type Surface Mount Package / Case Series 100 Ohm Fundamental -10°C ~ 60°C Surface Mount 4-SMD, No Lead	Frequency Stability	±50ppm
ESR (Equivalent Series Resistance) Operating Mode Fundamental Operating Temperature -10°C ~ 60°C Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead	Frequency Tolerance	±30ppm
$\begin{array}{cccccccccccccccccccccccccccccccccccc$	Load Capacitance	Series
$ \begin{array}{cccc} \text{Operating Temperature} & & -10^{\circ}\text{C} \sim 60^{\circ}\text{C} \\ \text{Ratings} & & - \\ \text{Mounting Type} & & \text{Surface Mount} \\ \text{Package / Case} & & 4\text{-SMD, No Lead} \\ \end{array} $	ESR (Equivalent Series Resistance)	100 Ohm
Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead	Operating Mode	Fundamental
Mounting Type Surface Mount Package / Case 4-SMD, No Lead	Operating Temperature	-10°C ~ 60°C
Package / Case 4-SMD, No Lead	Ratings	-
-	Mounting Type	Surface Mount
	Package / Case	4-SMD, No Lead
Size / Dimension 0.063" L x 0.047" W (1.60mm x 1.20mm)	Size / Dimension	0.063" L x 0.047" W (1.60mm x 1.20mm)
Height - Seated (Max) 0.018" (0.45mm)	Height - Seated (Max)	0.018" (0.45mm)
Report errors?		Report errors?

416F40635ASR Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

416F40635ASR Payment Methods





















416F40635ASR Shipping Methods













If you have any question about 416F40635ASR, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com