



416F406X3CKR Information



For Reference Only

Part Number 416F406X3CKR

Manufacturer CTS-Frequency Controls

Category Crystals, Oscillators, Resonators

Crystals

Description CRYSTAL 40.610 MHZ 8PF SMT

Package 4-SMD, No Lead

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









416F406X3CKR Specifications

Manufacturer Part Number416F406X3CKRManufacturerCTS-Frequency ControlsCategoryCrystals, Oscillators, ResonatorsPackage4-SMD, No LeadSeries416TypeMHz CrystalFrequency40.61MHzFrequency Stability±30ppmFrequency Tolerance±15ppmLoad Capacitance8pFESR (Equivalent Series Resistance)100 OhmOperating ModeFundamentalOperating Temperature-20°C ~ 70°CRatings-Mounting TypeSurface MountPackage / Case4-SMD, No LeadSize / Dimension0.063" L x 0.047" W (1.60mm x 1.20mm)Height - Seated (Max)0.018" (0.45mm)	•	
Category Crystals, Oscillators, Resonators Crystals Package 4-SMD, No Lead Series 416 Type MHz Crystal Frequency 40.61MHz Frequency Stability ±30ppm Frequency Tolerance ±15ppm Load Capacitance 8pF ESR (Equivalent Series Resistance) 100 Ohm Operating Mode Operating Temperature -20°C ~ 70°C Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.063" L x 0.047" W (1.60mm x 1.20mm) Height - Seated (Max) 0.018" (0.45mm)	Manufacturer Part Number	416F406X3CKR
Package 4-SMD, No Lead Series 416 Type MHz Crystal Frequency 40.61MHz Frequency Stability ±30ppm Frequency Tolerance ±15ppm Load Capacitance 8pF ESR (Equivalent Series Resistance) 100 Ohm Operating Mode Fundamental Operating Temperature -20°C ~ 70°C Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.063" L x 0.047" W (1.60mm x 1.20mm) Height - Seated (Max) 0.018" (0.45mm)	Manufacturer	CTS-Frequency Controls
Package 4-SMD, No Lead Series 416 Type MHz Crystal Frequency 40.61MHz Frequency Stability ±30ppm Frequency Tolerance ±15ppm Load Capacitance 8pF ESR (Equivalent Series Resistance) 100 Ohm Operating Mode Fundamental Operating Temperature -20°C ~ 70°C Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.063" L x 0.047" W (1.60mm x 1.20mm) Height - Seated (Max) 0.018" (0.45mm)	Category	Crystals, Oscillators, Resonators
Series 416 Type MHz Crystal Frequency 40.61MHz Frequency Stability ±30ppm Frequency Tolerance ±15ppm Load Capacitance 8pF ESR (Equivalent Series Resistance) 100 Ohm Operating Mode Fundamental Operating Temperature -20°C ~ 70°C Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.063" L x 0.047" W (1.60mm x 1.20mm) Height - Seated (Max) 0.018" (0.45mm)		Crystals
Type MHz Crystal Frequency 40.61MHz Frequency Stability ±30ppm Frequency Tolerance ±15ppm Load Capacitance 8pF ESR (Equivalent Series Resistance) 100 Ohm Operating Mode Fundamental Operating Temperature -20°C ~ 70°C Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.063" L x 0.047" W (1.60mm x 1.20mm) Height - Seated (Max) 0.018" (0.45mm)	Package	4-SMD, No Lead
Frequency Stability ±30ppm Frequency Tolerance ±15ppm Load Capacitance 8pF ESR (Equivalent Series Resistance) 100 Ohm Operating Mode Fundamental Operating Temperature -20°C ~ 70°C Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.063" L x 0.047" W (1.60mm x 1.20mm) Height - Seated (Max) 0.018" (0.45mm)	Series	416
Frequency Stability ±30ppm Frequency Tolerance ±15ppm Load Capacitance 8pF ESR (Equivalent Series Resistance) 100 Ohm Operating Mode Fundamental Operating Temperature -20°C ~ 70°C Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.063" L x 0.047" W (1.60mm x 1.20mm) Height - Seated (Max) 0.018" (0.45mm)	Type	MHz Crystal
Frequency Tolerance ±15ppm Load Capacitance 8pF ESR (Equivalent Series Resistance) 100 Ohm Operating Mode Fundamental Operating Temperature -20°C ~ 70°C Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.063" L x 0.047" W (1.60mm x 1.20mm) Height - Seated (Max) 0.018" (0.45mm)	Frequency	40.61MHz
Load Capacitance8pFESR (Equivalent Series Resistance)100 OhmOperating ModeFundamentalOperating Temperature-20°C ~ 70°CRatings-Mounting TypeSurface MountPackage / Case4-SMD, No LeadSize / Dimension0.063" L x 0.047" W (1.60mm x 1.20mm)Height - Seated (Max)0.018" (0.45mm)	Frequency Stability	±30ppm
ESR (Equivalent Series Resistance) 100 Ohm Operating Mode Fundamental Operating Temperature $-20^{\circ}\text{C} \sim 70^{\circ}\text{C}$ Ratings $-$ Mounting Type Surface Mount Package / Case 4-SMD , No Lead Size / Dimension $0.063^{\circ}\text{L x } 0.047^{\circ}\text{W } (1.60\text{mm x } 1.20\text{mm})$ Height - Seated (Max) $0.018^{\circ} (0.45\text{mm})$	Frequency Tolerance	±15ppm
Operating ModeFundamentalOperating Temperature $-20^{\circ}\text{C} \sim 70^{\circ}\text{C}$ Ratings-Mounting TypeSurface MountPackage / Case 4-SMD , No LeadSize / Dimension $0.063^{\circ}\text{L} \times 0.047^{\circ}\text{W} (1.60\text{mm} \times 1.20\text{mm})$ Height - Seated (Max) 0.018° (0.45mm)	Load Capacitance	8pF
Operating Temperature -20°C ~ 70°C Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.063" L x 0.047" W (1.60mm x 1.20mm) Height - Seated (Max) 0.018" (0.45mm)	ESR (Equivalent Series Resistance)	100 Ohm
Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.063" L x 0.047" W (1.60mm x 1.20mm) Height - Seated (Max) 0.018" (0.45mm)	Operating Mode	Fundamental
Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.063" L x 0.047" W (1.60mm x 1.20mm) Height - Seated (Max) 0.018" (0.45mm)	Operating Temperature	-20°C ~ 70°C
Package / Case 4-SMD, No Lead Size / Dimension 0.063" L x 0.047" W (1.60mm x 1.20mm) Height - Seated (Max) 0.018" (0.45mm)	Ratings	-
Size / Dimension 0.063" L x 0.047" W (1.60mm x 1.20mm) Height - Seated (Max) 0.018" (0.45mm)	Mounting Type	Surface Mount
Height - Seated (Max) 0.018" (0.45mm)	Package / Case	4-SMD, No Lead
	Size / Dimension	0.063" L x 0.047" W (1.60mm x 1.20mm)
Report errors?	Height - Seated (Max)	0.018" (0.45mm)
		Report errors?

416F406X3CKR Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

416F406X3CKR Payment Methods

































If you have any question about 416F406X3CKR, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com