

420AS18035 Information

Heisener.com

Part Number 420AS18035
Manufacturer Tamura

Category Power Supplies - External/Internal (Off-Board)

AC DC Desktop, Wall Adapters

Description AC/DC WALL MOUNT ADAPTER 18V 6W

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com

Request a Quote



Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









420AS18035 Specifications

Manufacturer Part Number 420A\$18035 Manufacturer Tamura Category Power Supplies - External/Internal (Off-Board) AC DC Desktop, Wall Adapters Package - Series 420A\$ Region Utilized North America Form Wall Mount Input Type Fixed Blade Voltage - Input 120VAC Voltage - Output (Max) 350mA Power (Watts) 6.3W No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency - Operating Temperature -10°C ~ 40°C Output Connector Barrel Plug R/A, 2.1mm I.D. x 5.5mm O.D. x 12.5mm Size / Dimension 2.84" L x 2.05" W x 1.83" H (72.0mm x 52.0mm x 46.5mm)	•	
Category Power Supplies - External/Internal (Off-Board) AC DC Desktop, Wall Adapters Package - Series 420AS Region Utilized North America Form Wall Mount Input Type Fixed Blade Voltage - Input 120VAC Voltage - Output 18V Current - Output (Max) 350mA Power (Watts) 6.3W No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency - Operating Temperature -10°C ~ 40°C Output Connector Barrel Plug R/A, 2.1mm I.D. x 5.5mm O.D. x 12.5mm Size / Dimension 2.84" L x 2.05" W x 1.83" H (72.0mm x 52.0mm x 46.5mm)	Manufacturer Part Number	420AS18035
Package - Series 420AS Region Utilized North America Form Wall Mount Input Type Fixed Blade Voltage - Input 120VAC Voltage - Output 18V Current - Output (Max) 350mA Power (Watts) 6.3W No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency - Operating Temperature -10°C ~ 40°C Output Connector Barrel Plug R/A, 2.1mm I.D. x 5.5mm O.D. x 12.5mm Size / Dimension 2.84" L x 2.05" W x 1.83" H (72.0mm x 52.0mm x 46.5mm)	Manufacturer	Tamura
Package - Series 420AS Region Utilized North America Form Wall Mount Input Type Fixed Blade Voltage - Input 120VAC Voltage - Output 18V Current - Output (Max) 350mA Power (Watts) 6.3W No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency - Operating Temperature -10°C ~ 40°C Output Connector Barrel Plug R/A, 2.1mm I.D. x 5.5mm O.D. x 12.5mm Size / Dimension 2.84" L x 2.05" W x 1.83" H (72.0mm x 52.0mm x 46.5mm)	Category	Power Supplies - External/Internal (Off-Board)
Series420ASRegion UtilizedNorth AmericaFormWall MountInput TypeFixed BladeVoltage - Input120VACVoltage - Output18VCurrent - Output (Max)350mAPower (Watts)6.3WNo Load Power Consumption-PolarizationPositive CenterApplicationsITE (Commercial)Efficiency-Operating Temperature-10°C ~ 40°COutput ConnectorBarrel Plug R/A, 2.1mm I.D. x 5.5mm O.D. x 12.5mmSize / Dimension2.84" L x 2.05" W x 1.83" H (72.0mm x 52.0mm x 46.5mm)		AC DC Desktop, Wall Adapters
Region Utilized North America Form Wall Mount Input Type Fixed Blade Voltage - Input 120VAC Voltage - Output 18V Current - Output (Max) 350mA Power (Watts) 6.3W No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency - Operating Temperature -10°C ~ 40°C Output Connector Barrel Plug R/A, 2.1mm I.D. x 5.5mm O.D. x 12.5mm Size / Dimension 2.84" L x 2.05" W x 1.83" H (72.0mm x 52.0mm x 46.5mm)	Package	-
Form Wall Mount Input Type Fixed Blade Voltage - Input 120VAC Voltage - Output 18V Current - Output (Max) 350mA Power (Watts) 6.3W No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency - Operating Temperature -10°C ~ 40°C Output Connector Barrel Plug R/A, 2.1mm I.D. x 5.5mm O.D. x 12.5mm Size / Dimension 2.84" L x 2.05" W x 1.83" H (72.0mm x 52.0mm x 46.5mm)	Series	420AS
Input Type Fixed Blade Voltage - Input 120VAC Voltage - Output 18V Current - Output (Max) 350mA Power (Watts) 6.3W No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency - Operating Temperature -10°C ~ 40°C Output Connector Barrel Plug R/A, 2.1mm I.D. x 5.5mm O.D. x 12.5mm Size / Dimension 2.84" L x 2.05" W x 1.83" H (72.0mm x 52.0mm x 46.5mm)	Region Utilized	North America
Voltage - Input 120VAC Voltage - Output 18V Current - Output (Max) 350mA Power (Watts) No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency Operating Temperature Output Connector Barrel Plug R/A, 2.1mm I.D. x 5.5mm O.D. x 12.5mm Size / Dimension 120VAC 18V 18V 100C 100C	Form	Wall Mount
Voltage - Output Current - Output (Max) 350mA Power (Watts) 6.3W No Load Power Consumption Polarization Positive Center Applications ITE (Commercial) Efficiency Operating Temperature Output Connector Barrel Plug R/A, 2.1mm I.D. x 5.5mm O.D. x 12.5mm Size / Dimension 18V 18V 18V 10 Current - Output Commercial 10 C ~ 40 C 2.84" L x 2.05" W x 1.83" H (72.0mm x 52.0mm x 46.5mm)	Input Type	Fixed Blade
Current - Output (Max) Power (Watts) 6.3W No Load Power Consumption Polarization Positive Center Applications ITE (Commercial) Efficiency Operating Temperature -10°C ~ 40°C Output Connector Barrel Plug R/A, 2.1mm I.D. x 5.5mm O.D. x 12.5mm Size / Dimension 2.84" L x 2.05" W x 1.83" H (72.0mm x 52.0mm x 46.5mm)	Voltage - Input	120VAC
Power (Watts) 6.3W No Load Power Consumption Polarization Positive Center Applications ITE (Commercial) Efficiency Operating Temperature -10°C ~ 40°C Output Connector Barrel Plug R/A, 2.1mm I.D. x 5.5mm O.D. x 12.5mm Size / Dimension 2.84" L x 2.05" W x 1.83" H (72.0mm x 52.0mm x 46.5mm)	Voltage - Output	18V
No Load Power Consumption-PolarizationPositive CenterApplicationsITE (Commercial)Efficiency-Operating Temperature -10° C $\sim 40^{\circ}$ COutput ConnectorBarrel Plug R/A, 2.1 mm I.D. $x 5.5$ mm O.D. $x 12.5$ mmSize / Dimension 2.84 " L $x 2.05$ " W $x 1.83$ " H (72.0 mm $x 52.0$ mm $x 46.5$ mm)	Current - Output (Max)	350mA
Polarization Positive Center Applications ITE (Commercial) Efficiency - Operating Temperature $-10^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug R/A, 2.1mm I.D. x 5.5mm O.D. x 12.5mm Size / Dimension 2.84" L x 2.05" W x 1.83" H (72.0mm x 52.0mm x 46.5mm)	Power (Watts)	6.3W
Applications ITE (Commercial) Efficiency - Operating Temperature $-10^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug R/A, 2.1mm I.D. x 5.5mm O.D. x 12.5mm Size / Dimension 2.84" L x 2.05" W x 1.83" H (72.0mm x 52.0mm x 46.5mm)	No Load Power Consumption	-
Efficiency - Operating Temperature -10°C ~ 40°C Output Connector Barrel Plug R/A, 2.1mm I.D. x 5.5mm O.D. x 12.5mm Size / Dimension 2.84" L x 2.05" W x 1.83" H (72.0mm x 52.0mm x 46.5mm)	Polarization	Positive Center
Operating Temperature $-10^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug R/A, 2.1mm I.D. x 5.5mm O.D. x 12.5mm Size / Dimension 2.84" L x 2.05" W x 1.83" H (72.0mm x 52.0mm x 46.5mm)	Applications	ITE (Commercial)
Output Connector Barrel Plug R/A, 2.1mm I.D. x 5.5mm O.D. x 12.5mm Size / Dimension 2.84" L x 2.05" W x 1.83" H (72.0mm x 52.0mm x 46.5mm)	Efficiency	-
Size / Dimension 2.84" L x 2.05" W x 1.83" H (72.0mm x 52.0mm x 46.5mm)	Operating Temperature	-10°C ~ 40°C
	Output Connector	Barrel Plug R/A, 2.1mm I.D. x 5.5mm O.D. x 12.5mm
Report errors?	Size / Dimension	2.84" L x 2.05" W x 1.83" H (72.0mm x 52.0mm x 46.5mm)
		Report errors?

420AS18035 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

420AS18035 Payment Methods



















420AS18035 Shipping Methods













If you have any question about 420AS18035, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com