

422-87-244-41-001101 Information

www.heisener.dom

For Reference Only

Part Number 422-87-244-41-001101

Manufacturer Preci-Dip

Category Connectors, Interconnects

Rectangular Connectors - Headers, Receptacles,

Female Sockets

Description PCB CONN WIRE WRAP 2.54MM

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









422-87-244-41-001101 Specifications

Manufacturer Part Number 422-87-244-41-001101 Manufacturer Preci-Dip Category Connectors, Interconnects Rectangular Connectors - Headers, Receptacles, Female Sockets Package - Scries 422 Connector Type Socket Contact Type Female Socket Style Board to Cable/Wire Number of Positions 44 Number of Positions Loaded All Pitch - Mating 0.100" (2.54mm) Number of Rows 2 Row Spacing - Mating 0.100" (2.54mm) Mounting Type Through Hole Termination Wire Wrap Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating Flash Insulation Color Black Insulation Height 0.193" (4.90mm) Contact Length - Post 0.370" (9.40mm) Operating Temperature -55°C ~ 125°C Material Flammability Rating UL94 V-0		
Category Connectors, Interconnects Package - Series 422 Connector Type Socket Contact Type Female Socket Style Board to Cable/Wire Number of Positions 44 Number of Positions Loaded All Pitch - Mating 0.100" (2.54mm) Number of Rows 2 Row Spacing - Mating 0.100" (2.54mm) Mounting Type Through Hole Termination Wire Wrap Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating Flash Insulation Color Black Insulation Height 0.193" (4.90mm) Contact Length - Post 0.370" (9.40mm) Operating Temperature -55°C ~ 125°C	Manufacturer Part Number	422-87-244-41-001101
Rectangular Connectors - Headers, Receptacles, Female Sockets Package - Series 422 Connector Type Socket Contact Type Female Socket Style Board to Cable/Wire Number of Positions	Manufacturer	Preci-Dip
Package - Series 422 Connector Type Socket Contact Type Female Socket Style Board to Cable/Wire Number of Positions 44 Number of Positions Loaded All Pitch - Mating 0.100" (2.54mm) Number of Rows 2 Row Spacing - Mating 0.100" (2.54mm) Mounting Type Through Hole Termination Wire Wrap Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating Flash Insulation Color Black Insulation Height 0.193" (4.90mm) Contact Length - Post 0.370" (9.40mm) Operating Temperature -55°C ~ 125°C	Category	Connectors, Interconnects
Series 422 Connector Type Socket Contact Type Female Socket Style Board to Cable/Wire Number of Positions 44 Number of Positions Loaded All Pitch - Mating 0.100" (2.54mm) Number of Rows 2 Row Spacing - Mating 0.100" (2.54mm) Mounting Type Through Hole Termination Wire Wrap Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating Flash Insulation Color Black Insulation Height 0.193" (4.90mm) Contact Length - Post 0.370" (9.40mm) Operating Temperature -55°C ~ 125°C		Rectangular Connectors - Headers, Receptacles, Female Sockets
Connector TypeSocketContact TypeFemale SocketStyleBoard to Cable/WireNumber of Positions44Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting TypeThrough HoleTerminationWire WrapFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - MatingFlashInsulation ColorBlackInsulation Height0.193" (4.90mm)Contact Length - Post0.370" (9.40mm)Operating Temperature-55°C ~ 125°C	Package	-
Contact TypeFemale SocketStyleBoard to Cable/WireNumber of Positions44Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting TypeThrough HoleTerminationWire WrapFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - MatingFlashInsulation ColorBlackInsulation Height0.193" (4.90mm)Contact Length - Post0.370" (9.40mm)Operating Temperature-55°C ~ 125°C	Series	422
StyleBoard to Cable/WireNumber of Positions44Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting TypeThrough HoleTerminationWire WrapFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - MatingFlashInsulation ColorBlackInsulation Height0.193" (4.90mm)Contact Length - Post0.370" (9.40mm)Operating Temperature-55°C ~ 125°C	Connector Type	Socket
Number of Positions44Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting TypeThrough HoleTerminationWire WrapFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - MatingFlashInsulation ColorBlackInsulation Height0.193" (4.90mm)Contact Length - Post0.370" (9.40mm)Operating Temperature-55°C ~ 125°C	Contact Type	Female Socket
Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting TypeThrough HoleTerminationWire WrapFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - MatingFlashInsulation ColorBlackInsulation Height0.193" (4.90mm)Contact Length - Post0.370" (9.40mm)Operating Temperature-55°C ~ 125°C	Style	Board to Cable/Wire
Pitch - Mating 0.100" (2.54mm) Number of Rows 2 Row Spacing - Mating 0.100" (2.54mm) Mounting Type Through Hole Termination Wire Wrap Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating Flash Insulation Color Black Insulation Height 0.193" (4.90mm) Contact Length - Post 0.370" (9.40mm) Operating Temperature -55°C ~ 125°C	Number of Positions	44
Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting TypeThrough HoleTerminationWire WrapFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - MatingFlashInsulation ColorBlackInsulation Height0.193" (4.90mm)Contact Length - Post0.370" (9.40mm)Operating Temperature-55°C ~ 125°C	Number of Positions Loaded	All
Row Spacing - Mating Mounting Type Through Hole Termination Wire Wrap Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating Insulation Color Black Insulation Height O.193" (4.90mm) Contact Length - Post Operating Temperature -55°C ~ 125°C	Pitch - Mating	0.100" (2.54mm)
Mounting Type Through Hole Wire Wrap Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating Insulation Color Black Insulation Height 0.193" (4.90mm) Contact Length - Post 0.370" (9.40mm) Operating Temperature -55°C ~ 125°C	Number of Rows	2
Termination Wire Wrap Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating Flash Insulation Color Black Insulation Height 0.193" (4.90mm) Contact Length - Post 0.370" (9.40mm) Operating Temperature -55°C ~ 125°C	Row Spacing - Mating	0.100" (2.54mm)
Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating Flash Insulation Color Black Insulation Height 0.193" (4.90mm) Contact Length - Post 0.370" (9.40mm) Operating Temperature -55°C ~ 125°C	Mounting Type	Through Hole
Contact Finish - Mating Contact Finish Thickness - Mating Insulation Color Black Insulation Height 0.193" (4.90mm) Contact Length - Post 0.370" (9.40mm) Operating Temperature -55°C ~ 125°C	Termination	Wire Wrap
Contact Finish Thickness - Mating Flash Insulation Color Black Insulation Height 0.193" (4.90mm) Contact Length - Post 0.370" (9.40mm) Operating Temperature -55°C ~ 125°C	Fastening Type	Push-Pull
Insulation ColorBlackInsulation Height $0.193"$ ($4.90mm$)Contact Length - Post $0.370"$ ($9.40mm$)Operating Temperature -55 °C ~ 125 °C	Contact Finish - Mating	Gold
Insulation Height $0.193''$ (4.90mm) Contact Length - Post $0.370''$ (9.40mm) Operating Temperature $-55^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Contact Finish Thickness - Mating	Flash
Contact Length - Post $0.370" (9.40 \text{mm})$ Operating Temperature $-55^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Insulation Color	Black
Operating Temperature $-55^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Insulation Height	0.193" (4.90mm)
	Contact Length - Post	0.370" (9.40mm)
Material Flammability Rating UL94 V-0	Operating Temperature	-55°C ~ 125°C
	Material Flammability Rating	UL94 V-0

Contact Finish - Post	Tin
Mated Stacking Heights	-
Ingress Protection	-
Features	-
	Report errors?

422-87-244-41-001101 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

422-87-244-41-001101 Payment Methods



















422-87-244-41-001101 Shipping Methods













If you have any question about 422-87-244-41-001101, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com