

43-01229 Information



For Reference Only

Part Number 43-01229 Manufacturer Conec

Category Connectors, Interconnects Circular Connectors

Description CON ETHERNET 100MHZ FML SCKT SLD

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









43-01229 Specifications

Manufacturer Part Number 43-01229 Manufacturer Conec Category Connectors, Interconnects Package - Series 43 Connector Type Receptacle, Female Sockets Number of Positions 4 Shell Size - Insert M12-4 Shell Size, MIL - Mounting Type Panel Mount, Bulkhead; Through Hole, Right Angle Termination Solder Fastening Type Threaded Orientation D Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Copper Zinc Alloy, Nickel Plated Contact Finish Gold Features Board Lock Voltage - Rated 250V Current Rating 4A		
CategoryConnectors, InterconnectsPackage-Series43Connector TypeReceptacle, Female SocketsNumber of Positions4Shell Size - InsertM12-4Shell Size, MIL-Mounting TypePanel Mount, Bulkhead; Through Hole, Right AngleTerminationSolderFastening TypeThreadedOrientationDIngress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishCopper Zinc Alloy, Nickel PlatedContact FinishGoldFeaturesBoard LockVoltage - Rated250VCurrent Rating4A	Manufacturer Part Number	43-01229
Package-Series43Connector TypeReceptacle, Female SocketsNumber of Positions4Shell Size - InsertM12-4Shell Size, MIL-Mounting TypePanel Mount, Bulkhead; Through Hole, Right AngleTerminationSolderFastening TypeThreadedOrientationDIngress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishCopper Zinc Alloy, Nickel PlatedContact FinishGoldFeaturesBoard LockVoltage - Rated250VCurrent Rating4A	Manufacturer	Conec
Package-Series43Connector TypeReceptacle, Female SocketsNumber of Positions4Shell Size - InsertM12-4Shell Size, MIL-Mounting TypePanel Mount, Bulkhead; Through Hole, Right AngleTerminationSolderFastening TypeThreadedOrientationDIngress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishCopper Zinc Alloy, Nickel PlatedContact FinishGoldFeaturesBoard LockVoltage - Rated250VCurrent Rating4A	Category	Connectors, Interconnects
Series43Connector TypeReceptacle, Female SocketsNumber of Positions4Shell Size - InsertM12-4Shell Size, MIL-Mounting TypePanel Mount, Bulkhead; Through Hole, Right AngleTerminationSolderFastening TypeThreadedOrientationDIngress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishCopper Zinc Alloy, Nickel PlatedContact FinishGoldFeaturesBoard LockVoltage - Rated250VCurrent Rating4A		Circular Connectors
Connector Type Receptacle, Female Sockets Number of Positions 4 Shell Size - Insert M12-4 Shell Size, MIL - Mounting Type Panel Mount, Bulkhead; Through Hole, Right Angle Termination Solder Fastening Type Threaded Orientation D Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Copper Zinc Alloy, Nickel Plated Contact Finish Gold Features Board Lock Voltage - Rated 250V Current Rating 4A	Package	-
Number of Positions4Shell Size - InsertM12-4Shell Size, MIL-Mounting TypePanel Mount, Bulkhead; Through Hole, Right AngleTerminationSolderFastening TypeThreadedOrientationDIngress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishCopper Zinc Alloy, Nickel PlatedContact FinishGoldFeaturesBoard LockVoltage - Rated250VCurrent Rating4A	Series	43
Shell Size - Insert Shell Size, MIL - Mounting Type Panel Mount, Bulkhead; Through Hole, Right Angle Termination Solder Fastening Type Threaded Orientation D Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Copper Zinc Alloy, Nickel Plated Contact Finish Gold Features Board Lock Voltage - Rated 250V Current Rating 4A	Connector Type	Receptacle, Female Sockets
Shell Size, MIL Mounting Type Panel Mount, Bulkhead; Through Hole, Right Angle Termination Solder Fastening Type Threaded Orientation D Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Copper Zinc Alloy, Nickel Plated Contact Finish Gold Features Board Lock Voltage - Rated 250V Current Rating 4A	Number of Positions	4
Mounting TypePanel Mount, Bulkhead; Through Hole, Right AngleTerminationSolderFastening TypeThreadedOrientationDIngress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishCopper Zinc Alloy, Nickel PlatedContact FinishGoldFeaturesBoard LockVoltage - Rated250VCurrent Rating4A	Shell Size - Insert	M12-4
Termination Solder Fastening Type Threaded Orientation D Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Copper Zinc Alloy, Nickel Plated Contact Finish Gold Features Board Lock Voltage - Rated 250V Current Rating 4A	Shell Size, MIL	-
Fastening Type Threaded Orientation D Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Copper Zinc Alloy, Nickel Plated Contact Finish Gold Features Board Lock Voltage - Rated 250V Current Rating 4A	Mounting Type	Panel Mount, Bulkhead; Through Hole, Right Angle
Orientation D Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Copper Zinc Alloy, Nickel Plated Contact Finish Gold Features Board Lock Voltage - Rated 250V Current Rating 4A	Termination	Solder
Ingress Protection Shell Material, Finish Copper Zinc Alloy, Nickel Plated Contact Finish Gold Features Board Lock Voltage - Rated Current Rating 1P67 - Dust Tight, Waterproof Copper Zinc Alloy, Nickel Plated Sold 4A	Fastening Type	Threaded
Shell Material, Finish Copper Zinc Alloy, Nickel Plated Contact Finish Gold Features Board Lock Voltage - Rated 250V Current Rating 4A	Orientation	D
Contact Finish Gold Features Board Lock Voltage - Rated 250V Current Rating 4A	Ingress Protection	IP67 - Dust Tight, Waterproof
Features Board Lock Voltage - Rated 250V Current Rating 4A	Shell Material, Finish	Copper Zinc Alloy, Nickel Plated
Voltage - Rated 250V Current Rating 4A	Contact Finish	Gold
Current Rating 4A	Features	Board Lock
	Voltage - Rated	250V
Report errors?	Current Rating	4A
The state of the s		Report errors?

43-01229 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

43-01229 Payment Methods





















43-01229 Shipping Methods













If you have any question about 43-01229, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com