

4304M-101-912 Information

Heisener.com

Part Number 4304M-101-912
Manufacturer Bourns Inc.
Category Resistors

Resistor Networks, Arrays

Description RES ARRAY 3 RES 9.1K OHM 4SIP

Package 4-SIF

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









4304M-101-912 Specifications

Manufacturer Part Number 4304M-101-912 Manufacturer Bourns Inc. Category Resistors Resistor Networks, Arrays Package 4-SIP Series 4300M Circuit Type Bussed Resistance (Ohms) 9.1k Tolerance ±2% Number of Resistors 3 Number of Pins 4 Power Per Element 250mW Temperature Coefficient ±100ppm/°C Operating Temperature -55°C ~ 125°C Applications - Mounting Type Through Hole Package / Case 4-SIP Supplier Device Package 4-SIP Size / Dimension 0.384" L x 0.085" W (9.75mm x 2.16mm) Height - Seated (Max) 0.250" (6.35mm)		
Category Resistors Package 4-SIP Series 4300M Circuit Type Bussed Resistance (Ohms) 9.1k Tolerance ±2% Number of Resistors 3 Number of Pins 4 Power Per Element 250mW Temperature Coefficient ±100ppm/°C Operating Temperature -55°C ~ 125°C Applications - Mounting Type Through Hole Package / Case 4-SIP Supplier Device Package 4-SIP Size / Dimension 0.384" L x 0.085" W (9.75mm x 2.16mm) Height - Seated (Max) 0.250" (6.35mm)	Manufacturer Part Number	4304M-101-912
Package 4-SIP Series 4300M Circuit Type Bussed Resistance (Ohms) 9.1k Tolerance ±2% Number of Resistors 3 Number of Pins 4 Power Per Element 250mW Temperature Coefficient ±100ppm/°C Operating Temperature -55°C ~ 125°C Applications - Mounting Type Through Hole Package / Case 4-SIP Supplier Device Package 4-SIP Size / Dimension 0.384" L x 0.085" W (9.75mm x 2.16mm) Height - Seated (Max) 0.250" (6.35mm)	Manufacturer	Bourns Inc.
Package 4-SIP Series 4300M Circuit Type Bussed Resistance (Ohms) 9.1k Tolerance ±2% Number of Resistors 3 Number of Pins 4 Power Per Element 250mW Temperature Coefficient ±100ppm/°C Operating Temperature -55°C ~ 125°C Applications - Mounting Type Through Hole Package / Case 4-SIP Supplier Device Package 4-SIP Size / Dimension 0.384" L x 0.085" W (9.75mm x 2.16mm) Height - Seated (Max) 0.250" (6.35mm)	Category	Resistors
Series 4300M Circuit Type Bussed Resistance (Ohms) 9.1k Tolerance ±2% Number of Resistors 3 Number of Pins 4 Power Per Element 250mW Temperature Coefficient ±100ppm/°C Operating Temperature -55°C ~ 125°C Applications - Mounting Type Through Hole Package / Case 4-SIP Supplier Device Package 4-SIP Size / Dimension 0.384" L x 0.085" W (9.75mm x 2.16mm) Height - Seated (Max) 0.250" (6.35mm)		Resistor Networks, Arrays
Circuit TypeBussedResistance (Ohms)9.1kTolerance±2%Number of Resistors3Number of Pins4Power Per Element250mWTemperature Coefficient±100ppm/°COperating Temperature-55°C ~ 125°CApplications-Mounting TypeThrough HolePackage / Case4-SIPSupplier Device Package4-SIPSize / Dimension0.384" L x 0.085" W (9.75mm x 2.16mm)Height - Seated (Max)0.250" (6.35mm)	Package	4-SIP
Resistance (Ohms) 9.1k Tolerance ±2% Number of Resistors 3 Number of Pins 4 Power Per Element 250mW Temperature Coefficient ±100ppm/°C Operating Temperature -55°C ~ 125°C Applications - Mounting Type Through Hole Package / Case 4-SIP Supplier Device Package 4-SIP Size / Dimension 0.384" L x 0.085" W (9.75mm x 2.16mm) Height - Seated (Max) 0.250" (6.35mm)	Series	4300M
Tolerance ±2% Number of Resistors 3 Number of Pins 4 Power Per Element 250mW Temperature Coefficient ±100ppm/°C Operating Temperature -55°C ~ 125°C Applications - Mounting Type Through Hole Package / Case 4-SIP Supplier Device Package 4-SIP Size / Dimension 0.384" L x 0.085" W (9.75mm x 2.16mm) Height - Seated (Max) 0.250" (6.35mm)	Circuit Type	Bussed
Number of Resistors Number of Pins 4 Power Per Element 250mW Temperature Coefficient 4100ppm/°C Operating Temperature -55°C ~ 125°C Applications - Mounting Type Through Hole Package / Case 4-SIP Supplier Device Package Size / Dimension 0.384" L x 0.085" W (9.75mm x 2.16mm) Height - Seated (Max) 0.250" (6.35mm)	Resistance (Ohms)	9.1k
Number of Pins 4 Power Per Element 250mW Temperature Coefficient ±100ppm/°C Operating Temperature -55°C ~ 125°C Applications - Mounting Type Through Hole Package / Case 4-SIP Supplier Device Package 4-SIP Size / Dimension 0.384" L x 0.085" W (9.75mm x 2.16mm) Height - Seated (Max) 0.250" (6.35mm)	Tolerance	±2%
Power Per Element 250mW Temperature Coefficient $\pm 100 \text{ppm/}^{\circ}\text{C}$ Operating Temperature $-55^{\circ}\text{C} \sim 125^{\circ}\text{C}$ Applications-Mounting TypeThrough HolePackage / Case $4-\text{SIP}$ Supplier Device Package $4-\text{SIP}$ Size / Dimension $0.384^{\circ}\text{L} \times 0.085^{\circ}\text{W} (9.75 \text{mm} \times 2.16 \text{mm})$ Height - Seated (Max) $0.250^{\circ}\text{(6.35 mm)}$	Number of Resistors	3
Temperature Coefficient ± 100 ppm/°C Operating Temperature -55 °C ~ 125 °C Applications - Mounting Type Through Hole Package / Case 4 -SIP Supplier Device Package 4 -SIP Size / Dimension 0.384 " L x 0.085 " W $(9.75$ mm x 2.16 mm) Height - Seated (Max) 0.250 " $(6.35$ mm)	Number of Pins	4
Operating Temperature -55°C ~ 125°C Applications - Mounting Type Through Hole Package / Case 4-SIP Supplier Device Package 4-SIP Size / Dimension 0.384" L x 0.085" W (9.75mm x 2.16mm) Height - Seated (Max) 0.250" (6.35mm)	Power Per Element	250mW
Applications - Mounting Type Through Hole Package / Case 4-SIP Supplier Device Package 4-SIP Size / Dimension 0.384" L x 0.085" W (9.75mm x 2.16mm) Height - Seated (Max) 0.250" (6.35mm)	Temperature Coefficient	±100ppm/°C
Mounting Type Through Hole Package / Case 4-SIP Supplier Device Package 4-SIP Size / Dimension 0.384" L x 0.085" W (9.75mm x 2.16mm) Height - Seated (Max) 0.250" (6.35mm)	Operating Temperature	-55°C ~ 125°C
Package / Case 4-SIP Supplier Device Package 4-SIP Size / Dimension 0.384" L x 0.085" W (9.75mm x 2.16mm) Height - Seated (Max) 0.250" (6.35mm)	Applications	-
Supplier Device Package 4-SIP Size / Dimension 0.384" L x 0.085" W (9.75mm x 2.16mm) Height - Seated (Max) 0.250" (6.35mm)	Mounting Type	Through Hole
Size / Dimension 0.384" L x 0.085" W (9.75mm x 2.16mm) Height - Seated (Max) 0.250" (6.35mm)	Package / Case	4-SIP
Height - Seated (Max) 0.250" (6.35mm)	Supplier Device Package	4-SIP
	Size / Dimension	0.384" L x 0.085" W (9.75mm x 2.16mm)
	Height - Seated (Max)	0.250" (6.35mm)
Report errors?		Report errors?

4304M-101-912 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

4304M-101-912 Payment Methods



















4304M-101-912 Shipping Methods













If you have any question about 4304M-101-912, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com