

4306M-102-473 Information



For Reference Only

Part Number 4306M-102-473 Manufacturer Bourns Inc. Category Resistors

Resistor Networks, Arrays

Description RES ARRAY 3 RES 47K OHM 6SIP

Package 6-SIF

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









4306M-102-473 Specifications

| Manufacturer Part Number 4306M-102-473 Manufacturer Bourns Inc. Category Resistors Package 6-SIP Series 4300M Circuit Type Isolated Resistance (Ohms) 47k Tolerance ±2% Number of Resistors 3 Number of Pins 6 Power Per Element 400mW Temperature Coefficient ±100ppm/°C Operating Temperature -55°C ~ 125°C Applications - Mounting Type Through Hole Package / Case 6-SIP Supplier Device Package 6-SIP Size / Dimension 0.584" L x 0.085" W (14.83mm x 2.16mm) Height, Sected (Max) 0.250" (6.35mm) | | |
|---|--------------------------|--|
| Category Resistors Package 6-SIP Series 4300M Circuit Type Isolated Resistance (Ohms) 47k Tolerance ±2% Number of Resistors 3 Number of Pins 6 Power Per Element 400mW Temperature Coefficient ±100ppm/°C Operating Temperature -55°C ~ 125°C Applications - Mounting Type Through Hole Package / Case 6-SIP Supplier Device Package 6-SIP Size / Dimension 0.584" L x 0.085" W (14.83mm x 2.16mm) | Manufacturer Part Number | 4306M-102-473 |
| Resistor Networks, Arrays Package 6-SIP Series 4300M Circuit Type Isolated Resistance (Ohms) 47k Tolerance ±2% Number of Resistors 3 Number of Pins 6 Power Per Element 400mW Temperature Coefficient ±100ppm/°C Operating Temperature -55°C ~ 125°C Applications - Mounting Type Through Hole Package / Case 6-SIP Supplier Device Package 6-SIP Size / Dimension 0.584" L x 0.085" W (14.83mm x 2.16mm) | Manufacturer | Bourns Inc. |
| Package 6-SIP Series 4300M Circuit Type Isolated Resistance (Ohms) 47k Tolerance ±2% Number of Resistors 3 Number of Pins 6 Power Per Element 400mW Temperature Coefficient ±100ppm/°C Operating Temperature -55°C ~ 125°C Applications - Mounting Type Through Hole Package / Case 6-SIP Supplier Device Package 6-SIP Size / Dimension 0.584" L x 0.085" W (14.83mm x 2.16mm) | Category | Resistors |
| Series 4300M Circuit Type Isolated Resistance (Ohms) 47k Tolerance ±2% Number of Resistors 3 Number of Pins 6 Power Per Element 400mW Temperature Coefficient ±100ppm/°C Operating Temperature -55°C ~ 125°C Applications - Mounting Type Through Hole Package / Case 6-SIP Supplier Device Package 6-SIP Size / Dimension 0.584" L x 0.085" W (14.83mm x 2.16mm) | | Resistor Networks, Arrays |
| Circuit TypeIsolatedResistance (Ohms)47kTolerance±2%Number of Resistors3Number of Pins6Power Per Element400mWTemperature Coefficient±100ppm/°COperating Temperature-55°C ~ 125°CApplications-Mounting TypeThrough HolePackage / Case6-SIPSupplier Device Package6-SIPSize / Dimension0.584" L x 0.085" W (14.83mm x 2.16mm) | Package | 6-SIP |
| Resistance (Ohms) 47k Tolerance ±2% Number of Resistors 3 Number of Pins 6 Power Per Element 400mW Temperature Coefficient ±100ppm/°C Operating Temperature -55°C ~ 125°C Applications - Mounting Type Through Hole Package / Case 6-SIP Supplier Device Package 6-SIP Size / Dimension 0.584" L x 0.085" W (14.83mm x 2.16mm) | Series | 4300M |
| Tolerance ±2% Number of Resistors 3 Number of Pins 6 Power Per Element 400mW Temperature Coefficient ±100ppm/°C Operating Temperature -55°C ~ 125°C Applications - Mounting Type Through Hole Package / Case 6-SIP Supplier Device Package 6-SIP Size / Dimension 0.584" L x 0.085" W (14.83mm x 2.16mm) | Circuit Type | Isolated |
| Number of Resistors3Number of Pins6Power Per Element400mWTemperature Coefficient±100ppm/°COperating Temperature-55°C ~ 125°CApplications-Mounting TypeThrough HolePackage / Case6-SIPSupplier Device Package6-SIPSize / Dimension0.584" L x 0.085" W (14.83mm x 2.16mm) | Resistance (Ohms) | 47k |
| Number of Pins 6 Power Per Element 400mW Temperature Coefficient ±100ppm/°C Operating Temperature -55°C ~ 125°C Applications - Mounting Type Through Hole Package / Case 6-SIP Supplier Device Package 6-SIP Size / Dimension 6 6 Commonwealth Additional Size (14.83mm x 2.16mm) | Tolerance | ±2% |
| Power Per Element 400mW Temperature Coefficient ±100ppm/°C Operating Temperature -55°C ~ 125°C Applications - Mounting Type Through Hole Package / Case 6-SIP Supplier Device Package 6-SIP Size / Dimension 0.584" L x 0.085" W (14.83mm x 2.16mm) | Number of Resistors | 3 |
| Temperature Coefficient $\pm 100 \text{ppm/}^{\circ}\text{C}$ Operating Temperature $-55^{\circ}\text{C} \sim 125^{\circ}\text{C}$ Applications $-$ Mounting Type Through Hole Package / Case 6-SIP Supplier Device Package 6-SIP Size / Dimension $0.584^{\circ}\text{L} \times 0.085^{\circ}\text{W} (14.83 \text{mm} \times 2.16 \text{mm})$ | Number of Pins | 6 |
| Operating Temperature -55°C ~ 125°C Applications - Mounting Type Through Hole Package / Case 6-SIP Supplier Device Package 6-SIP Size / Dimension 0.584" L x 0.085" W (14.83mm x 2.16mm) | Power Per Element | 400mW |
| Applications - Mounting Type Through Hole Package / Case 6-SIP Supplier Device Package 6-SIP Size / Dimension 0.584" L x 0.085" W (14.83mm x 2.16mm) | Temperature Coefficient | $\pm 100 ppm/^{\circ}C$ |
| Mounting Type Through Hole Package / Case 6-SIP Supplier Device Package 6-SIP Size / Dimension 0.584" L x 0.085" W (14.83mm x 2.16mm) | Operating Temperature | -55°C ~ 125°C |
| Package / Case 6-SIP Supplier Device Package 6-SIP Size / Dimension 0.584" L x 0.085" W (14.83mm x 2.16mm) | Applications | - |
| Supplier Device Package 6-SIP Size / Dimension 0.584" L x 0.085" W (14.83mm x 2.16mm) | Mounting Type | Through Hole |
| Size / Dimension 0.584" L x 0.085" W (14.83mm x 2.16mm) | Package / Case | 6-SIP |
| · · · · · · · · · · · · · · · · · · · | Supplier Device Package | 6-SIP |
| Height Seated (May) 0.250" (6.25mm) | Size / Dimension | 0.584" L x 0.085" W (14.83mm x 2.16mm) |
| 11cigii - Scatcu (Max) 0.230 (0.3311111) | Height - Seated (Max) | 0.250" (6.35mm) |
| Report errors? | | Report errors? |

4306M-102-473 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

4306M-102-473 Payment Methods



















4306M-102-473 Shipping Methods













If you have any question about 4306M-102-473, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com