

43500.2 Information

For Reference Only

Part Number 43500.2

ManufacturerOn Shore Technology Inc.CategoryConnectors, Interconnects

Terminal Blocks - Din Rail, Channel

Description CONN TERM BLK FEED THRU 12-20AWG

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









43500.2 Specifications

Manufacturer Part Number 43500.2 Manufacturer On Shore Technology Inc. Category Connectors, Interconnects Package - Series ZR2.5 Type Feed Through Disconnect Type - Number of Positions 2 Number of Levels 1 Terminal - Width 5.1mm Termination Style Push In, Spring Current - IEC 24A Voltage - IEC 800V Current - UL 27A Voltage - UL 300V Wire Gauge or Range - AWG 12-20 AWG Wire Gauge or Range - mm² 0.5-4mm² Features - Color Beige		
Category Connectors, Interconnects Package	Manufacturer Part Number	43500.2
Package - Series ZR2.5 Type Feed Through Disconnect Type - Number of Positions 2 Number of Levels 1 Terminal - Width 5.1mm Termination Style Push In, Spring Current - IEC 24A Voltage - IEC 800V Current - UL 27A Voltage - UL 300V Wire Gauge or Range - AWG 12-20 AWG Wire Gauge or Range - mm² 0.5-4mm² Features - Color Beige	Manufacturer	On Shore Technology Inc.
Package - Series ZR2.5 Type Feed Through Disconnect Type - Number of Positions 2 Number of Levels 1 Terminal - Width 5.1mm Termination Style Push In, Spring Current - IEC 24A Voltage - IEC 800V Current - UL 27A Voltage - UL 300V Wire Gauge or Range - AWG 12-20 AWG Wire Gauge or Range - mm² 0.5-4mm² Features - Color Beige	Category	Connectors, Interconnects
Series ZR2.5 Type Feed Through Disconnect Type - Number of Positions 2 Number of Levels 1 Terminal - Width 5.1mm Termination Style Push In, Spring Current - IEC 24A Voltage - IEC 800V Current - UL 27A Voltage - UL 300V Wire Gauge or Range - AWG 12-20 AWG Wire Gauge or Range - mm² 0.5-4mm² Features - Color Beige		Terminal Blocks - Din Rail, Channel
Type Feed Through Disconnect Type - Number of Positions 2 Number of Levels 1 Terminal - Width 5.1mm Termination Style Push In, Spring Current - IEC 24A Voltage - IEC 800V Current - UL 27A Voltage - UL 300V Wire Gauge or Range - AWG 12-20 AWG Wire Gauge or Range - mm² 0.5-4mm² Features - Color Beige	Package	-
Disconnect Type-Number of Positions2Number of Levels1Terminal - Width5.1mmTermination StylePush In, SpringCurrent - IEC24AVoltage - IEC800VCurrent - UL27AVoltage - UL300VWire Gauge or Range - AWG12-20 AWGWire Gauge or Range - mm²0.5-4mm²Features-ColorBeige	Series	ZR2.5
Number of Positions2Number of Levels1Terminal - Width5.1 mmTermination StylePush In, SpringCurrent - IEC24AVoltage - IEC800VCurrent - UL27AVoltage - UL300VWire Gauge or Range - AWG12-20 AWGWire Gauge or Range - mm²0.5-4 mm²Features-ColorBeige	Туре	Feed Through
Number of Levels 1 Terminal - Width 5.1mm Termination Style Push In, Spring Current - IEC 24A Voltage - IEC 800V Current - UL 27A Voltage - UL 300V Wire Gauge or Range - AWG 12-20 AWG Wire Gauge or Range - mm² 0.5-4mm² Features - Color Beige	Disconnect Type	-
Terminal - Width Termination Style Push In, Spring Current - IEC 24A Voltage - IEC 800V Current - UL 27A Voltage - UL 300V Wire Gauge or Range - AWG Wire Gauge or Range - mm² Features - Color Beige	Number of Positions	2
Termination Style Current - IEC 24A Voltage - IEC 800V Current - UL 27A Voltage - UL 300V Wire Gauge or Range - AWG Wire Gauge or Range - mm² Features - Color Push In, Spring 24A 800V 800V 800V 27A 300V 300V Beige	Number of Levels	1
Current - IEC 24A Voltage - IEC 800V Current - UL 27A Voltage - UL 300V Wire Gauge or Range - AWG 12-20 AWG Wire Gauge or Range - mm² 0.5-4mm² Features - Color Beige	Terminal - Width	5.1mm
Voltage - IEC800VCurrent - UL27AVoltage - UL300VWire Gauge or Range - AWG12-20 AWGWire Gauge or Range - mm²0.5-4mm²Features-ColorBeige	Termination Style	Push In, Spring
Current - UL 27A Voltage - UL 300V Wire Gauge or Range - AWG 12-20 AWG Wire Gauge or Range - mm² 0.5-4mm² Features - Color Beige	Current - IEC	24A
Voltage - UL300VWire Gauge or Range - AWG12-20 AWGWire Gauge or Range - mm²0.5-4mm²Features-ColorBeige	Voltage - IEC	800V
Wire Gauge or Range - AWG Wire Gauge or Range - mm² Color 12-20 AWG 0.5-4mm² - Beige	Current - UL	27A
Wire Gauge or Range - mm² Features Color Beige	Voltage - UL	300V
Features - Color Beige	Wire Gauge or Range - AWG	12-20 AWG
Color Beige	Wire Gauge or Range - mm ²	0.5-4mm ²
	Features	-
Report errors?	Color	Beige
		Report errors?

43500.2 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

43500.2 Payment Methods



















43500.2 Shipping Methods













If you have any question about 43500.2, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com