

4470R-22J Information

Heisener.com

Part Number 4470R-22J

Manufacturer API Delevan Inc.

Category Inductors, Coils, Chokes

Fixed Inductors

Description FIXED IND 56UH 540MA 1.8 OHM TH

Package Axial

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









4470R-22J Specifications

Manufacturer API Delevan Inc. Category Inductors, Coils, Chokes Fixed Inductors Package Axial Series 4470R Type Molded Material - Core Iron Inductance 56µH Tolerance ±5% Current Rating 540mA Current - Saturation - Shielding Unshielded DC Resistance (DCR) 1.8 Ohm Max Q @ Freq 80 @ 2.5MHz Frequency - Self Resonant 17.6MHz Ratings - Operating Temperature -55°C ~ 125°C
Fixed Inductors Package Axial Series 4470R Type Molded Material - Core Iron Inductance 56μH Tolerance ±5% Current Rating 540mA Current - Saturation - Shielding Unshielded DC Resistance (DCR) 1.8 Ohm Max Q @ Freq 80 @ 2.5MHz Frequency - Self Resonant 17.6MHz Ratings - Operating Temperature -55°C ~ 125°C
Package Axial Series 4470R Type Molded Material - Core Iron Inductance 56μH Tolerance ±5% Current Rating 540mA Current - Saturation - Shielding Unshielded DC Resistance (DCR) 1.8 Ohm Max Q @ Freq 80 @ 2.5MHz Frequency - Self Resonant 17.6MHz Ratings - Operating Temperature -55°C ~ 125°C
Series 4470R Type Molded Material - Core Iron Inductance $56\mu H$ Tolerance $\pm 5\%$ Current Rating $540mA$ Current - Saturation - Shielding Unshielded DC Resistance (DCR) 1.8 Ohm Max Q @ Freq 80 @ 2.5MHz Frequency - Self Resonant 17.6MHz Ratings - Operating Temperature -55° C $\sim 125^{\circ}$ C
$ \begin{array}{cccccccccccccccccccccccccccccccccccc$
$ \begin{array}{cccccccccccccccccccccccccccccccccccc$
Inductance $56\mu H$ Tolerance $\pm 5\%$ Current Rating $540mA$ Current - Saturation-ShieldingUnshieldedDC Resistance (DCR) 1.8 Ohm Max Q @ Freq $80 @ 2.5 \text{MHz}$ Frequency - Self Resonant 17.6MHz Ratings-Operating Temperature $-55^{\circ}\text{C} \sim 125^{\circ}\text{C}$
Tolerance $\pm 5\%$ Current Rating 540mA Current - Saturation - Shielding Unshielded DC Resistance (DCR) 1.8 Ohm Max Q @ Freq $80 \text{ @ } 2.5 \text{MHz}$ Frequency - Self Resonant 17.6MHz Ratings - Operating Temperature $-55^{\circ}\text{C} \sim 125^{\circ}\text{C}$
Current Rating 540mA Current - Saturation - Shielding Unshielded DC Resistance (DCR) 1.8 Ohm Max Q @ Freq 80 @ 2.5MHz Frequency - Self Resonant 17.6MHz Ratings - Operating Temperature -55°C ~ 125°C
Current - Saturation - Shielding Unshielded DC Resistance (DCR) 1.8 Ohm Max Q @ Freq 80 @ 2.5MHz Frequency - Self Resonant 17.6MHz Ratings - Operating Temperature -55°C ~ 125°C
Shielding Unshielded DC Resistance (DCR) 1.8 Ohm Max Q @ Freq 80 @ 2.5MHz Frequency - Self Resonant 17.6MHz Ratings - Operating Temperature -55°C ~ 125°C
DC Resistance (DCR) 1.8 Ohm Max Q @ Freq 80 @ 2.5MHz Frequency - Self Resonant 17.6MHz Ratings - Operating Temperature -55°C ~ 125°C
Q @ Freq 80 @ 2.5MHz Frequency - Self Resonant 17.6MHz Ratings - Operating Temperature $-55^{\circ}\text{C} \sim 125^{\circ}\text{C}$
Frequency - Self Resonant 17.6MHz Ratings - Operating Temperature $-55^{\circ}\text{C} \sim 125^{\circ}\text{C}$
Ratings - Operating Temperature $-55^{\circ}\text{C} \sim 125^{\circ}\text{C}$
Operating Temperature $-55^{\circ}\text{C} \sim 125^{\circ}\text{C}$
Frequency - Test 2.5MHz
Features -
Mounting Type Through Hole
Package / Case Axial
Supplier Device Package -
Size / Dimension 0.310" Dia x 0.910" L (7.87mm x 23.11mm)

Height - Seated (Max) Report errors?

4470R-22J Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

4470R-22J Payment Methods



















4470R-22J Shipping Methods













If you have any question about 4470R-22J, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com