

45024R2C5.5XW

uest a Quote

45024R2C5.5XW Information

Cital levice card her	Part Number	45024R2C5.5XW
	Manufacturer	Littelfuse Inc.
	Category	Circuit Protection Electrical, Specialty Fuses
	Description	FUSE CRTRDGE 450A 5.5KVAC NONSTD
	Package	Cartridge, Non-Standard
		For the pricing/inventory/lead time, please contact
For Reference Only		us Wahaitaa https://www.haisanan.com
		Website: https://www.heisener.com E-mail: salesdept@heisener.com

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



45024R2C5.5XW Specifications

ManufacturerLittelfuse Inc.CategoryCircuit ProtectionElectrical, Specialty FusesPackageCartridge, Non-StandardSeriesPOWR-GARD?Fuse TypeCartridgeCurrent Rating450AVoltage Rating - AC5500V (5.5kV)Voltage Rating - DC-ApplicationsMotor ProtectionFuserIndicatingClassRApprovals-Operating Temperature90KAOperating Temperature80KAMounting TypeHolderPackage / CaseCartidge, Non-StandardSize / Dimension17.875" L x 3.000" W x 6.380" H (454.03mm x 76.20mm x 162.05mm)			
CategoryCircuit ProtectionElectrical, Specialty FusesPackageCartridge, Non-StandardSeriesPOWR-GARD?Fuse TypeCartridgeCurrent Rating450AVoltage Rating - AC5500V (5.5kV)Voltage Rating - DC-ApplicationsMotor ProtectionFeaturesIndicatingClassRApprovals-Operating Temperature80kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension1.875" L x 3.000" Wx 6.380" H (454.03mm x 76.20mm x 162.05mm)	Manufacturer Part Number	45024R2C5.5XW	
Electrical, Specialty FusesPackageCartridge, Non-StandardSeriesPOWR-GARD?Fuse TypeCartridgeCurrent Rating450AVoltage Rating - AC5500V (5.5kV)Voltage Rating - DC-Response Time-ApplicationsMotor ProtectionFeaturesIndicatingClassRApprovals-Operating Temperature80kABreaking Capacity @ Rated Voltage80kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension1.7875" L x 3.000" W x 6.380" H (454.03mm x 76.20mm x 162.05mm)	Manufacturer	Littelfuse Inc.	
PackageCartridge, Non-StandardSeriesPOWR-GARD?Fuse TypeCartridgeCurrent Rating450AVoltage Rating - AC5500V (5.5kV)Voltage Rating - DC-Response Time-ApplicationsMotor ProtectionFeaturesIndicatingClassRApprovals-Operating Type80kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension17.875" L x 3.000" W x 6.380" H (454.03mm x 76.20mm x 162.05mm)	Category	Circuit Protection	
SeriesPOWR-GARD?Fuse TypeCartridgeCurrent Rating450AVoltage Rating - AC5500V (5.5kV)Voltage Rating - DC-Response Time-ApplicationsMotor ProtectionFeaturesIndicatingClassRApprovals-Operating Temperature80kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension17.875" L x 3.000" W x 6.380" H (454.03mm x 76.20mm x 162.05mm)		Electrical, Specialty Fuses	
Fuse TypeCartridgeFuse TypeCartridgeCurrent Rating450AVoltage Rating - AC5500V (5.5kV)Voltage Rating - DC-Response Time-ApplicationsMotor ProtectionFeaturesIndicatingClassRApprovals-Operating Temperature80kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension1.875" L x 3.000" W x 6.380" H (454.03mm x 76.20mm x 162.05mm)	Package	Cartridge, Non-Standard	
Current Rating450AVoltage Rating - AC5500V (5.5kV)Voltage Rating - DC-Response Time-ApplicationsMotor ProtectionFeaturesIndicatingClassRApprovals-Operating Temperature-Breaking Capacity @ Rated Voltage80kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension1.7.875" L x 3.000" W x 6.380" H (454.03mm x 76.20mm x 162.05mm)	Series	POWR-GARD?	
Voltage Rating - AC5500V (5.5kV)Voltage Rating - DC-Response Time-ApplicationsMotor ProtectionFeaturesIndicatingClassRApprovals-Operating Temperature-Breaking Capacity @ Rated Voltage80kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension1.875" L x 3.000" W x 6.380" H (454.03mm x 76.20mm x 162.05mm)	Fuse Type	Cartridge	
Voltage Rating - DC-Response Time-ApplicationsMotor ProtectionFeaturesIndicatingClassRApprovals-Operating Temperature-Breaking Capacity @ Rated Voltage80kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension1.875" L x 3.000" W x 6.380" H (454.03mm x 76.20mm x 162.05mm)	Current Rating	450A	
Response Time-ApplicationsMotor ProtectionFeaturesIndicatingClassRApprovals-Operating Temperature-Breaking Capacity @ Rated Voltage80kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension1.875" L x 3.000" W x 6.380" H (454.03mm x 76.20mm x 162.05mm)	Voltage Rating - AC	5500V (5.5kV)	
ApplicationsMotor ProtectionFeaturesIndicatingClassRApprovals-Operating Temperature-Breaking Capacity @ Rated Voltage80kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension17.875" L x 3.000" W x 6.380" H (454.03mm x 76.20mm x 162.05mm)	Voltage Rating - DC	-	
IndicatingFeaturesIndicatingClassRApprovals-Operating Temperature-Breaking Capacity @ Rated Voltage80kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension17.875" L x 3.000" W x 6.380" H (454.03mm x 76.20mm x 162.05mm)	Response Time	_	
ClassRApprovals-Operating Temperature-Breaking Capacity @ Rated Voltage80kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension17.875" L x 3.000" W x 6.380" H (454.03mm x 76.20mm x 162.05mm)	Applications	Motor Protection	
Approvals-Operating Temperature-Breaking Capacity @ Rated Voltage80kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension17.875" L x 3.000" W x 6.380" H (454.03mm x 76.20mm x 162.05mm)	Features	Indicating	
Operating Temperature-Breaking Capacity @ Rated Voltage80kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension17.875" L x 3.000" W x 6.380" H (454.03mm x 76.20mm x 162.05mm)	Class	R	
Breaking Capacity @ Rated Voltage80kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension17.875" L x 3.000" W x 6.380" H (454.03mm x 76.20mm x 162.05mm)	Approvals	-	
Mounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension17.875" L x 3.000" W x 6.380" H (454.03mm x 76.20mm x 162.05mm)	Operating Temperature	-	
Package / CaseCartridge, Non-StandardSize / Dimension17.875" L x 3.000" W x 6.380" H (454.03mm x 76.20mm x 162.05mm)	Breaking Capacity @ Rated Voltage	80kA	
Size / Dimension 17.875" L x 3.000" W x 6.380" H (454.03mm x 76.20mm x 162.05mm)	Mounting Type	Holder	
	Package / Case	Cartridge, Non-Standard	
Report errors?	Size / Dimension	17.875" L x 3.000" W x 6.380" H (454.03mm x 76.20mm x 162.05mm)	
		Report errors?	

45024R2C5.5XW Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE EUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

45024R2C5.5XW Payment Methods



45024R2C5.5XW Shipping Methods



If you have any question about 45024R2C5.5XW, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com