

450MXC150MEFCSN22X45

450MXC150MEFCSN22X45 Information



For Reference Only

Part Number 450MXC150MEFCSN22X45

Manufacturer Rubycon
Category Capacitors

Aluminum Electrolytic Capacitors

Description CAP ALUM 150UF 20% 450V SNAP

Package Radial, Can - Snap-In

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









450MXC150MEFCSN22X45 Specifications

Manufacturer Part Number450MXC150MEFCSN22X45ManufacturerRubyconCategoryCapacitorsPackageRadial, Can - Snap-InSeriesMXCCapacitance150μFTolerance±20%Voltage - Rated450VESR (Equivalent Series Resistance)-Lifetime @ Temp.3000 Hrs @ 105°COperating Temperature-25°C ~ 105°CPolarization-ApplicationsGeneral PurposeRipple Current - Low Frequency880mA @ 120HzRipple Current - High Frequency1.232A @ 10kHz	*	
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, Can - Snap-InSeriesMXCCapacitance $150\mu F$ Tolerance $\pm 20\%$ Voltage - Rated $450V$ ESR (Equivalent Series Resistance)-Lifetime @ Temp. $3000 Hrs @ 105^{\circ}C$ Operating Temperature $-25^{\circ}C \sim 105^{\circ}C$ Polarization-ApplicationsGeneral PurposeRipple Current - Low Frequency $880mA @ 120Hz$	Manufacturer Part Number	450MXC150MEFCSN22X45
PackageRadial, Can - Snap-InSeriesMXCCapacitance150μFTolerance±20%Voltage - Rated450VESR (Equivalent Series Resistance)-Lifetime @ Temp.3000 Hrs @ 105°COperating Temperature-25°C ~ 105°CPolarization-ApplicationsGeneral PurposeRipple Current - Low Frequency880mA @ 120Hz	Manufacturer	Rubycon
PackageRadial, Can - Snap-InSeriesMXCCapacitance $150\mu F$ Tolerance $\pm 20\%$ Voltage - Rated $450V$ ESR (Equivalent Series Resistance)-Lifetime @ Temp. $3000 \text{ Hrs } @ 105 ^{\circ}\text{C}$ Operating Temperature $-25 ^{\circ}\text{C} \sim 105 ^{\circ}\text{C}$ Polarization-ApplicationsGeneral PurposeRipple Current - Low Frequency $880\text{mA} @ 120\text{Hz}$	Category	Capacitors
SeriesMXCCapacitance $150\mu F$ Tolerance $\pm 20\%$ Voltage - Rated $450V$ ESR (Equivalent Series Resistance)-Lifetime @ Temp. $3000 \text{ Hrs } @ 105^{\circ}\text{C}$ Operating Temperature $-25^{\circ}\text{C} \sim 105^{\circ}\text{C}$ Polarization-ApplicationsGeneral PurposeRipple Current - Low Frequency $880\text{mA} @ 120\text{Hz}$		Aluminum Electrolytic Capacitors
Capacitance150μFTolerance $\pm 20\%$ Voltage - Rated $450V$ ESR (Equivalent Series Resistance)-Lifetime @ Temp. $3000 \text{ Hrs @ } 105^{\circ}\text{C}$ Operating Temperature $-25^{\circ}\text{C} \sim 105^{\circ}\text{C}$ Polarization-ApplicationsGeneral PurposeRipple Current - Low Frequency $880\text{mA @ } 120\text{Hz}$	Package	Radial, Can - Snap-In
Tolerance ±20% Voltage - Rated 450V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 3000 Hrs @ 105°C Operating Temperature -25°C ~ 105°C Polarization - Applications General Purpose Ripple Current - Low Frequency 880mA @ 120Hz	Series	MXC
Voltage - Rated 450V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 3000 Hrs @ 105°C Operating Temperature -25°C ~ 105°C Polarization - Applications General Purpose Ripple Current - Low Frequency 880mA @ 120Hz	Capacitance	150μF
ESR (Equivalent Series Resistance) Lifetime @ Temp. 3000 Hrs @ 105°C Operating Temperature -25°C ~ 105°C Polarization - Applications General Purpose Ripple Current - Low Frequency 880mA @ 120Hz	Tolerance	±20%
Lifetime @ Temp. 3000 Hrs @ 105°C Operating Temperature -25°C ~ 105°C Polarization - Applications General Purpose Ripple Current - Low Frequency 880mA @ 120Hz	Voltage - Rated	450V
Operating Temperature -25°C ~ 105°C Polarization - Applications General Purpose Ripple Current - Low Frequency 880mA @ 120Hz	ESR (Equivalent Series Resistance)	-
Polarization - Applications General Purpose Ripple Current - Low Frequency 880mA @ 120Hz	Lifetime @ Temp.	3000 Hrs @ 105°C
Applications General Purpose Ripple Current - Low Frequency 880mA @ 120Hz	Operating Temperature	-25°C ~ 105°C
Ripple Current - Low Frequency 880mA @ 120Hz	Polarization	-
	Applications	General Purpose
Ripple Current - High Frequency 1.232A @ 10kHz	Ripple Current - Low Frequency	880mA @ 120Hz
	Ripple Current - High Frequency	1.232A @ 10kHz
Impedance -	Impedance	-
Lead Spacing 0.394" (10.00mm)	Lead Spacing	0.394" (10.00mm)
Size / Dimension 0.866" Dia (22.00mm)	Size / Dimension	0.866" Dia (22.00mm)
Height - Seated (Max) 1.850" (47.00mm)	Height - Seated (Max)	1.850" (47.00mm)
Surface Mount Land Size -	Surface Mount Land Size	-
Mounting Type Through Hole	Mounting Type	Through Hole
Package / Case Radial, Can - Snap-In	Package / Case	Radial, Can - Snap-In
Report errors?		Report errors?

450MXC150MEFCSN22X45 Guarantees



Ouality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

450MXC150MEFCSN22X45 Payment Methods



















450MXC150MEFCSN22X45 Shipping Methods













If you have any question about 450MXC150MEFCSN22X45, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com