



450R11C Information

www lisener.dom

Part Number 450R11C Manufacturer Eaton

Category Circuit Protection

Electrical, Specialty Fuses

Description FUSE CRTRDGE 450A 600VAC/250VDC

Package Cylindrical, Blade Terminal (Bolt)

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









450R11C Specifications

| Manufacturer Part Number450R11CManufacturerEatonCategoryCircuit ProtectionPackageCylindrical, Specialty FusesPackageCylindrical, Blade Terminal (Bolt)Series-Fuse TypeCartridgeCurrent Rating450AVoltage Rating - AC600VVoltage Rating - DC250VResponse Time-ApplicationsElectrical, IndustrialFeatures-Class-ApprovalsCE, CSAOperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension2.874" Dia x 3.189" L (73.00mm x 81.00mm) | | |
|--|-----------------------------------|---|
| CategoryCircuit ProtectionBectrical, Specialty FusesPackageCylindrical, Blade Terminal (Bolt)Series-Fuse TypeCartridgeCurrent Rating450AVoltage Rating - AC600VVoltage Rating - DC250VResponse Time-ApplicationsElectrical, IndustrialFeatures-Class-ApprovalsCE, CSAOperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension2.874" Dia x 3.189" L (73.00mm x 81.00mm) | Manufacturer Part Number | 450R11C |
| Electrical, Specialty Fuses Package Cylindrical, Blade Terminal (Bolt) Series - Fuse Type Cartridge Current Rating Voltage Rating - AC Voltage Rating - DC Response Time Applications Electrical, Industrial Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension Electrical, Industrial Features - CE, CSA Operating Temperature - Breaking Capacity @ Rated Voltage CUIndrical, Blade Terminal (Bolt) Size / Dimension Electrical, Industrial Features - CE, CSA CUIndrical, Blade Terminal (Bolt) Size / Dimension Electrical, Industrial Features - CE, CSA CUIndrical, Blade Terminal (Bolt) Size / Dimension | Manufacturer | Eaton |
| PackageCylindrical, Blade Terminal (Bolt)Series-Fuse TypeCartridgeCurrent Rating450AVoltage Rating - AC600VVoltage Rating - DC250VResponse Time-ApplicationsElectrical, IndustrialFeatures-Class-ApprovalsCE, CSAOperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension2.874" Dia x 3.189" L (73.00mm x 81.00mm) | Category | Circuit Protection |
| Series-Fuse TypeCartridgeCurrent Rating450AVoltage Rating - AC600VVoltage Rating - DC250VResponse Time-ApplicationsElectrical, IndustrialFeatures-Class-ApprovalsCE, CSAOperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension2.874" Dia x 3.189" L (73.00mm x 81.00mm) | | Electrical, Specialty Fuses |
| Fuse Type Current Rating 450A Voltage Rating - AC 600V Voltage Rating - DC 250V Response Time - Applications Electrical, Industrial Features - Class - Approvals CE, CSA Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension Cartridge 600V Cartridge A50A Cetrical, Industrial - CE, CSA Colorating Temperature - Bolt Mount Cylindrical, Blade Terminal (Bolt) Size / Dimension Cartridge A50A Coverating Capacity @ Rated Voltage Capacity @ Rated Voltage Cylindrical, Blade Terminal (Bolt) Size / Dimension Capacity @ Rated Voltage Capacity @ Rated Voltage Cylindrical, Blade Terminal (Bolt) | Package | Cylindrical, Blade Terminal (Bolt) |
| Current Rating 450A Voltage Rating - AC 600V Voltage Rating - DC 250V Response Time - Applications Electrical, Industrial Features - Class - Approvals CE, CSA Operating Temperature - Breaking Capacity @ Rated Voltage 200kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 2800V | Series | - |
| Voltage Rating - AC Voltage Rating - DC 250V Response Time - Applications Electrical, Industrial Features - Class - Approvals CE, CSA Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 600V 6 | Fuse Type | Cartridge |
| Voltage Rating - DC Response Time - Applications Electrical, Industrial Features - Class - Approvals CE, CSA Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Size / Dimension 250V 250V 250V 260V 260V 260V 260V 260V 260V 260V 26 | Current Rating | 450A |
| Response Time - Applications Electrical, Industrial - Class - Class - CE, CSA - CE, CS | Voltage Rating - AC | 600V |
| Applications Electrical, Industrial Features - Class - Approvals CE, CSA Operating Temperature - Breaking Capacity @ Rated Voltage 200kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 2.874" Dia x 3.189" L (73.00mm x 81.00mm) | Voltage Rating - DC | 250V |
| Features - Class - CE, CSA Approvals CE, CSA Operating Temperature - Breaking Capacity @ Rated Voltage 200kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 2.874" Dia x 3.189" L (73.00mm x 81.00mm) | Response Time | - |
| Class - Approvals CE, CSA Operating Temperature - Breaking Capacity @ Rated Voltage 200kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 2.874" Dia x 3.189" L (73.00mm x 81.00mm) | Applications | Electrical, Industrial |
| Approvals CE, CSA Operating Temperature - Breaking Capacity @ Rated Voltage Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension CE, CSA CURL CASA CURL CASA CONCAR CE, CSA CONCAR CONCAR CONCAR CONCAR CASA CYL CASA CYSA | Features | - |
| Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 2.874" Dia x 3.189" L (73.00mm x 81.00mm) | Class | - |
| Breaking Capacity @ Rated Voltage 200kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 2.874" Dia x 3.189" L (73.00mm x 81.00mm) | Approvals | CE, CSA |
| Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 2.874" Dia x 3.189" L (73.00mm x 81.00mm) | Operating Temperature | - |
| Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 2.874" Dia x 3.189" L (73.00mm x 81.00mm) | Breaking Capacity @ Rated Voltage | 200kA |
| Size / Dimension 2.874" Dia x 3.189" L (73.00mm x 81.00mm) | Mounting Type | Bolt Mount |
| , , , , , , , , , , , , , , , , , , , | Package / Case | Cylindrical, Blade Terminal (Bolt) |
| Report errors? | Size / Dimension | 2.874" Dia x 3.189" L (73.00mm x 81.00mm) |
| I. | | Report errors? |

450R11C Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

450R11C Payment Methods





















450R11C Shipping Methods













If you have any question about 450R11C, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com