

## 4515DO-SS5AI005GP

#### 4515DO-SS5AI005GP Information



For Reference Only

Part Number 4515DO-SS5AI005GP

Manufacturer TE Connectivity Measurement Specialties

Category Sensors, Transducers

Pressure Sensors, Transducers

**Description** SENSOR PRESS GAUGE 5" H2O 8DIP

Package 8-DIP Module

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# 4515DO-SS5AI005GP Specifications

Manufacturer Part Number       4515DO-SS5AI005GP         Manufacturer       TE Connectivity Measurement Specialties         Category       Sensors, Transducers         Package       8-DIP Module         Series       -         Pressure Type       Vented Gauge         Operating Pressure       0.18 PSI (1.25 kPa)         Output Type       I2C         Output       14 b         Accuracy       ±0.25%         Voltage - Supply       5V         Port Size       Male - 0.14" (3.56mm) Tube         Port Style       Barbed         Features       Temperature Compensated         Termination Style       PC Pin         Maximum Pressure       10 PSI (68.95 kPa)         Operating Temperature       -10°C ~ 85°C         Package / Case       8-DIP Module         Supplier Device Package		
CategorySensors, TransducersPackage8-DIP ModuleSeries-Pressure TypeVented GaugeOperating Pressure0.18 PSI (1.25 kPa)Output TypeI2COutput14 bAccuracy±0.25%Voltage - Supply5VPort SizeMale - 0.14" (3.56mm) TubePort StyleBarbedFeaturesTemperature CompensatedTermination StylePC PinMaximum Pressure10 PSI (68.95 kPa)Operating Temperature-10°C ~ 85°CPackage / Case8-DIP ModuleSupplier Device Package-	Manufacturer Part Number	4515DO-SS5AI005GP
Package 8-DIP Module Series - Pressure Type Vented Gauge Operating Pressure Output Type 12C Output 14 b Accuracy ±0.25% Voltage - Supply 5V Port Size Male - 0.14" (3.56mm) Tube Port Style Barbed Features Tempination Style PC Pin Maximum Pressure 10 PSI (68.95 kPa) Operating Temperature Package 1-10°C ~ 85°C Package / Case 8-DIP Module Supplier Device Package	Manufacturer	TE Connectivity Measurement Specialties
Package         8-DIP Module           Series         -           Pressure Type         Vented Gauge           Operating Pressure         0.18 PSI (1.25 kPa)           Output Type         12C           Output         14 b           Accuracy         ±0.25%           Voltage - Supply         5V           Port Size         Male - 0.14" (3.56mm) Tube           Port Style         Barbed           Features         Temperature Compensated           Termination Style         PC Pin           Maximum Pressure         10 PSI (68.95 kPa)           Operating Temperature         -10°C ~ 85°C           Package / Case         8-DIP Module           Supplier Device Package         -	Category	Sensors, Transducers
Series         -           Pressure Type         Vented Gauge           Operating Pressure         0.18 PSI (1.25 kPa)           Output Type         12C           Output         14 b           Accuracy         ±0.25%           Voltage - Supply         5V           Port Size         Male - 0.14" (3.56mm) Tube           Port Style         Barbed           Features         Temperature Compensated           Termination Style         PC Pin           Maximum Pressure         10 PSI (68.95 kPa)           Operating Temperature         -10°C ~ 85°C           Package / Case         8-DIP Module           Supplier Device Package         -		Pressure Sensors, Transducers
Pressure Type Vented Gauge Operating Pressure 0.18 PSI (1.25 kPa) Output Type I2C Output 14 b Accuracy ±0.25% Voltage - Supply 5V Port Size Male - 0.14" (3.56mm) Tube Port Style Barbed Features Temperature Compensated Termination Style PC Pin Maximum Pressure 10 PSI (68.95 kPa) Operating Temperature -10°C ~ 85°C Package / Case 8-DIP Module Supplier Device Package	Package	8-DIP Module
Operating Pressure Output Type I2C Output 14 b Accuracy ±0.25% Voltage - Supply Port Size Male - 0.14" (3.56mm) Tube Port Style Barbed Features Temperature Compensated Termination Style Maximum Pressure 10 PSI (68.95 kPa) Operating Temperature Package / Case Supplier Device Package -  0.18 PSI (1.25 kPa)  0.18 PSI (1.25 kPa)  14 b  14 b  14 b  14 b  16 c  17 c  18 c  19 c  10 PSI (68.95 kPa)  -10°C ~ 85°C  8-DIP Module  10 PSI (68.95 kPa)  -10°C ~ 85°C	Series	-
Output TypeI2COutput14 bAccuracy±0.25%Voltage - Supply5VPort SizeMale - 0.14" (3.56mm) TubePort StyleBarbedFeaturesTemperature CompensatedTermination StylePC PinMaximum Pressure10 PSI (68.95 kPa)Operating Temperature-10°C ~ 85°CPackage / Case8-DIP ModuleSupplier Device Package-	Pressure Type	Vented Gauge
Output         14 b           Accuracy         ±0.25%           Voltage - Supply         5V           Port Size         Male - 0.14" (3.56mm) Tube           Port Style         Barbed           Features         Temperature Compensated           Termination Style         PC Pin           Maximum Pressure         10 PSI (68.95 kPa)           Operating Temperature         -10°C ~ 85°C           Package / Case         8-DIP Module           Supplier Device Package         -	Operating Pressure	0.18 PSI (1.25 kPa)
Accuracy ±0.25%  Voltage - Supply 5V  Port Size Male - 0.14" (3.56mm) Tube  Port Style Barbed  Features Temperature Compensated  Termination Style PC Pin  Maximum Pressure 10 PSI (68.95 kPa)  Operating Temperature -10°C ~ 85°C  Package / Case 8-DIP Module  Supplier Device Package -	Output Type	12C
Voltage - Supply  Fort Size  Male - 0.14" (3.56mm) Tube  Barbed  Features  Temperature Compensated  Termination Style  PC Pin  Maximum Pressure  10 PSI (68.95 kPa)  Operating Temperature  -10°C ~ 85°C  Package / Case  8-DIP Module  Supplier Device Package  -	Output	14 b
Port Size Male - 0.14" (3.56mm) Tube  Port Style Barbed  Features Temperature Compensated  Termination Style PC Pin  Maximum Pressure 10 PSI (68.95 kPa)  Operating Temperature -10°C ~ 85°C  Package / Case 8-DIP Module  Supplier Device Package -	Accuracy	±0.25%
Port Style Barbed  Features Temperature Compensated  Termination Style PC Pin  Maximum Pressure 10 PSI (68.95 kPa)  Operating Temperature -10°C ~ 85°C  Package / Case 8-DIP Module  Supplier Device Package -	Voltage - Supply	5V
Features Temperature Compensated  Termination Style PC Pin  Maximum Pressure 10 PSI (68.95 kPa)  Operating Temperature -10°C ~ 85°C  Package / Case 8-DIP Module  Supplier Device Package -	Port Size	Male - 0.14" (3.56mm) Tube
Termination Style PC Pin  Maximum Pressure 10 PSI (68.95 kPa)  Operating Temperature -10°C ~ 85°C  Package / Case 8-DIP Module  Supplier Device Package -	Port Style	Barbed
Maximum Pressure  10 PSI (68.95 kPa)  Operating Temperature  -10°C ~ 85°C  Package / Case  8-DIP Module  Supplier Device Package  -	Features	Temperature Compensated
Operating Temperature -10°C ~ 85°C  Package / Case 8-DIP Module  Supplier Device Package -	Termination Style	PC Pin
Package / Case 8-DIP Module Supplier Device Package -	Maximum Pressure	10 PSI (68.95 kPa)
Supplier Device Package -	Operating Temperature	-10°C ~ 85°C
	Package / Case	8-DIP Module
Report errors?	Supplier Device Package	-
100000		Report errors?

#### 4515DO-SS5AI005GP Guarantees



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### **4515DO-SS5AI005GP Payment Methods**



















## 4515DO-SS5AI005GP Shipping Methods













If you have any question about 4515DO-SS5AI005GP, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com