



4540B152K103LE Information

Heisener.com

4540B152K103LE Part Number Manufacturer Knowles Novacap

Category Capacitors

Ceramic Capacitors

Description CAP RADIAL 4540,1500PF,10KV, 10%

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









4540B152K103LE Specifications

| Manufacturer Part Number 4540B152K103LE Manufacturer Knowles Novacap Category Capacitors Package Radial Series - Capacitance 1500pF Tolerance ±10% Voltage - Rated 10000V (10kV) Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features High Voltage Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.598" L x 0.402" W (15.20mm x 10.20mm) Height - Seated (Max) 0.676" (17.18mm) Thickness (Max) - Lead Spacing 0.480" (12.20mm) Lead Style Straight | | |
|---|--------------------------|---|
| Category Capacitors Package Radial Series - Capacitance 1500pF Tolerance ±10% Voltage - Rated 10000V (10kV) Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features High Voltage Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.598" L x 0.402" W (15.20mm x 10.20mm) Height - Seated (Max) 0.676" (17.18mm) Thickness (Max) - Lead Spacing 0.480" (12.20mm) Lead Style Straight | Manufacturer Part Number | 4540B152K103LE |
| Package Radial Series - Capacitance 1500pF Tolerance ±10% Voltage - Rated 10000V (10kV) Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features High Voltage Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.598" L x 0.402" W (15.20mm x 10.20mm) Height - Seated (Max) 0.676" (17.18mm) Thickness (Max) - Lead Spacing 0.480" (12.20mm) Lead Style Straight | Manufacturer | Knowles Novacap |
| Package Radial Series - Capacitance 1500pF Tolerance ±10% Voltage - Rated 10000V (10kV) Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features High Voltage Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.598" L x 0.402" W (15.20mm x 10.20mm) Height - Seated (Max) 0.676" (17.18mm) Thickness (Max) - Lead Spacing 0.480" (12.20mm) Lead Style Straight | Category | Capacitors |
| Series - Capacitance 1500pF Tolerance ±10% Voltage - Rated 10000V (10kV) Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features High Voltage Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.598" L x 0.402" W (15.20mm x 10.20mm) Height - Seated (Max) 0.676" (17.18mm) Thickness (Max) - Lead Spacing 0.480" (12.20mm) Lead Style Straight | | Ceramic Capacitors |
| Capacitance 1500pF Tolerance ±10% Voltage - Rated 10000V (10kV) Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features High Voltage Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.598" L x 0.402" W (15.20mm x 10.20mm) Height - Seated (Max) 0.676" (17.18mm) Thickness (Max) - Lead Spacing 0.480" (12.20mm) Lead Style Straight | Package | Radial |
| Tolerance±10%Voltage - Rated10000V (10kV)Temperature CoefficientX7ROperating Temperature-55°C ~ 125°CFeaturesHigh VoltageRatings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.598" L x 0.402" W (15.20mm x 10.20mm)Height - Seated (Max)0.676" (17.18mm)Thickness (Max)-Lead Spacing0.480" (12.20mm)Lead StyleStraight | Series | - |
| Voltage - Rated10000V (10kV)Temperature CoefficientX7ROperating Temperature-55°C ~ 125°CFeaturesHigh VoltageRatings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.598" L x 0.402" W (15.20mm x 10.20mm)Height - Seated (Max)0.676" (17.18mm)Thickness (Max)-Lead Spacing0.480" (12.20mm)Lead StyleStraight | Capacitance | 1500pF |
| Temperature CoefficientX7ROperating Temperature-55°C ~ 125°CFeaturesHigh VoltageRatings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.598" L x 0.402" W (15.20mm x 10.20mm)Height - Seated (Max)0.676" (17.18mm)Thickness (Max)-Lead Spacing0.480" (12.20mm)Lead StyleStraight | Tolerance | ±10% |
| Operating Temperature-55°C ~ 125°CFeaturesHigh VoltageRatings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.598" L x 0.402" W (15.20mm x 10.20mm)Height - Seated (Max)0.676" (17.18mm)Thickness (Max)-Lead Spacing0.480" (12.20mm)Lead StyleStraight | Voltage - Rated | 10000V (10kV) |
| Features High Voltage Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.598" L x 0.402" W (15.20mm x 10.20mm) Height - Seated (Max) 0.676" (17.18mm) Thickness (Max) - Lead Spacing 0.480" (12.20mm) Lead Style Straight | Temperature Coefficient | X7R |
| Ratings - General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.598" L x 0.402" W (15.20mm x 10.20mm) Height - Seated (Max) 0.676" (17.18mm) Thickness (Max) - Lead Spacing 0.480" (12.20mm) Lead Style Straight | Operating Temperature | -55°C ~ 125°C |
| Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.598" L x 0.402" W (15.20mm x 10.20mm) Height - Seated (Max) 0.676" (17.18mm) Thickness (Max) - Lead Spacing 0.480" (12.20mm) Lead Style Straight | Features | High Voltage |
| Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.598" L x 0.402" W (15.20mm x 10.20mm) Height - Seated (Max) 0.676" (17.18mm) Thickness (Max) - Lead Spacing 0.480" (12.20mm) Lead Style Straight | Ratings | - |
| Mounting Type Through Hole Package / Case Radial Size / Dimension 0.598" L x 0.402" W (15.20mm x 10.20mm) Height - Seated (Max) 0.676" (17.18mm) Thickness (Max) - Lead Spacing 0.480" (12.20mm) Lead Style Straight | Applications | General Purpose |
| Package / Case Radial Size / Dimension 0.598" L x 0.402" W (15.20mm x 10.20mm) Height - Seated (Max) 0.676" (17.18mm) Thickness (Max) - Lead Spacing 0.480" (12.20mm) Lead Style Straight | Failure Rate | - |
| Size / Dimension 0.598" L x 0.402" W (15.20mm x 10.20mm) Height - Seated (Max) 0.676" (17.18mm) Thickness (Max) - Lead Spacing 0.480" (12.20mm) Lead Style Straight | Mounting Type | Through Hole |
| Height - Seated (Max) 0.676" (17.18mm) Thickness (Max) - Lead Spacing 0.480" (12.20mm) Lead Style Straight | Package / Case | Radial |
| Thickness (Max) Lead Spacing 0.480" (12.20mm) Lead Style Straight | Size / Dimension | 0.598" L x 0.402" W (15.20mm x 10.20mm) |
| Lead Spacing0.480" (12.20mm)Lead StyleStraight | Height - Seated (Max) | 0.676" (17.18mm) |
| Lead Style Straight | Thickness (Max) | - |
| | Lead Spacing | 0.480" (12.20mm) |
| Report errors? | Lead Style | Straight |
| • | | Report errors? |

4540B152K103LE Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

4540B152K103LE Payment Methods



















4540B152K103LE Shipping Methods













If you have any question about 4540B152K103LE, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com