



### 4605M-101-222LF Information

**Part Number** 4605M-101-222LF

Manufacturer Bourns Inc.
Category Resistors

Resistor Networks, Arrays

**Description** RES ARRAY 4 RES 2.2K OHM 5SIP

Package 5-SIF

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# 4605M-101-222LF Specifications

Manufacturer Part Number4605M-101-222LFManufacturerBourns Inc.CategoryResistorsPackage5-SIPSeries4600MCircuit TypeBussedResistance (Ohms)2.2kTolerance±2%Number of Resistors4Number of Pins5Power Per Element250mWTemperature Coefficient±100ppm/°COperating Temperature-55°C ~ 125°CApplications-Mounting TypeThrough Hole		
CategoryResistorsResistor Networks, ArraysPackage5-SIPSeries4600MCircuit TypeBussedResistance (Ohms)2.2kTolerance±2%Number of Resistors4Number of Pins5Power Per Element250mWTemperature Coefficient±100ppm/°COperating Temperature-55°C ~ 125°CApplications-	Manufacturer Part Number	4605M-101-222LF
Resistor Networks, Arrays           Package         5-SIP           Series         4600M           Circuit Type         Bussed           Resistance (Ohms)         2.2k           Tolerance         ±2%           Number of Resistors         4           Number of Pins         5           Power Per Element         250mW           Temperature Coefficient         ±100ppm/°C           Operating Temperature         -55°C ~ 125°C           Applications         -	Manufacturer	Bourns Inc.
Package5-SIPSeries4600MCircuit TypeBussedResistance (Ohms)2.2kTolerance±2%Number of Resistors4Number of Pins5Power Per Element250mWTemperature Coefficient±100ppm/°COperating Temperature-55°C ~ 125°CApplications-	Category	Resistors
Series $4600M$ Circuit TypeBussedResistance (Ohms) $2.2k$ Tolerance $\pm 2\%$ Number of Resistors $4$ Number of Pins $5$ Power Per Element $250mW$ Temperature Coefficient $\pm 100ppm/^{\circ}C$ Operating Temperature $-55^{\circ}C \sim 125^{\circ}C$ Applications $-$		Resistor Networks, Arrays
Circuit TypeBussedResistance (Ohms) $2.2k$ Tolerance $\pm 2\%$ Number of Resistors $4$ Number of Pins $5$ Power Per Element $250mW$ Temperature Coefficient $\pm 100ppm/^{\circ}C$ Operating Temperature $-55^{\circ}C \sim 125^{\circ}C$ Applications $-$	Package	5-SIP
Resistance (Ohms)  2.2k  Tolerance $\pm 2\%$ Number of Resistors  4  Number of Pins  5  Power Per Element  250mW  Temperature Coefficient $\pm 100$ ppm/°C  Operating Temperature  -55°C ~ 125°C  Applications  -	Series	4600M
Tolerance $\pm 2\%$ Number of Resistors4Number of Pins5Power Per Element $250 \text{mW}$ Temperature Coefficient $\pm 100 \text{ppm/°C}$ Operating Temperature $-55^{\circ}\text{C} \sim 125^{\circ}\text{C}$ Applications-	Circuit Type	Bussed
Number of Resistors4Number of Pins5Power Per Element $250 \text{mW}$ Temperature Coefficient $\pm 100 \text{ppm/°C}$ Operating Temperature $-55^{\circ}\text{C} \sim 125^{\circ}\text{C}$ Applications-	Resistance (Ohms)	2.2k
Number of Pins5Power Per Element $250 \text{mW}$ Temperature Coefficient $\pm 100 \text{ppm/°C}$ Operating Temperature $-55^{\circ}\text{C} \sim 125^{\circ}\text{C}$ Applications-	Tolerance	±2%
Power Per Element $250 \text{mW}$ Temperature Coefficient $\pm 100 \text{ppm/°C}$ Operating Temperature $-55^{\circ}\text{C} \sim 125^{\circ}\text{C}$ Applications-	Number of Resistors	4
Temperature Coefficient $\pm 100 \text{ppm/}^{\circ}\text{C}$ Operating Temperature $-55^{\circ}\text{C} \sim 125^{\circ}\text{C}$ Applications -	Number of Pins	5
Operating Temperature -55°C ~ 125°C Applications -	Power Per Element	250mW
Applications -	Temperature Coefficient	±100ppm/°C
	Operating Temperature	-55°C ~ 125°C
Mounting Type Through Hole	Applications	-
	Mounting Type	Through Hole
Package / Case 5-SIP	Package / Case	5-SIP
Supplier Device Package 5-SIP	Supplier Device Package	5-SIP
Size / Dimension 0.498" L x 0.098" W (12.65mm x 2.49mm)	Size / Dimension	0.498" L x 0.098" W (12.65mm x 2.49mm)
Height - Seated (Max) 0.250" (6.35mm)	Height - Seated (Max)	0.250" (6.35mm)
Report errors?		Report errors?

#### **4605M-101-222LF Guarantees**



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### 4605M-101-222LF Payment Methods



















## 4605M-101-222LF Shipping Methods













If you have any question about 4605M-101-222LF, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com