



4606X-AP2-333LF Information



For Reference Only

Part Number 4606X-AP2-333LF

Manufacturer Bourns Inc.
Category Resistors

Resistor Networks, Arrays

Description RES ARRAY 3 RES 33K OHM 6SIP

Package 6-SII

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









4606X-AP2-333LF Specifications

Manufacturer Part Number4606X-AP2-333LFManufacturerBourns Inc.CategoryResistorsResistor Networks, ArraysPackage6-SIPSeries4600XCircuit TypeIsolatedResistance (Ohms)33kTolerance±2%Number of Resistors3Number of Pins6Power Per Element300mWTemperature Coefficient±100ppm/°COperating Temperature-55°C ~ 125°CApplications-Mounting TypeThrough HolePackage / Case6-SIPSundard Package6 SIP		
Category Resistors Resistor Networks, Arrays Package 6-SIP Series 4600X Circuit Type Isolated Resistance (Ohms) 33k Tolerance ±2% Number of Resistors 3 Number of Pins 6 Power Per Element 300mW Temperature Coefficient ±100ppm/°C Operating Temperature -55°C ~ 125°C Applications - Mounting Type Through Hole Package / Case 6-SIP	Manufacturer Part Number	4606X-AP2-333LF
Resistor Networks, Arrays Package 6-SIP Series 4600X Circuit Type Isolated Resistance (Ohms) 33k Tolerance ±2% Number of Resistors 3 Number of Pins 6 Power Per Element 300mW Temperature Coefficient ±100ppm/°C Operating Temperature -55°C ~ 125°C Applications - Mounting Type Through Hole Package / Case 6-SIP	Manufacturer	Bourns Inc.
Package 6-SIP Series 4600X Circuit Type Isolated Resistance (Ohms) 33k Tolerance ±2% Number of Resistors 3 Number of Pins 6 Power Per Element 300mW Temperature Coefficient ±100ppm/°C Operating Temperature -55°C ~ 125°C Applications - Mounting Type Through Hole Package / Case 6-SIP	Category	Resistors
Series 4600X Circuit Type Isolated Resistance (Ohms) 33k Tolerance ±2% Number of Resistors 3 Number of Pins 6 Power Per Element 300mW Temperature Coefficient ±100ppm/°C Operating Temperature -55°C ~ 125°C Applications - Mounting Type Through Hole Package / Case 6-SIP		Resistor Networks, Arrays
Circuit Type Isolated Resistance (Ohms) 33k Tolerance ±2% Number of Resistors 3 Number of Pins 6 Power Per Element 300mW Temperature Coefficient ±100ppm/°C Operating Temperature -55°C ~ 125°C Applications - Mounting Type Through Hole Package / Case 6-SIP	Package	6-SIP
Resistance (Ohms) 33k Tolerance ±2% Number of Resistors 3 Number of Pins 6 Power Per Element 300mW Temperature Coefficient ±100ppm/°C Operating Temperature -55°C ~ 125°C Applications - Mounting Type Through Hole Package / Case 6-SIP	Series	4600X
Tolerance ±2% Number of Resistors 3 Number of Pins 6 Power Per Element 300mW Temperature Coefficient ±100ppm/°C Operating Temperature -55°C ~ 125°C Applications - Mounting Type Through Hole Package / Case 6-SIP	Circuit Type	Isolated
Number of Resistors3Number of Pins6Power Per Element300mWTemperature Coefficient±100ppm/°COperating Temperature-55°C ~ 125°CApplications-Mounting TypeThrough HolePackage / Case6-SIP	Resistance (Ohms)	33k
Number of Pins6Power Per Element 300mW Temperature Coefficient $\pm 100 \text{ppm/°C}$ Operating Temperature $-55^{\circ}\text{C} \sim 125^{\circ}\text{C}$ Applications-Mounting TypeThrough HolePackage / Case 6-SIP	Tolerance	±2%
Power Per Element 300mW Temperature Coefficient $\pm 100 \text{ppm/°C}$ Operating Temperature $-55^{\circ}\text{C} \sim 125^{\circ}\text{C}$ Applications-Mounting TypeThrough HolePackage / Case 6-SIP	Number of Resistors	3
Temperature Coefficient $\pm 100 \text{ppm/}^{\circ}\text{C}$ Operating Temperature $-55^{\circ}\text{C} \sim 125^{\circ}\text{C}$ Applications - Mounting Type Through Hole Package / Case 6-SIP	Number of Pins	6
Operating Temperature -55°C ~ 125°C Applications - Mounting Type Through Hole Package / Case 6-SIP	Power Per Element	300mW
Applications - Mounting Type Through Hole Package / Case 6-SIP	Temperature Coefficient	±100ppm/°C
Mounting Type Through Hole Package / Case 6-SIP	Operating Temperature	-55°C ~ 125°C
Package / Case 6-SIP	Applications	-
	Mounting Type	Through Hole
Cumpling Davies Peaks as 6 CID	Package / Case	6-SIP
Supplier Device Package 0-SIP	Supplier Device Package	6-SIP
Size / Dimension 0.598" L x 0.098" W (15.19mm x 2.49mm)	Size / Dimension	0.598" L x 0.098" W (15.19mm x 2.49mm)
Height - Seated (Max) 0.200" (5.08mm)	Height - Seated (Max)	0.200" (5.08mm)
Report errors?		Report errors?

4606X-AP2-333LF Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

4606X-AP2-333LF Payment Methods



















4606X-AP2-333LF Shipping Methods













If you have any question about 4606X-AP2-333LF, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com