



# 4608X-102-124LF Information



For Reference Only

**Part Number** 4608X-102-124LF

Manufacturer Bourns Inc.
Category Resistors

Resistor Networks, Arrays

**Description** RES ARRAY 4 RES 120K OHM 8SIP

Package 8-SIF

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# 4608X-102-124LF Specifications

Manufacturer Part Number4608X-102-124LFManufacturerBourns Inc.CategoryResistorsPackage8-SIPSeries4600XCircuit TypeIsolatedResistance (Ohms)120kTolerance±2%Number of Resistors4Number of Pins8Power Per Element300mWTemperature Coefficient±100ppm/°COperating Temperature-55°C ~ 125°CApplications-Mounting TypeThrough Hole		
CategoryResistorsResistor Networks, ArraysPackage8-SIPSeries4600XCircuit TypeIsolatedResistance (Ohms)120kTolerance±2%Number of Resistors4Number of Pins8Power Per Element300mWTemperature Coefficient±100ppm/°COperating Temperature-55°C ~ 125°CApplications-	Manufacturer Part Number	4608X-102-124LF
Resistor Networks, Arrays           Package         8-SIP           Series         4600X           Circuit Type         Isolated           Resistance (Ohms)         120k           Tolerance         ±2%           Number of Resistors         4           Number of Pins         8           Power Per Element         300mW           Temperature Coefficient         ±100ppm/°C           Operating Temperature         -55°C ~ 125°C           Applications         -	Manufacturer	Bourns Inc.
Package8-SIPSeries4600XCircuit TypeIsolatedResistance (Ohms)120kTolerance±2%Number of Resistors4Number of Pins8Power Per Element300mWTemperature Coefficient±100ppm/°COperating Temperature-55°C ~ 125°CApplications-	Category	Resistors
Series $4600X$ Circuit TypeIsolatedResistance (Ohms) $120k$ Tolerance $\pm 2\%$ Number of Resistors $4$ Number of Pins $8$ Power Per Element $300mW$ Temperature Coefficient $\pm 100ppm/^{\circ}C$ Operating Temperature $-55^{\circ}C \sim 125^{\circ}C$ Applications $-$		Resistor Networks, Arrays
Circuit TypeIsolatedResistance (Ohms) $120k$ Tolerance $\pm 2\%$ Number of Resistors $4$ Number of Pins $8$ Power Per Element $300mW$ Temperature Coefficient $\pm 100ppm/^{\circ}C$ Operating Temperature $-55^{\circ}C \sim 125^{\circ}C$ Applications $-$	Package	8-SIP
Resistance (Ohms) $120k$ Tolerance $\pm 2\%$ Number of Resistors $4$ Number of Pins $8$ Power Per Element $300mW$ Temperature Coefficient $\pm 100ppm/^{\circ}C$ Operating Temperature $-55^{\circ}C \sim 125^{\circ}C$ Applications $-$	Series	4600X
Tolerance $\pm 2\%$ Number of Resistors4Number of Pins8Power Per Element $300 \text{mW}$ Temperature Coefficient $\pm 100 \text{ppm/°C}$ Operating Temperature $-55^{\circ}\text{C} \sim 125^{\circ}\text{C}$ Applications-	Circuit Type	Isolated
Number of Resistors4Number of Pins8Power Per Element $300 \text{mW}$ Temperature Coefficient $\pm 100 \text{ppm/°C}$ Operating Temperature $-55^{\circ}\text{C} \sim 125^{\circ}\text{C}$ Applications-	Resistance (Ohms)	120k
Number of Pins8Power Per Element $300 \text{mW}$ Temperature Coefficient $\pm 100 \text{ppm/°C}$ Operating Temperature $-55 ^{\circ}\text{C} \sim 125 ^{\circ}\text{C}$ Applications-	Tolerance	±2%
Power Per Element $300 \text{mW}$ Temperature Coefficient $\pm 100 \text{ppm/°C}$ Operating Temperature $-55 ^{\circ}\text{C} \sim 125 ^{\circ}\text{C}$ Applications-	Number of Resistors	4
Temperature Coefficient $\pm 100 \text{ppm/}^{\circ}\text{C}$ Operating Temperature $-55^{\circ}\text{C} \sim 125^{\circ}\text{C}$ Applications -	Number of Pins	8
Operating Temperature -55°C ~ 125°C Applications -	Power Per Element	300mW
Applications -	Temperature Coefficient	±100ppm/°C
	Operating Temperature	-55°C ~ 125°C
Mounting Type Through Hole	Applications	-
	Mounting Type	Through Hole
Package / Case 8-SIP	Package / Case	8-SIP
Supplier Device Package 8-SIP	Supplier Device Package	8-SIP
Size / Dimension 0.798" L x 0.098" W (20.27mm x 2.49mm)	Size / Dimension	0.798" L x 0.098" W (20.27mm x 2.49mm)
Height - Seated (Max) 0.200" (5.08mm)	Height - Seated (Max)	0.200" (5.08mm)
Report errors?		Report errors?

#### **4608X-102-124LF Guarantees**



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## 4608X-102-124LF Payment Methods



















## 4608X-102-124LF Shipping Methods













If you have any question about 4608X-102-124LF, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com