



4610X-101-154LF Information



For Reference Only

Part Number 4610X-101-154LF

Manufacturer Bourns Inc.
Category Resistors

Resistor Networks, Arrays

Description RES ARRAY 9 RES 150K OHM 10SIP

Package 10-SIF

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









4610X-101-154LF Specifications

| Manufacturer Part Number4610X-101-154LFManufacturerBourns Inc.CategoryResistorsResistor Networks, ArraysPackage10-SIPSeries4600XCircuit TypeBussedResistance (Ohms)150kTolerance±2%Number of Resistors9Number of Pins10Power Per Element200mWTemperature Coefficient±100ppm/°COperating Temperature-55°C ~ 125°CApplications-Mounting TypeThrough HolePackage / Case10-SIP | | |
|--|--------------------------|--|
| CategoryResistorsPackage10-SIPSeries4600XCircuit TypeBussedResistance (Ohms)150kTolerance±2%Number of Resistors9Number of Pins10Power Per Element200mWTemperature Coefficient±100ppm/°COperating Temperature-55°C ~ 125°CApplications-Mounting TypeThrough Hole | Manufacturer Part Number | 4610X-101-154LF |
| Resistor Networks, Arrays Package 10-SIP Series 4600X Circuit Type Bussed Resistance (Ohms) 150k Tolerance ±2% Number of Resistors 9 Number of Pins 10 Power Per Element 200mW Temperature Coefficient ±100ppm/°C Operating Temperature -55°C ~ 125°C Applications - Mounting Type Through Hole | Manufacturer | Bourns Inc. |
| Package 10-SIP Series 4600X Circuit Type Bussed Resistance (Ohms) 150k Tolerance ±2% Number of Resistors 9 Number of Pins 10 Power Per Element 200mW Temperature Coefficient ±100ppm/°C Operating Temperature -55°C ~ 125°C Applications - Mounting Type Through Hole | Category | Resistors |
| Series 4600X Circuit Type Bussed Resistance (Ohms) 150k Tolerance ±2% Number of Resistors 9 Number of Pins 10 Power Per Element 200mW Temperature Coefficient ±100ppm/°C Operating Temperature -55°C ~ 125°C Applications - Mounting Type Through Hole | | Resistor Networks, Arrays |
| Circuit Type Resistance (Ohms) 150k Tolerance ±2% Number of Resistors 9 Number of Pins 10 Power Per Element 200mW Temperature Coefficient ±100ppm/°C Operating Temperature -55°C ~ 125°C Applications Mounting Type Bussed ±2% Bussed 10 -50k -2% Through Hole | Package | 10-SIP |
| Resistance (Ohms) 150k Tolerance $\pm 2\%$ Number of Resistors 9 Number of Pins 10 Power Per Element 200mW Temperature Coefficient ± 100 ppm/°C Operating Temperature -55 °C ~ 125 °C Applications - Mounting Type Through Hole | Series | 4600X |
| Tolerance $\pm 2\%$ Number of Resistors9Number of Pins 10 Power Per Element $200mW$ Temperature Coefficient $\pm 100ppm/^{\circ}C$ Operating Temperature $-55^{\circ}C \sim 125^{\circ}C$ Applications-Mounting TypeThrough Hole | Circuit Type | Bussed |
| Number of Resistors9Number of Pins10Power Per Element200mWTemperature Coefficient±100ppm/°COperating Temperature-55°C ~ 125°CApplications-Mounting TypeThrough Hole | Resistance (Ohms) | 150k |
| Number of Pins 10 Power Per Element 200mW Temperature Coefficient $\pm 100 \text{ppm/°C}$ Operating Temperature $-55^{\circ}\text{C} \sim 125^{\circ}\text{C}$ Applications-Mounting TypeThrough Hole | Tolerance | ±2% |
| Power Per Element 200mW Temperature Coefficient $\pm 100 \text{ppm/°C}$ Operating Temperature $-55^{\circ}\text{C} \sim 125^{\circ}\text{C}$ Applications-Mounting TypeThrough Hole | Number of Resistors | 9 |
| Temperature Coefficient $\pm 100 \text{ppm/}^{\circ}\text{C}$ Operating Temperature $-55^{\circ}\text{C} \sim 125^{\circ}\text{C}$ Applications - Mounting Type Through Hole | Number of Pins | 10 |
| Operating Temperature $-55^{\circ}\text{C} \sim 125^{\circ}\text{C}$ Applications - Mounting Type Through Hole | Power Per Element | 200mW |
| Applications - Mounting Type Through Hole | Temperature Coefficient | ±100ppm/°C |
| Mounting Type Through Hole | Operating Temperature | -55°C ~ 125°C |
| | Applications | - |
| Package / Case 10-SIP | Mounting Type | Through Hole |
| | Package / Case | 10-SIP |
| Supplier Device Package 10-SIP | Supplier Device Package | 10-SIP |
| Size / Dimension 0.998" L x 0.098" W (25.35mm x 2.49mm) | Size / Dimension | 0.998" L x 0.098" W (25.35mm x 2.49mm) |
| Height - Seated (Max) 0.200" (5.08mm) | Height - Seated (Max) | 0.200" (5.08mm) |
| Report errors? | | Report errors? |

4610X-101-154LF Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

4610X-101-154LF Payment Methods



















4610X-101-154LF Shipping Methods













If you have any question about 4610X-101-154LF, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com