



4610X-101-224LF Information



For Reference Only

Part Number 4610X-101-224LF

Manufacturer Bourns Inc.
Category Resistors

Resistor Networks, Arrays

Description RES ARRAY 9 RES 220K OHM 10SIP

Package 10-SIP

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









4610X-101-224LF Specifications

| Manufacturer Part Number 4610X-101-224LF Manufacturer Bourns Inc. Category Resistors Package 10-SIP Series 4600X Circuit Type Bussed Resistance (Ohms) 220k Tolerance ±2% Number of Resistors 9 Number of Pins 10 Power Per Element 200mW Temperature Coefficient ±100ppm/°C Operating Temperature -55°C ~ 125°C Applications - Mounting Type Through Hole Package / Case 10-SIP Supplier Device Package 10-SIP Size / Dimension 0.998" L x 0.098" W (25.35mm x 2.49mm) Height - Seated (Max) 0.200" (5.08mm) | | |
|---|--------------------------|--|
| Category Resistors Package 10-SIP Series 4600X Circuit Type Bussed Resistance (Ohms) 220k Tolerance ±2% Number of Resistors 9 Number of Pins 10 Power Per Element 200mW Temperature Coefficient ±100ppm/°C Operating Temperature -55°C ~ 125°C Applications - Mounting Type Through Hole Package / Case 10-SIP Supplier Device Package 10-SIP Size / Dimension 0.998" L x 0.098" W (25.35mm x 2.49mm) Height - Seated (Max) 0.200" (5.08mm) | Manufacturer Part Number | 4610X-101-224LF |
| Resistor Networks, Arrays Package 10-SIP Series 4600X Circuit Type Bussed Resistance (Ohms) 220k Tolerance ±2% Number of Resistors 9 Number of Pins 10 Power Per Element 200mW Temperature Coefficient ±100ppm/°C Operating Temperature -55°C ~ 125°C Applications - Mounting Type Through Hole Package / Case 10-SIP Supplier Device Package 10-SIP Size / Dimension 0.998" L x 0.098" W (25.35mm x 2.49mm) Height - Seated (Max) 0.200" (5.08mm) | Manufacturer | Bourns Inc. |
| Package 10-SIP Series 4600X Circuit Type Bussed Resistance (Ohms) 220k Tolerance ±2% Number of Resistors 9 Number of Pins 10 Power Per Element 200mW Temperature Coefficient ±100ppm/°C Operating Temperature -55°C ~ 125°C Applications - Mounting Type Through Hole Package / Case 10-SIP Supplier Device Package 10-SIP Size / Dimension 0.998" L x 0.098" W (25.35mm x 2.49mm) Height - Seated (Max) 0.200" (5.08mm) | Category | Resistors |
| Series 4600X Circuit Type Bussed Resistance (Ohms) 220k Tolerance ±2% Number of Resistors 9 Number of Pins 10 Power Per Element 200mW Temperature Coefficient ±100ppm/°C Operating Temperature -55°C ~ 125°C Applications - Mounting Type Through Hole Package / Case 10-SIP Supplier Device Package 10-SIP Size / Dimension 0.998" L x 0.098" W (25.35mm x 2.49mm) Height - Seated (Max) 0.200" (5.08mm) | | Resistor Networks, Arrays |
| Circuit TypeBussedResistance (Ohms)220kTolerance±2%Number of Resistors9Number of Pins10Power Per Element200mWTemperature Coefficient±100ppm/°COperating Temperature-55°C ~ 125°CApplications-Mounting TypeThrough HolePackage / Case10-SIPSupplier Device Package10-SIPSize / Dimension0.998" L x 0.098" W (25.35mm x 2.49mm)Height - Seated (Max)0.200" (5.08mm) | Package | 10-SIP |
| Resistance (Ohms) 220k Tolerance ±2% Number of Resistors 9 Number of Pins 10 Power Per Element 200mW Temperature Coefficient ±100ppm/°C Operating Temperature -55°C ~ 125°C Applications - Mounting Type Through Hole Package / Case 10-SIP Supplier Device Package 10-SIP Size / Dimension 0.998" L x 0.098" W (25.35mm x 2.49mm) Height - Seated (Max) 0.200" (5.08mm) | Series | 4600X |
| Tolerance ±2% Number of Resistors 9 Number of Pins 10 Power Per Element 200mW Temperature Coefficient ±100ppm/°C Operating Temperature -55°C ~ 125°C Applications - Mounting Type Through Hole Package / Case 10-SIP Supplier Device Package 10-SIP Size / Dimension 0.998" L x 0.098" W (25.35mm x 2.49mm) Height - Seated (Max) 0.200" (5.08mm) | Circuit Type | Bussed |
| Number of Resistors9Number of Pins10Power Per Element200mWTemperature Coefficient±100ppm/°COperating Temperature-55°C ~ 125°CApplications-Mounting TypeThrough HolePackage / Case10-SIPSupplier Device Package10-SIPSize / Dimension0.998" L x 0.098" W (25.35mm x 2.49mm)Height - Seated (Max)0.200" (5.08mm) | Resistance (Ohms) | 220k |
| Number of Pins 10 Power Per Element 200mW Temperature Coefficient ±100ppm/°C Operating Temperature -55°C ~ 125°C Applications - Mounting Type Through Hole Package / Case 10-SIP Supplier Device Package 10-SIP Size / Dimension 0.998" L x 0.098" W (25.35mm x 2.49mm) Height - Seated (Max) 0.200" (5.08mm) | Tolerance | ±2% |
| Power Per Element 200mW Temperature Coefficient ±100ppm/°C Operating Temperature -55°C ~ 125°C Applications - Mounting Type Through Hole Package / Case 10-SIP Supplier Device Package 10-SIP Size / Dimension 0.998" L x 0.098" W (25.35mm x 2.49mm) Height - Seated (Max) 0.200" (5.08mm) | Number of Resistors | 9 |
| Temperature Coefficient ±100ppm/°C Operating Temperature -55°C ~ 125°C Applications - Mounting Type Through Hole Package / Case 10-SIP Supplier Device Package 10-SIP Size / Dimension 0.998" L x 0.098" W (25.35mm x 2.49mm) Height - Seated (Max) 0.200" (5.08mm) | Number of Pins | 10 |
| Operating Temperature -55°C ~ 125°C Applications - Mounting Type Through Hole Package / Case 10-SIP Supplier Device Package 10-SIP Size / Dimension 0.998" L x 0.098" W (25.35mm x 2.49mm) Height - Seated (Max) 0.200" (5.08mm) | Power Per Element | 200mW |
| Applications - Mounting Type Through Hole Package / Case 10-SIP Supplier Device Package 10-SIP Size / Dimension 0.998" L x 0.098" W (25.35mm x 2.49mm) Height - Seated (Max) 0.200" (5.08mm) | Temperature Coefficient | ±100ppm/°C |
| Mounting Type Through Hole Package / Case 10-SIP Supplier Device Package 10-SIP Size / Dimension 0.998" L x 0.098" W (25.35mm x 2.49mm) Height - Seated (Max) 0.200" (5.08mm) | Operating Temperature | -55°C ~ 125°C |
| Package / Case 10-SIP Supplier Device Package 10-SIP Size / Dimension 0.998" L x 0.098" W (25.35mm x 2.49mm) Height - Seated (Max) 0.200" (5.08mm) | Applications | - |
| Supplier Device Package 10-SIP Size / Dimension 0.998" L x 0.098" W (25.35mm x 2.49mm) Height - Seated (Max) 0.200" (5.08mm) | Mounting Type | Through Hole |
| Size / Dimension 0.998" L x 0.098" W (25.35mm x 2.49mm) Height - Seated (Max) 0.200" (5.08mm) | Package / Case | 10-SIP |
| Height - Seated (Max) 0.200" (5.08mm) | Supplier Device Package | 10-SIP |
| | Size / Dimension | 0.998" L x 0.098" W (25.35mm x 2.49mm) |
| Report errors? | Height - Seated (Max) | 0.200" (5.08mm) |
| report errors. | | Report errors? |

4610X-101-224LF Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

4610X-101-224LF Payment Methods



















4610X-101-224LF Shipping Methods













If you have any question about 4610X-101-224LF, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com