



4610X-101-471LF Information



For Reference Only

Part Number 4610X-101-471LF

Manufacturer Bourns Inc.
Category Resistors

Resistor Networks, Arrays

Description RES ARRAY 9 RES 470 OHM 10SIP

Package 10-SIF

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









4610X-101-471LF Specifications

Manufacturer Part Number 4610X-101-471LF Manufacturer Bourns Inc. Category Resistors Resistor Networks, Arrays Package 10-SIP Series 4600X Circuit Type Bussed Resistance (Ohms) 470 Tolerance ±2% Number of Resistors 9 Number of Pins 10 Power Per Element 200mW Temperature Coefficient ±100ppm/°C Operating Temperature -55°C ~ 125°C Applications - Mounting Type Through Hole Package / Case 10-SIP		
Category Resistors Resistor Networks, Arrays Package 10-SIP Series 4600X Circuit Type Bussed Resistance (Ohms) 470 Tolerance ±2% Number of Resistors 9 Number of Pins 10 Power Per Element 200mW Temperature Coefficient ±100ppm/°C Operating Temperature -55°C ~ 125°C Applications - Mounting Type Through Hole Package / Case 10-SIP	Manufacturer Part Number	4610X-101-471LF
Resistor Networks, Arrays Package 10-SIP Series 4600X Circuit Type Bussed Resistance (Ohms) 470 Tolerance ±2% Number of Resistors 9 Number of Pins 10 Power Per Element 200mW Temperature Coefficient ±100ppm/°C Operating Temperature -55°C ~ 125°C Applications - Mounting Type Through Hole Package / Case 10-SIP	Manufacturer	Bourns Inc.
Package 10-SIP Series 4600X Circuit Type Bussed Resistance (Ohms) 470 Tolerance ±2% Number of Resistors 9 Number of Pins 10 Power Per Element 200mW Temperature Coefficient ±100ppm/°C Operating Temperature -55°C ~ 125°C Applications - Mounting Type Through Hole Package / Case 10-SIP	Category	Resistors
Series 4600X Circuit Type Bussed Resistance (Ohms) 470 Tolerance ±2% Number of Resistors 9 Number of Pins 10 Power Per Element 200mW Temperature Coefficient ±100ppm/°C Operating Temperature -55°C ~ 125°C Applications - Mounting Type Through Hole Package / Case 10-SIP		Resistor Networks, Arrays
Circuit Type Resistance (Ohms) 470 Tolerance ±2% Number of Resistors 9 Number of Pins 10 Power Per Element 200mW Temperature Coefficient ±100ppm/°C Operating Temperature -55°C ~ 125°C Applications - Mounting Type Through Hole Package / Case Bussed 470 470 470 470 470 59 Common Applications - Through Hole Package / Case	Package	10-SIP
Resistance (Ohms) 470 Tolerance ±2% Number of Resistors 9 Number of Pins 10 Power Per Element 200mW Temperature Coefficient ±100ppm/°C Operating Temperature -55°C ~ 125°C Applications - Mounting Type Through Hole Package / Case 10-SIP	Series	4600X
Tolerance ±2% Number of Resistors 9 Number of Pins 10 Power Per Element 200mW Temperature Coefficient ±100ppm/°C Operating Temperature -55°C ~ 125°C Applications - Mounting Type Through Hole Package / Case 10-SIP	Circuit Type	Bussed
Number of Resistors9Number of Pins10Power Per Element200mWTemperature Coefficient±100ppm/°COperating Temperature-55°C ~ 125°CApplications-Mounting TypeThrough HolePackage / Case10-SIP	Resistance (Ohms)	470
Number of Pins 10 Power Per Element 200mW Temperature Coefficient $\pm 100 \text{ppm/°C}$ Operating Temperature $-55^{\circ}\text{C} \sim 125^{\circ}\text{C}$ Applications-Mounting TypeThrough HolePackage / Case 10-SIP	Tolerance	±2%
Power Per Element 200mW Temperature Coefficient $\pm 100 \text{ppm/°C}$ Operating Temperature $-55^{\circ}\text{C} \sim 125^{\circ}\text{C}$ Applications-Mounting TypeThrough HolePackage / Case $10-\text{SIP}$	Number of Resistors	9
Temperature Coefficient $\pm 100 \text{ppm/}^{\circ}\text{C}$ Operating Temperature $-55^{\circ}\text{C} \sim 125^{\circ}\text{C}$ Applications - Mounting Type Through Hole Package / Case 10-SIP	Number of Pins	10
Operating Temperature -55°C ~ 125°C Applications - Mounting Type Through Hole Package / Case 10-SIP	Power Per Element	200mW
Applications - Mounting Type Through Hole Package / Case 10-SIP	Temperature Coefficient	±100ppm/°C
Mounting Type Through Hole Package / Case 10-SIP	Operating Temperature	-55°C ~ 125°C
Package / Case 10-SIP	Applications	-
	Mounting Type	Through Hole
	Package / Case	10-SIP
Supplier Device Package 10-SIP	Supplier Device Package	10-SIP
Size / Dimension 0.998" L x 0.098" W (25.35mm x 2.49mm)	Size / Dimension	0.998" L x 0.098" W (25.35mm x 2.49mm)
Height - Seated (Max) 0.200" (5.08mm)	Height - Seated (Max)	0.200" (5.08mm)
Report errors?		Report errors?

4610X-101-471LF Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

4610X-101-471LF Payment Methods



















4610X-101-471LF Shipping Methods













If you have any question about 4610X-101-471LF, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com