



4610X-102-681LF Information



For Reference Only

Part Number 4610X-102-681LF

Manufacturer Bourns Inc.
Category Resistors

Resistor Networks, Arrays

Description RES ARRAY 5 RES 680 OHM 10SIP

Package 10-SIF

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









4610X-102-681LF Specifications

Manufacturer Part Number 4610X-102-681LF Manufacturer Bourns Inc. Category Resistors Resistor Networks, Arrays Package 10-SIP Series 4600X Circuit Type Isolated Resistance (Ohms) 680 Tolerance ±2% Number of Resistors 5 Number of Pins 10 Power Per Element 300mW Temperature Coefficient ±100ppm/°C Operating Temperature -55°C ~ 125°C Applications - Mounting Type Through Hole Package / Case 10-SIP Supplier Device Package 10-SIP Size / Dimension 0.998" L x 0.098" W (25.35mm x 2.49mm) Height - Seated (Max) 0.200" (5.08mm)		
Category Resistors Resistor Networks, Arrays Package 10-SIP Series 4600X Circuit Type Isolated Resistance (Ohms) 680 Tolerance ±2% Number of Resistors 5 Number of Pins 10 Power Per Element 300mW Temperature Coefficient ±100ppm/°C Operating Temperature -55°C ~ 125°C Applications - Mounting Type Through Hole Package / Case 10-SIP Supplier Device Package 10-SIP Size / Dimension 0.998" L x 0.098" W (25.35mm x 2.49mm) Height - Seated (Max) 0.200" (5.08mm)	Manufacturer Part Number	4610X-102-681LF
Resistor Networks, Arrays Package 10-SIP Series 4600X Circuit Type Isolated Resistance (Ohms) 680 Tolerance ±2% Number of Resistors 5 Number of Pins 10 Power Per Element 300mW Temperature Coefficient ±100ppm/°C Operating Temperature -55°C ~ 125°C Applications - Mounting Type Through Hole Package / Case 10-SIP Supplier Device Package 10-SIP Size / Dimension 0.998" L x 0.098" W (25.35mm x 2.49mm) Height - Seated (Max) 0.200" (5.08mm)	Manufacturer	Bourns Inc.
Package 10-SIP Series 4600X Circuit Type Isolated Resistance (Ohms) 680 Tolerance ±2% Number of Resistors 5 Number of Pins 10 Power Per Element 300mW Temperature Coefficient ±100ppm/°C Operating Temperature -55°C ~ 125°C Applications - Mounting Type Through Hole Package / Case 10-SIP Supplier Device Package 10-SIP Size / Dimension 0.998" L x 0.098" W (25.35mm x 2.49mm) Height - Seated (Max) 0.200" (5.08mm)	Category	Resistors
Series 4600X Circuit Type Isolated Resistance (Ohms) 680 Tolerance ±2% Number of Resistors 5 Number of Pins 10 Power Per Element 300mW Temperature Coefficient ±100ppm/°C Operating Temperature -55°C ~ 125°C Applications - Mounting Type Through Hole Package / Case 10-SIP Supplier Device Package 10-SIP Size / Dimension 0.998" L x 0.098" W (25.35mm x 2.49mm) Height - Seated (Max) 0.200" (5.08mm)		Resistor Networks, Arrays
Circuit TypeIsolatedResistance (Ohms)680Tolerance±2%Number of Resistors5Number of Pins10Power Per Element300mWTemperature Coefficient±100ppm/°COperating Temperature-55°C ~ 125°CApplications-Mounting TypeThrough HolePackage / Case10-SIPSupplier Device Package10-SIPSize / Dimension0.998" L x 0.098" W (25.35mm x 2.49mm)Height - Seated (Max)0.200" (5.08mm)	Package	10-SIP
Resistance (Ohms) 680 Tolerance ±2% Number of Resistors 5 Number of Pins 10 Power Per Element 300mW Temperature Coefficient ±100ppm/°C Operating Temperature -55°C ~ 125°C Applications - Mounting Type Through Hole Package / Case 10-SIP Supplier Device Package 10-SIP Size / Dimension 0.998" L x 0.098" W (25.35mm x 2.49mm) Height - Seated (Max) 0.200" (5.08mm)	Series	4600X
Tolerance ±2% Number of Resistors 5 Number of Pins 10 Power Per Element 300mW Temperature Coefficient ±100ppm/°C Operating Temperature -55°C ~ 125°C Applications - Mounting Type Through Hole Package / Case 10-SIP Supplier Device Package 10-SIP Size / Dimension 0.998" L x 0.098" W (25.35mm x 2.49mm) Height - Seated (Max) 0.200" (5.08mm)	Circuit Type	Isolated
Number of Resistors5Number of Pins10Power Per Element300mWTemperature Coefficient±100ppm/°COperating Temperature-55°C ~ 125°CApplications-Mounting TypeThrough HolePackage / Case10-SIPSupplier Device Package10-SIPSize / Dimension0.998" L x 0.098" W (25.35mm x 2.49mm)Height - Seated (Max)0.200" (5.08mm)	Resistance (Ohms)	680
Number of Pins 10 Power Per Element 300mW Temperature Coefficient ±100ppm/°C Operating Temperature -55°C ~ 125°C Applications - Mounting Type Through Hole Package / Case 10-SIP Supplier Device Package 10-SIP Size / Dimension 0.998" L x 0.098" W (25.35mm x 2.49mm) Height - Seated (Max) 0.200" (5.08mm)	Tolerance	±2%
Power Per Element 300mW Temperature Coefficient ±100ppm/°C Operating Temperature -55°C ~ 125°C Applications - Mounting Type Through Hole Package / Case 10-SIP Supplier Device Package 10-SIP Size / Dimension 0.998" L x 0.098" W (25.35mm x 2.49mm) Height - Seated (Max) 0.200" (5.08mm)	Number of Resistors	5
Temperature Coefficient ±100ppm/°C Operating Temperature -55°C ~ 125°C Applications - Mounting Type Through Hole Package / Case 10-SIP Supplier Device Package 10-SIP Size / Dimension 0.998" L x 0.098" W (25.35mm x 2.49mm) Height - Seated (Max) 0.200" (5.08mm)	Number of Pins	10
Operating Temperature -55°C ~ 125°C Applications - Mounting Type Through Hole Package / Case 10-SIP Supplier Device Package 10-SIP Size / Dimension 0.998" L x 0.098" W (25.35mm x 2.49mm) Height - Seated (Max) 0.200" (5.08mm)	Power Per Element	300mW
Applications - Mounting Type Through Hole Package / Case 10-SIP Supplier Device Package 10-SIP Size / Dimension 0.998" L x 0.098" W (25.35mm x 2.49mm) Height - Seated (Max) 0.200" (5.08mm)	Temperature Coefficient	±100ppm/°C
Mounting Type Through Hole Package / Case 10-SIP Supplier Device Package 10-SIP Size / Dimension 0.998" L x 0.098" W (25.35mm x 2.49mm) Height - Seated (Max) 0.200" (5.08mm)	Operating Temperature	-55°C ~ 125°C
Package / Case 10-SIP Supplier Device Package 10-SIP Size / Dimension 0.998" L x 0.098" W (25.35mm x 2.49mm) Height - Seated (Max) 0.200" (5.08mm)	Applications	-
Supplier Device Package 10-SIP Size / Dimension 0.998" L x 0.098" W (25.35mm x 2.49mm) Height - Seated (Max) 0.200" (5.08mm)	Mounting Type	Through Hole
Size / Dimension 0.998" L x 0.098" W (25.35mm x 2.49mm) Height - Seated (Max) 0.200" (5.08mm)	Package / Case	10-SIP
Height - Seated (Max) 0.200" (5.08mm)	Supplier Device Package	10-SIP
	Size / Dimension	0.998" L x 0.098" W (25.35mm x 2.49mm)
Report errors?	Height - Seated (Max)	0.200" (5.08mm)
		Report errors?

4610X-102-681LF Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

4610X-102-681LF Payment Methods





















4610X-102-681LF Shipping Methods













If you have any question about 4610X-102-681LF, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com