



4610X-104-224/331L Information



For Reference Only

Part Number 4610X-104-224/331L

Manufacturer Bourns Inc.
Category Resistors

Resistor Networks, Arrays

Description RES NTWRK 16 RES MULT OHM 10SIP

Package 10-SII

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









4610X-104-224/331L Specifications

Manufacturer Part Number 4610X-104-224/331L Manufacturer Bourns Inc. Category Resistors Package 10-SIP Series 4600X Circuit Type Dual Terminator Resistance (Ohms) 330, 220k Tolerance ±2% Number of Resistors 16 Number of Pins 10 Power Per Element 200mW Temperature Coefficient ±100ppm/°C Operating Temperature -55°C ~ 125°C Applications - Mounting Type Through Hole Package / Case 10-SIP Supplier Device Package 10-SIP Size / Dimension 0.998" L x 0.098" W (25.35mm x 2.49mm) Height - Seated (Max) 0.200" (5.08mm)		
Category Resistors Package 10-SIP Series 4600X Circuit Type Dual Terminator Resistance (Ohms) 330, 220k Tolerance ±2% Number of Resistors 16 Number of Pins 10 Power Per Element 200mW Temperature Coefficient ±100ppm/°C Operating Temperature -55°C ~ 125°C Applications - Mounting Type Through Hole Package / Case 10-SIP Supplier Device Package 10-SIP Size / Dimension 0.998" L x 0.098" W (25.35mm x 2.49mm) Height - Seated (Max) 0.200" (5.08mm)	Manufacturer Part Number	4610X-104-224/331L
Resistor Networks, Arrays Package 10-SIP Series 4600X Circuit Type Dual Terminator Resistance (Ohms) 330, 220k Tolerance ±2% Number of Resistors 16 Number of Pins 10 Power Per Element 200mW Temperature Coefficient ±100ppm/°C Operating Temperature -55°C ~ 125°C Applications - Mounting Type Through Hole Package / Case 10-SIP Supplier Device Package 10-SIP Size / Dimension 0.998" L x 0.098" W (25.35mm x 2.49mm) Height - Seated (Max) 0.200" (5.08mm)	Manufacturer	Bourns Inc.
Package 10-SIP Series 4600X Circuit Type Dual Terminator Resistance (Ohms) 330, 220k Tolerance ±2% Number of Resistors 16 Number of Pins 10 Power Per Element 200mW Temperature Coefficient ±100ppm/°C Operating Temperature -55°C ~ 125°C Applications - Mounting Type Through Hole Package / Case 10-SIP Supplier Device Package 10-SIP Size / Dimension 0.998" L x 0.098" W (25.35mm x 2.49mm) Height - Seated (Max) 0.200" (5.08mm)	Category	Resistors
Series 4600X Circuit Type Dual Terminator Resistance (Ohms) 330, 220k Tolerance ±2% Number of Resistors 16 Number of Pins 10 Power Per Element 200mW Temperature Coefficient ±100ppm/°C Operating Temperature -55°C ~ 125°C Applications - Mounting Type Through Hole Package / Case 10-SIP Supplier Device Package 10-SIP Size / Dimension 0.998" L x 0.098" W (25.35mm x 2.49mm) Height - Seated (Max) 0.200" (5.08mm)		Resistor Networks, Arrays
Circuit TypeDual TerminatorResistance (Ohms)330, 220kTolerance±2%Number of Resistors16Number of Pins10Power Per Element200mWTemperature Coefficient±100ppm/°COperating Temperature-55°C ~ 125°CApplications-Mounting TypeThrough HolePackage / Case10-SIPSupplier Device Package10-SIPSize / Dimension0.998" L x 0.098" W (25.35mm x 2.49mm)Height - Seated (Max)0.200" (5.08mm)	Package	10-SIP
Resistance (Ohms) 330, 220k Tolerance ±2% Number of Resistors 16 Number of Pins 10 Power Per Element 200mW Temperature Coefficient ±100ppm/°C Operating Temperature -55°C ~ 125°C Applications - Mounting Type Through Hole Package / Case 10-SIP Supplier Device Package 10-SIP Size / Dimension 0.998" L x 0.098" W (25.35mm x 2.49mm) Height - Seated (Max) 0.200" (5.08mm)	Series	4600X
Tolerance ±2% Number of Resistors 16 Number of Pins 10 Power Per Element 200mW Temperature Coefficient ±100ppm/°C Operating Temperature -55°C ~ 125°C Applications - Mounting Type Through Hole Package / Case 10-SIP Supplier Device Package 10-SIP Size / Dimension 0.998" L x 0.098" W (25.35mm x 2.49mm) Height - Seated (Max) 0.200" (5.08mm)	Circuit Type	Dual Terminator
Number of Resistors 10 Power Per Element 200mW Temperature Coefficient 55°C ~ 125°C Applications - Mounting Type Through Hole Package / Case 10-SIP Size / Dimension 0.200" (5.08mm) 10 10 10 10 10 10 10 10 10 1	Resistance (Ohms)	330, 220k
Number of Pins 10 Power Per Element 200mW Temperature Coefficient ±100ppm/°C Operating Temperature -55°C ~ 125°C Applications - Mounting Type Through Hole Package / Case 10-SIP Supplier Device Package 10-SIP Size / Dimension 0.998" L x 0.098" W (25.35mm x 2.49mm) Height - Seated (Max) 0.200" (5.08mm)	Tolerance	±2%
Power Per Element 200mW Temperature Coefficient ±100ppm/°C Operating Temperature -55°C ~ 125°C Applications - Mounting Type Through Hole Package / Case 10-SIP Supplier Device Package 10-SIP Size / Dimension 0.998" L x 0.098" W (25.35mm x 2.49mm) Height - Seated (Max) 0.200" (5.08mm)	Number of Resistors	16
Temperature Coefficient ±100ppm/°C Operating Temperature -55°C ~ 125°C Applications - Mounting Type Through Hole Package / Case 10-SIP Supplier Device Package 10-SIP Size / Dimension 0.998" L x 0.098" W (25.35mm x 2.49mm) Height - Seated (Max) 0.200" (5.08mm)	Number of Pins	10
Operating Temperature -55°C ~ 125°C Applications - Mounting Type Through Hole Package / Case 10-SIP Supplier Device Package 10-SIP Size / Dimension 0.998" L x 0.098" W (25.35mm x 2.49mm) Height - Seated (Max) 0.200" (5.08mm)	Power Per Element	200mW
Applications - Mounting Type Through Hole Package / Case 10-SIP Supplier Device Package 10-SIP Size / Dimension 0.998" L x 0.098" W (25.35mm x 2.49mm) Height - Seated (Max) 0.200" (5.08mm)	Temperature Coefficient	±100ppm/°C
Mounting Type Through Hole Package / Case 10-SIP Supplier Device Package 10-SIP Size / Dimension 0.998" L x 0.098" W (25.35mm x 2.49mm) Height - Seated (Max) 0.200" (5.08mm)	Operating Temperature	-55°C ~ 125°C
Package / Case 10-SIP Supplier Device Package 10-SIP Size / Dimension 0.998" L x 0.098" W (25.35mm x 2.49mm) Height - Seated (Max) 0.200" (5.08mm)	Applications	-
Supplier Device Package 10-SIP Size / Dimension 0.998" L x 0.098" W (25.35mm x 2.49mm) Height - Seated (Max) 0.200" (5.08mm)	Mounting Type	Through Hole
Size / Dimension 0.998" L x 0.098" W (25.35mm x 2.49mm) Height - Seated (Max) 0.200" (5.08mm)	Package / Case	10-SIP
Height - Seated (Max) 0.200" (5.08mm)	Supplier Device Package	10-SIP
	Size / Dimension	0.998" L x 0.098" W (25.35mm x 2.49mm)
Report errors?	Height - Seated (Max)	0.200" (5.08mm)
		Report errors?

4610X-104-224/331L Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

4610X-104-224/331L Payment Methods





















4610X-104-224/331L Shipping Methods













If you have any question about 4610X-104-224/331L, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com