



4612X-102-680LF Information



For Reference Only

Part Number 4612X-102-680LF

Manufacturer Bourns Inc.
Category Resistors

Resistor Networks, Arrays

Description RES ARRAY 6 RES 68 OHM 12SIP

Package 12-SIF

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









4612X-102-680LF Specifications

Manufacturer Part Number 4612X-102-680LF Manufacturer Bourns Inc. Category Resistors Resistor Networks, Arrays Package 12-SIP Series 4600X Circuit Type Isolated Resistance (Ohms) 68 Tolerance ±2% Number of Resistors 6 Number of Pins 12 Power Per Element 300mW Temperature Coefficient ±100ppm/°C Operating Temperature -55°C ~ 125°C Applications - Mounting Type Through Hole Package / Case 12-SIP Supplier Device Package 12-SIP Size / Dimension 1.198" L x 0.098" W (30.43mm x 2.49mm) Height - Seated (Max) 0.200" (5.08mm)		
Category Resistors Package 12-SIP Series 4600X Circuit Type Isolated Resistance (Ohms) 68 Tolerance ±2% Number of Resistors 6 Number of Pins 12 Power Per Element 300mW Temperature Coefficient ±100ppm/°C Operating Temperature -55°C ~ 125°C Applications - Mounting Type Through Hole Package / Case 12-SIP Supplier Device Package 12-SIP Size / Dimension 1.198" L x 0.098" W (30.43mm x 2.49mm) Height - Seated (Max) 0.200" (5.08mm)	Manufacturer Part Number	4612X-102-680LF
Resistor Networks, Arrays Package 12-SIP Series 4600X Circuit Type Isolated Resistance (Ohms) 68 Tolerance ±2% Number of Resistors 6 Number of Pins 12 Power Per Element 300mW Temperature Coefficient ±100ppm/°C Operating Temperature -55°C ~ 125°C Applications - Mounting Type Through Hole Package / Case 12-SIP Supplier Device Package 12-SIP Size / Dimension 1.198" L x 0.098" W (30.43mm x 2.49mm) Height - Seated (Max) 0.200" (5.08mm)	Manufacturer	Bourns Inc.
Package 12-SIP Series 4600X Circuit Type Isolated Resistance (Ohms) 68 Tolerance ±2% Number of Resistors 6 Number of Pins 12 Power Per Element 300mW Temperature Coefficient ±100ppm/°C Operating Temperature -55°C ~ 125°C Applications - Mounting Type Through Hole Package / Case 12-SIP Supplier Device Package 12-SIP Size / Dimension 1.198" L x 0.098" W (30.43mm x 2.49mm) Height - Seated (Max) 0.200" (5.08mm)	Category	Resistors
Series 4600X Circuit Type Isolated Resistance (Ohms) 68 Tolerance ±2% Number of Resistors 6 Number of Pins 12 Power Per Element 300mW Temperature Coefficient ±100ppm/°C Operating Temperature -55°C ~ 125°C Applications - Mounting Type Through Hole Package / Case 12-SIP Supplier Device Package 12-SIP Size / Dimension 1.198" L x 0.098" W (30.43mm x 2.49mm) Height - Seated (Max) 0.200" (5.08mm)		Resistor Networks, Arrays
Circuit TypeIsolatedResistance (Ohms)68Tolerance±2%Number of Resistors6Number of Pins12Power Per Element300mWTemperature Coefficient±100ppm/°COperating Temperature-55°C ~ 125°CApplications-Mounting TypeThrough HolePackage / Case12-SIPSupplier Device Package12-SIPSize / Dimension1.198" L x 0.098" W (30.43mm x 2.49mm)Height - Seated (Max)0.200" (5.08mm)	Package	12-SIP
Resistance (Ohms) 68 Tolerance ±2% Number of Resistors 6 Number of Pins 12 Power Per Element 300mW Temperature Coefficient ±100ppm/°C Operating Temperature -55°C ~ 125°C Applications - Mounting Type Through Hole Package / Case 12-SIP Supplier Device Package 12-SIP Size / Dimension 1.198" L x 0.098" W (30.43mm x 2.49mm) Height - Seated (Max) 0.200" (5.08mm)	Series	4600X
Tolerance ±2% Number of Resistors 6 Number of Pins 12 Power Per Element 300mW Temperature Coefficient ±100ppm/°C Operating Temperature -55°C ~ 125°C Applications - Mounting Type Through Hole Package / Case 12-SIP Supplier Device Package 12-SIP Size / Dimension 1.198" L x 0.098" W (30.43mm x 2.49mm) Height - Seated (Max) 0.200" (5.08mm)	Circuit Type	Isolated
Number of Resistors6Number of Pins12Power Per Element300mWTemperature Coefficient±100ppm/°COperating Temperature-55°C ~ 125°CApplications-Mounting TypeThrough HolePackage / Case12-SIPSupplier Device Package12-SIPSize / Dimension1.198" L x 0.098" W (30.43mm x 2.49mm)Height - Seated (Max)0.200" (5.08mm)	Resistance (Ohms)	68
Number of Pins 12 Power Per Element 300mW Temperature Coefficient ±100ppm/°C Operating Temperature -55°C ~ 125°C Applications - Mounting Type Through Hole Package / Case 12-SIP Supplier Device Package 12-SIP Size / Dimension 1.198" L x 0.098" W (30.43mm x 2.49mm) Height - Seated (Max) 0.200" (5.08mm)	Tolerance	±2%
Power Per Element 300mW Temperature Coefficient ±100ppm/°C Operating Temperature -55°C ~ 125°C Applications - Mounting Type Through Hole Package / Case 12-SIP Supplier Device Package 12-SIP Size / Dimension 1.198" L x 0.098" W (30.43mm x 2.49mm) Height - Seated (Max) 0.200" (5.08mm)	Number of Resistors	6
Temperature Coefficient ±100ppm/°C Operating Temperature -55°C ~ 125°C Applications - Mounting Type Through Hole Package / Case 12-SIP Supplier Device Package 12-SIP Size / Dimension 1.198" L x 0.098" W (30.43mm x 2.49mm) Height - Seated (Max) 0.200" (5.08mm)	Number of Pins	12
Operating Temperature -55°C ~ 125°C Applications - Mounting Type Through Hole Package / Case 12-SIP Supplier Device Package 12-SIP Size / Dimension 1.198" L x 0.098" W (30.43mm x 2.49mm) Height - Seated (Max) 0.200" (5.08mm)	Power Per Element	300mW
Applications - Mounting Type Through Hole Package / Case 12-SIP Supplier Device Package 12-SIP Size / Dimension 1.198" L x 0.098" W (30.43mm x 2.49mm) Height - Seated (Max) 0.200" (5.08mm)	Temperature Coefficient	±100ppm/°C
Mounting Type Through Hole Package / Case 12-SIP Supplier Device Package 12-SIP Size / Dimension 1.198" L x 0.098" W (30.43mm x 2.49mm) Height - Seated (Max) 0.200" (5.08mm)	Operating Temperature	-55°C ~ 125°C
Package / Case 12-SIP Supplier Device Package 12-SIP Size / Dimension 1.198" L x 0.098" W (30.43mm x 2.49mm) Height - Seated (Max) 0.200" (5.08mm)	Applications	-
Supplier Device Package 12-SIP Size / Dimension 1.198" L x 0.098" W (30.43mm x 2.49mm) Height - Seated (Max) 0.200" (5.08mm)	Mounting Type	Through Hole
Size / Dimension 1.198" L x 0.098" W (30.43mm x 2.49mm) Height - Seated (Max) 0.200" (5.08mm)	Package / Case	12-SIP
Height - Seated (Max) 0.200" (5.08mm)	Supplier Device Package	12-SIP
	Size / Dimension	1.198" L x 0.098" W (30.43mm x 2.49mm)
Report errors?	Height - Seated (Max)	0.200" (5.08mm)
		Report errors?

4612X-102-680LF Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

4612X-102-680LF Payment Methods



















4612X-102-680LF Shipping Methods













If you have any question about 4612X-102-680LF, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com