

4700-81L15K999

4700-81L15K999 Information

Heisener.com	 4700-81L15K999 TE Connectivity Potter & Brumfield Relays Transformers Power Transformers XFRMR LAMINATED 60VA CHAS MOUNT - For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



4700-81L15K999 Specifications

Manufacturer TE Connectivity Potter & Brumfield Relays Category Transformers Power Transformers Power Transformers Package - Series 4700, Products Unlimited Type Laminated Core Voltage - Primary 208V, 240V, 480V Voltage - Secondary (Full Load) 120V Current - Output (Max) - Primary Winding(s) Single Secondary Winding(s) Single Power - Max 60 VA Mounting Type Chassis Mount Termination Style Wire Leads Size / Dimension 101.60mm L x 63.50mm W Height - Seated (Max) - Weight -		
CategoryTransformersPower TransformersPackagePackageSeries4700, Products UnlimitedTypeLaminated CoreVoltage - Primary208V, 240V, 480VVoltage - Secondary (Full Load)120VCurrent - Output (Max)-Primary Winding(s)Secondary Winding(s)SingleCenter TapPower - MaxMounting TypeChassis MountTermination StyleSize / DimensionHeight - Seated (Max)-Voltage - IsolationWeightKieght<	Manufacturer Part Number	4700-81L15K999
Power TransformersPackage-Series4700, Products UnlimitedTypeLaminated CoreVoltage - Primary208V, 240V, 480VVoltage - Secondary (Full Load)120VCurrent - Output (Max)-Primary Winding(s)SingleSecondary Winding(s)SingleCenter TapNoPower - Max60 VAMounting TypeChassis MountTermination Style101.60mm L x 63.50mm WSize / Dimension-Voltage - Isolation-WeightSouther CommentStigter Isolation-Stigter Isolation	Manufacturer	TE Connectivity Potter & Brumfield Relays
Package-Series4700, Products UnlimitedStriesLaminated CoreVoltage - Primary208V, 240V, 480VVoltage - Secondary (Full Load)120VCurrent - Output (Max)-Primary Winding(s)SingleSecondary Winding(s)SingleCenter TapNoPower - Max60 VAMounting TypeChassis MountTermination Style101.60mm Lx 63.50mm WSize / Dimension101.60mm Lx 63.50mm WVoltage - Isolation-WeightSeconder Second	Category	Transformers
Arrive4700, Products UnlimitedTypeLaminated CoreVoltage - Primary208V, 240V, 480VVoltage - Secondary (Full Load)120VCurrent - Output (Max)-Primary Winding(s)SingleSecondary Winding(s)SingleCenter TapNoPower - Max60 VAMounting TypeChassis MountTermination Style101.60mm L x 63.50mm WSize / Dimension-Height - Seated (Max)-Weight60 VA		Power Transformers
TypeLaminated CoreVoltage - Primary208V, 240V, 480VVoltage - Secondary (Full Load)120VCurrent - Output (Max)-Primary Winding(s)SingleSecondary Winding(s)SingleSecondary Winding(s)60 VAPower - Max60 VAMounting TypeChassis MountTermination StyleWire LeadsSize / Dimension101.60mm L x 63.50mm WHeight - Seated (Max)-WeightSingle	Package	-
NameVoltage - Primary208V, 240V, 480VVoltage - Secondary (Full Load)120VCurrent - Output (Max)-Primary Winding(s)SingleSecondary Winding(s)SingleCenter TapNoPower - Max60 VAMounting TypeChassis MountTermination StyleWire LeadsSize / Dimension-Height - Seated (Max)-Voltage - Isolation-Weight-	Series	4700, Products Unlimited
Voltage - Secondary (Full Load)120VCurrent - Output (Max)-Primary Winding(s)SingleSecondary Winding(s)SingleCenter TapNoPower - Max60 VAMounting TypeChassis MountTermination StyleWire LeadsSize / Dimension101.60mm L x 63.50mm WHeight - Seated (Max)-Voltage - Isolation-Weight-	Туре	Laminated Core
Current - Output (Max)-Primary Winding(s)SingleSecondary Winding(s)SingleCenter TapNoPower - Max60 VAMounting TypeChassis MountTermination StyleWire LeadsSize / Dimension101.60mm L x 63.50mm WHeight - Seated (Max)-Voltage - Isolation-Weight-	Voltage - Primary	208V, 240V, 480V
Primary Winding(s)SingleSecondary Winding(s)SingleCenter TapNoPower - Max60 VAMounting TypeChassis MountTermination StyleWire LeadsSize / Dimension101.60mm L x 63.50mm WHeight - Seated (Max)-Voltage - Isolation-Weight-	Voltage - Secondary (Full Load)	120V
Secondary Winding(s)SingleCenter TapNoPower - Max60 VAMounting TypeChassis MountTermination StyleWire LeadsSize / Dimension101.60mm L x 63.50mm WHeight - Seated (Max)-Voltage - Isolation-Weight-	Current - Output (Max)	-
Center TapNoPower - Max60 VAMounting TypeChassis MountTermination StyleWire LeadsSize / Dimension101.60mm L x 63.50mm WHeight - Seated (Max)-Voltage - Isolation-Weight-	Primary Winding(s)	Single
Power - Max60 VAMounting TypeChassis MountTermination StyleWire LeadsSize / Dimension101.60mm L x 63.50mm WHeight - Seated (Max)-Voltage - Isolation-Weight-	Secondary Winding(s)	Single
Mounting TypeChassis MountTermination StyleWire LeadsSize / Dimension101.60mm L x 63.50mm WHeight - Seated (Max)-Voltage - Isolation-Weight-	Center Tap	No
Termination StyleWire LeadsSize / Dimension101.60mm L x 63.50mm WHeight - Seated (Max)-Voltage - Isolation-Weight-	Power - Max	60 VA
Size / Dimension101.60mm L x 63.50mm WHeight - Seated (Max)-Voltage - Isolation-Weight-	Mounting Type	Chassis Mount
Height - Seated (Max)-Voltage - Isolation-Weight-	Termination Style	Wire Leads
Voltage - Isolation - Weight -	Size / Dimension	101.60mm L x 63.50mm W
Weight -	Height - Seated (Max)	-
-	Voltage - Isolation	-
Report errors?	Weight	-
		Report errors?

4700-81L15K999 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

4700-81L15K999 Payment Methods





If you have any question about 4700-81L15K999, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com