



### 474MKP275KB Information



Part Number 474MKP275KB
Manufacturer Illinois Capacitor
Category Capacitors
Film Capacitors

**Description** CAP FILM 0.47UF 10% 310VAC RAD

Package Radial

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## 474MKP275KB Specifications

Manufacturer Part Number         474MKP275KB           Manufacturer         Illinois Capacitor           Category         Capacitors           Package         Radial           Series         MKP           Capacitance         0.47µF           Tolerance         ±10%           Voltage Rating - AC         310V           Voltage Rating - DC         -           Dielectric Material         Polypropylene (PP), Metallized           ESR (Equivalent Series Resistance)         -           Operating Temperature         -40°C ~ 110°C           Mounting Type         Through Hole           Package / Case         Radial           Size / Dimension         1.024" L x 0.295" W (26.00mm x 7.50mm)           Height - Seated (Max)         0.661" (16.80mm)           Termination         -           Lead Spacing         0.886" (22.50mm)           Applications         EMI, RFI Suppression           Features         X2 Safety Rated	•	
Category         Capacitors           Package         Radial           Series         MKP           Capacitance         0.47µF           Tolerance         ±10%           Voltage Rating - AC         310V           Voltage Rating - DC         -           Dielectric Material         Polypropylene (PP), Metallized           ESR (Equivalent Series Resistance)         -           Operating Temperature         -40°C ~ 110°C           Mounting Type         Through Hole           Package / Case         Radial           Size / Dimension         1.024" L x 0.295" W (26.00mm x 7.50mm)           Height - Seated (Max)         0.661" (16.80mm)           Termination         -           Lead Spacing         0.886" (22.50mm)           Applications         EMI, RFI Suppression           Features         X2 Safety Rated	Manufacturer Part Number	474MKP275KB
Package         Radial           Series         MKP           Capacitance         0.47μF           Tolerance         ±10%           Voltage Rating - AC         310V           Voltage Rating - DC         -           Dielectric Material         Polypropylene (PP), Metallized           ESR (Equivalent Series Resistance)         -           Operating Temperature         -40°C ~ 110°C           Mounting Type         Through Hole           Package / Case         Radial           Size / Dimension         1.024" L x 0.295" W (26.00mm x 7.50mm)           Height - Seated (Max)         0.661" (16.80mm)           Termination         -           Lead Spacing         0.886" (22.50mm)           Applications         EMI, RFI Suppression           Features         X2 Safety Rated	Manufacturer	Illinois Capacitor
PackageRadialSeriesMKPCapacitance0.47μFTolerance±10%Voltage Rating - AC310VVoltage Rating - DC-Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-40°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension1.024" L x 0.295" W (26.00mm x 7.50mm)Height - Seated (Max)0.661" (16.80mm)Termination-Lead Spacing0.886" (22.50mm)ApplicationsEMI, RFI SuppressionFeaturesX2 Safety Rated	Category	Capacitors
Series         MKP           Capacitance         0.47μF           Tolerance         ±10%           Voltage Rating - AC         310V           Voltage Rating - DC         -           Dielectric Material         Polypropylene (PP), Metallized           ESR (Equivalent Series Resistance)         -           Operating Temperature         -40°C ~ 110°C           Mounting Type         Through Hole           Package / Case         Radial           Size / Dimension         1.024" L x 0.295" W (26.00mm x 7.50mm)           Height - Seated (Max)         0.661" (16.80mm)           Termination         -           Lead Spacing         0.886" (22.50mm)           Applications         EMI, RFI Suppression           Features         X2 Safety Rated		Film Capacitors
Capacitance $0.47\mu F$ Tolerance $\pm 10\%$ Voltage Rating - AC $310V$ Voltage Rating - DC-Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature $-40^{\circ}C \sim 110^{\circ}C$ Mounting TypeThrough HolePackage / CaseRadialSize / Dimension $1.024^{\circ}L \times 0.295^{\circ}W (26.00mm \times 7.50mm)$ Height - Seated (Max) $0.661^{\circ} (16.80mm)$ Termination-Lead Spacing $0.886^{\circ} (22.50mm)$ ApplicationsEMI, RFI SuppressionFeaturesX2 Safety Rated	Package	Radial
Tolerance ±10%  Voltage Rating - AC 310V  Voltage Rating - DC -  Dielectric Material Polypropylene (PP), Metallized  ESR (Equivalent Series Resistance) -  Operating Temperature -40°C ~ 110°C  Mounting Type Through Hole  Package / Case Radial  Size / Dimension 1.024" L x 0.295" W (26.00mm x 7.50mm)  Height - Seated (Max) 0.661" (16.80mm)  Termination -  Lead Spacing 0.886" (22.50mm)  Applications EMI, RFI Suppression  Features X2 Safety Rated	Series	MKP
Voltage Rating - AC  Voltage Rating - DC  Dielectric Material  Polypropylene (PP), Metallized  ESR (Equivalent Series Resistance)  Operating Temperature  -40°C ~ 110°C  Mounting Type  Through Hole  Package / Case  Radial  Size / Dimension  1.024" L x 0.295" W (26.00mm x 7.50mm)  Height - Seated (Max)  Termination  Lead Spacing  0.886" (22.50mm)  Applications  EMI, RFI Suppression  Features  X2 Safety Rated	Capacitance	0.47μF
Voltage Rating - DC  Dielectric Material  Polypropylene (PP), Metallized  ESR (Equivalent Series Resistance)  Operating Temperature  -40°C ~ 110°C  Mounting Type  Through Hole  Package / Case  Radial  Size / Dimension  1.024" L x 0.295" W (26.00mm x 7.50mm)  Height - Seated (Max)  Termination  -  Lead Spacing  0.886" (22.50mm)  Applications  EMI, RFI Suppression  Features  X2 Safety Rated	Tolerance	±10%
Dielectric Material  ESR (Equivalent Series Resistance)  Operating Temperature  -40°C ~ 110°C  Mounting Type  Through Hole  Package / Case  Radial  Size / Dimension  1.024" L x 0.295" W (26.00mm x 7.50mm)  Height - Seated (Max)  Termination  -  Lead Spacing  0.886" (22.50mm)  Applications  EMI, RFI Suppression  Features  X2 Safety Rated	Voltage Rating - AC	310V
ESR (Equivalent Series Resistance)  Operating Temperature  -40°C ~ 110°C  Mounting Type  Through Hole  Package / Case  Radial  Size / Dimension  1.024" L x 0.295" W (26.00mm x 7.50mm)  Height - Seated (Max)  Termination  -  Lead Spacing  0.886" (22.50mm)  Applications  EMI, RFI Suppression  Features  X2 Safety Rated	Voltage Rating - DC	-
Operating Temperature  -40°C ~ 110°C  Mounting Type  Through Hole  Package / Case  Radial  Size / Dimension  1.024" L x 0.295" W (26.00mm x 7.50mm)  Height - Seated (Max)  0.661" (16.80mm)  Termination  -  Lead Spacing  0.886" (22.50mm)  Applications  EMI, RFI Suppression  Features  X2 Safety Rated	Dielectric Material	Polypropylene (PP), Metallized
Mounting Type  Package / Case  Radial  Size / Dimension  1.024" L x 0.295" W (26.00mm x 7.50mm)  Height - Seated (Max)  7.50mm  1.024" L x 0.295" W (26.00mm x 7.50mm)  2.0661" (16.80mm)  1.024" L x 0.295" W (26.00mm x 7.50mm)  2.0661" (16.80mm)  2.086" (22.50mm)  3.086" (22.50mm)  4.086" (22.50mm)  4.086" (22.50mm)  5.086" (22.50mm)  5.086" (22.50mm)  5.086" (22.50mm)  6.086" (22.50mm)	ESR (Equivalent Series Resistance)	-
Package / CaseRadialSize / Dimension1.024" L x 0.295" W (26.00mm x 7.50mm)Height - Seated (Max)0.661" (16.80mm)Termination-Lead Spacing0.886" (22.50mm)ApplicationsEMI, RFI SuppressionFeaturesX2 Safety Rated	Operating Temperature	-40°C ~ 110°C
Size / Dimension       1.024" L x 0.295" W (26.00mm x 7.50mm)         Height - Seated (Max)       0.661" (16.80mm)         Termination       -         Lead Spacing       0.886" (22.50mm)         Applications       EMI, RFI Suppression         Features       X2 Safety Rated	Mounting Type	Through Hole
Height - Seated (Max)  Termination  Lead Spacing  O.886" (22.50mm)  Applications  EMI, RFI Suppression  Features  X2 Safety Rated	Package / Case	Radial
Termination - Lead Spacing 0.886" (22.50mm) Applications EMI, RFI Suppression Features X2 Safety Rated	Size / Dimension	1.024" L x 0.295" W (26.00mm x 7.50mm)
Lead Spacing0.886" (22.50mm)ApplicationsEMI, RFI SuppressionFeaturesX2 Safety Rated	Height - Seated (Max)	0.661" (16.80mm)
Applications EMI, RFI Suppression Features X2 Safety Rated	Termination	-
Features X2 Safety Rated	Lead Spacing	0.886" (22.50mm)
·	Applications	EMI, RFI Suppression
Report errors?	Features	X2 Safety Rated
		Report errors?

#### 474MKP275KB Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## 474MKP275KB Payment Methods



















### **474MKP275KB Shipping Methods**













If you have any question about 474MKP275KB, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com