



474PMB302KA Information



For Reference Only

Part Number 474PMB302KA
Manufacturer Illinois Capacitor
Category Capacitors
Film Capacitors

Description CAP FILM 0.47UF 3KVDC CHAS MT

Package Rectangular Box

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









474PMB302KA Specifications

Manufacturer Part Number 474PMB302KA Manufacturer Illinois Capacitors Category Capacitors Package Rectangular Box Series PMB Capacitance 0.47µF Tolerance ±10% Voltage Rating - AC 750V Voltage Rating - DC 3000V (3kV) Dielectric Material Polypropylene (PP), Metallized ESR (Equivalent Series Resistance) 3.8 mOhm Operating Temperature -40°C ~ 85°C Mounting Type Chassis Mount Package / Case Rectangular Box Size / Dimension 2.264" L x 1.378" W (57.50mm x 35.00mm) Height - Seated (Max) 1.969" (50.00mm) Termination - Lead Spacing - Applications DC Link, DC Filtering; High Frequency, Switching; Snubber Features - Report errors?	•		
CategoryCapacitorsPackageRectangular BoxSeriesPMBCapacitance0.47µFTolerance±10%Voltage Rating - AC750VVoltage Rating - DC3000V (3kV)Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)3.8 mOhmOperating Temperature-40°C ~ 85°CMounting TypeChassis MountPackage / CaseRectangular BoxSize / Dimension2.264" L x 1.378" W (57.50mm x 35.00mm)Height - Seated (Max)1.969" (50.00mm)Termination-Lead Spacing-ApplicationsDC Link, DC Filtering; High Frequency, Switching; SnubberFeatures-	Manufacturer Part Number	474PMB302KA	
PackageRectangular BoxSeriesPMBCapacitance0.47μFTolerance±10%Voltage Rating - AC750VVoltage Ratirg - DC3000V (3kV)Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)3.8 mOhmOperating Temperature-40°C ~ 85°CMounting TypeChassis MountPackage / CaseRectangular BoxSize / Dimension2.264" L x 1.378" W (57.50mm x 35.00mm)Height - Seated (Max)1.969" (50.00mm)Termination-Lead Spacing-ApplicationsDC Link, DC Filtering; High Frequency, Switching; SnubberFeatures-	Manufacturer	Illinois Capacitor	
PackageRectangular BoxSeriesPMBCapacitance0.47μFTolerance±10%Voltage Rating - AC750VVoltage Rating - DC3000V (3kV)Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)3.8 mOhmOperating Temperature-40°C ~ 85°CMounting TypeChassis MountPackage / CaseRectangular BoxSize / Dimension2.264" L x 1.378" W (57.50mm x 35.00mm)Height - Seated (Max)1.969" (50.00mm)Termination-Lead Spacing-ApplicationsDC Link, DC Filtering; High Frequency, Switching; SnubberFeatures-	Category	Capacitors	
SeriesPMBCapacitance0.47μFTolerance±10%Voltage Rating - AC750VVoltage Rating - DC3000V (3kV)Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)3.8 mOhmOperating Temperature-40°C ~ 85°CMounting TypeChassis MountPackage / CaseRectangular BoxSize / Dimension2.264" L x 1.378" W (57.50mm x 35.00mm)Height - Seated (Max)1.969" (50.00mm)Termination-Lead Spacing-ApplicationsDC Link, DC Filtering; High Frequency, Switching; SnubberFeatures-		Film Capacitors	
Capacitance 0.47µF Tolerance ±10% Voltage Rating - AC 750V Voltage Rating - DC 3000V (3kV) Dielectric Material Polypropylene (PP), Metallized ESR (Equivalent Series Resistance) 3.8 mOhm Operating Temperature -40°C ~ 85°C Mounting Type Chassis Mount Package / Case Rectangular Box Size / Dimension 2.264" L x 1.378" W (57.50mm x 35.00mm) Height - Seated (Max) 1.969" (50.00mm) Termination - Lead Spacing - Applications DC Link, DC Filtering; High Frequency, Switching; Snubber Features -	Package	Rectangular Box	
Tolerance ±10% Voltage Rating - AC 750V Voltage Rating - DC 3000V (3kV) Dielectric Material Polypropylene (PP), Metallized ESR (Equivalent Series Resistance) 3.8 mOhm Operating Temperature -40°C ~ 85°C Mounting Type Chassis Mount Package / Case Rectangular Box Size / Dimension 2.264" L x 1.378" W (57.50mm x 35.00mm) Height - Seated (Max) 1.969" (50.00mm) Termination - Lead Spacing - Applications DC Link, DC Filtering; High Frequency, Switching; Snubber Features -	Series	PMB	
Voltage Rating - AC Voltage Rating - DC 3000V (3kV) Dielectric Material Polypropylene (PP), Metallized ESR (Equivalent Series Resistance) 3.8 mOhm Operating Temperature -40°C ~ 85°C Mounting Type Chassis Mount Package / Case Rectangular Box Size / Dimension 2.264" L x 1.378" W (57.50mm x 35.00mm) Height - Seated (Max) 1.969" (50.00mm) Termination - Lead Spacing Applications DC Link, DC Filtering; High Frequency, Switching; Snubber Features -	Capacitance	0.47μF	
Voltage Rating - DC Dielectric Material Polypropylene (PP), Metallized ESR (Equivalent Series Resistance) 3.8 mOhm Operating Temperature -40°C ~ 85°C Mounting Type Chassis Mount Package / Case Rectangular Box Size / Dimension 2.264" L x 1.378" W (57.50mm x 35.00mm) Height - Seated (Max) 1.969" (50.00mm) Termination - Lead Spacing Applications DC Link, DC Filtering; High Frequency, Switching; Snubber Features -	Tolerance	±10%	
Dielectric Material Polypropylene (PP), Metallized ESR (Equivalent Series Resistance) 3.8 mOhm Operating Temperature -40°C ~ 85°C Mounting Type Chassis Mount Package / Case Rectangular Box Size / Dimension 2.264" L x 1.378" W (57.50mm x 35.00mm) Height - Seated (Max) 1.969" (50.00mm) Termination - Lead Spacing Applications DC Link, DC Filtering; High Frequency, Switching; Snubber Features -	Voltage Rating - AC	750V	
ESR (Equivalent Series Resistance) 3.8 mOhm Operating Temperature -40°C ~ 85°C Mounting Type Chassis Mount Package / Case Rectangular Box Size / Dimension 2.264" L x 1.378" W (57.50mm x 35.00mm) Height - Seated (Max) 1.969" (50.00mm) Termination Lead Spacing Applications DC Link, DC Filtering; High Frequency, Switching; Snubber Features -	Voltage Rating - DC	3000V (3kV)	
Operating Temperature -40°C ~ 85°C Mounting Type Chassis Mount Package / Case Rectangular Box Size / Dimension 2.264" L x 1.378" W (57.50mm x 35.00mm) Height - Seated (Max) 1.969" (50.00mm) Termination - Lead Spacing - Applications DC Link, DC Filtering; High Frequency, Switching; Snubber Features -	Dielectric Material	Polypropylene (PP), Metallized	
Mounting Type Chassis Mount Package / Case Rectangular Box Size / Dimension 2.264" L x 1.378" W (57.50mm x 35.00mm) Height - Seated (Max) 1.969" (50.00mm) Termination - Lead Spacing - Applications DC Link, DC Filtering; High Frequency, Switching; Snubber Features -	ESR (Equivalent Series Resistance)	3.8 mOhm	
Package / Case Rectangular Box Size / Dimension 2.264" L x 1.378" W (57.50mm x 35.00mm) Height - Seated (Max) 1.969" (50.00mm) Termination - Lead Spacing - Applications DC Link, DC Filtering; High Frequency, Switching; Snubber Features -	Operating Temperature	-40°C ~ 85°C	
Size / Dimension 2.264" L x 1.378" W (57.50mm x 35.00mm) Height - Seated (Max) 1.969" (50.00mm) Termination - Lead Spacing - Applications DC Link, DC Filtering; High Frequency, Switching; Snubber Features -	Mounting Type	Chassis Mount	
Height - Seated (Max) Termination Lead Spacing Applications DC Link, DC Filtering; High Frequency, Switching; Snubber Features -	Package / Case	Rectangular Box	
Termination - Lead Spacing - Applications DC Link, DC Filtering; High Frequency, Switching; Snubber Features -	Size / Dimension	2.264" L x 1.378" W (57.50mm x 35.00mm)	
Lead Spacing - Applications DC Link, DC Filtering; High Frequency, Switching; Snubber Features -	Height - Seated (Max)	1.969" (50.00mm)	
Applications DC Link, DC Filtering; High Frequency, Switching; Snubber Features -	Termination	-	
Features -	Lead Spacing	-	
	Applications	DC Link, DC Filtering; High Frequency, Switching; Snubber	
Report errors?	Features	-	
			Report errors?

474PMB302KA Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

474PMB302KA Payment Methods





















474PMB302KA Shipping Methods













If you have any question about 474PMB302KA, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com