



475CKS450MLN Information



For Reference Only

Part Number 475CKS450MLN
Manufacturer Illinois Capacitor

Category Capacitors

Aluminum Electrolytic Capacitors

Description CAP ALUM 4.7UF 20% 450V T/H

Package Radial, Can

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









475CKS450MLN Specifications

Manufacturer Part Number 475CKS450MLN Manufacturer Illinois Capacitor Category Capacitors Package Radial, Can Series CKS Capacitance 4.7µF Tolerance ±20% Voltage - Rated 450V ESR (Equivalent Series Resistance) 70.547 Ohm @ 120Hz Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -25°C ~ 85°C Polarization General Purpose Ripple Current - Low Frequency 70mA @ 120Hz Ripple Current - High Frequency 175mA @ 100kHz Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) 0.551" (14.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can		
Category Capacitors Package Radial, Can Series CKS Capacitance 4.7 μF Tolerance ±20% Voltage - Rated 450 V ESR (Equivalent Series Resistance) 70.547 Ohm @ 120Hz Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -25°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 70mA @ 120Hz Ripple Current - High Frequency 175mA @ 100kHz Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) 0.551" (14.00mm) Surface Mount Land Size - Mounting Type Through Hole	Manufacturer Part Number	475CKS450MLN
Package Radial, Can Series CKS Capacitance 4.7μF Tolerance ±20% Voltage - Rated 450V ESR (Equivalent Series Resistance) 70.547 Ohm @ 120Hz Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -25°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 70mA @ 120Hz Ripple Current - High Frequency 175mA @ 100kHz Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) 0.551" (14.00mm) Surface Mount Land Size - Mounting Type Through Hole	Manufacturer	Illinois Capacitor
Package Radial, Can Series CKS Capacitance 4.7μF Tolerance ±20% Voltage - Rated 450V ESR (Equivalent Series Resistance) 70.547 Ohm @ 120Hz Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -25°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 70mA @ 120Hz Ripple Current - High Frequency 175mA @ 100kHz Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) 0.551" (14.00mm) Surface Mount Land Size - Mounting Type Through Hole	Category	Capacitors
Series CKS Capacitance 4.7µF Tolerance ±20% Voltage - Rated 450V ESR (Equivalent Series Resistance) 70.547 Ohm @ 120Hz Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -25°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 70mA @ 120Hz Ripple Current - High Frequency 175mA @ 100kHz Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) 0.551" (14.00mm) Surface Mount Land Size - Mounting Type Through Hole		Aluminum Electrolytic Capacitors
Capacitance 4.7μF Tolerance ±20% Voltage - Rated 450V ESR (Equivalent Series Resistance) 70.547 Ohm @ 120Hz Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -25°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 70mA @ 120Hz Ripple Current - High Frequency 175mA @ 100kHz Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) 0.551" (14.00mm) Surface Mount Land Size - Mounting Type Through Hole	Package	Radial, Can
Tolerance ±20% Voltage - Rated 450V ESR (Equivalent Series Resistance) 70.547 Ohm @ 120Hz Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -25°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 70mA @ 120Hz Ripple Current - High Frequency 175mA @ 100kHz Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) 0.551" (14.00mm) Surface Mount Land Size - Mounting Type Through Hole	Series	CKS
Voltage - Rated450VESR (Equivalent Series Resistance)70.547 Ohm @ 120HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature-25°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency70mA @ 120HzRipple Current - High Frequency175mA @ 100kHzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.551" (14.00mm)Surface Mount Land Size-Mounting TypeThrough Hole	Capacitance	4.7μF
ESR (Equivalent Series Resistance) Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -25°C ~ 85°C Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency 175mA @ 120Hz Rippedance Lead Spacing 0.197" (5.00mm) Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type 70.547 Ohm @ 120Hz 2000 Hrs @ 85°C -25°C ~ 85°C Polar -25°C ~ 85°C -200 Hrs @ 85°C -200 Hrs @ 85°C -25°C ~ 85°C -200 Hrs @ 85°C -25°C ~ 85°C -200 Hrs @ 85°C -25°C ~ 85°C -200 Hrs @ 85°C -25°C ~ 85°C -25°C	Tolerance	±20%
Lifetime @ Temp. Operating Temperature -25°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 70mA @ 120Hz Ripple Current - High Frequency 175mA @ 100kHz Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) Surface Mount Land Size Mounting Type 100 Hrs @ 85°C 2000 Hrs @ 85°C Seneral Purpose General Purpose 101 Hughs 102 Hughs 103 Hughs 103 Hughs 104 Hughs 105 Hughs 105 Hughs 106 Hughs 107 Hughs 108 Hughs 1	Voltage - Rated	450V
Operating Temperature -25°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency 175mA @ 120Hz Impedance Lead Spacing 0.197" (5.00mm) Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) 0.551" (14.00mm) Surface Mount Land Size Mounting Type Through Hole	ESR (Equivalent Series Resistance)	70.547 Ohm @ 120Hz
Polarization Polar Applications General Purpose Ripple Current - Low Frequency 70mA @ 120Hz Ripple Current - High Frequency 175mA @ 100kHz Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) 0.551" (14.00mm) Surface Mount Land Size - Mounting Type Through Hole	Lifetime @ Temp.	2000 Hrs @ 85°C
Applications Ripple Current - Low Frequency Ripple Current - High Frequency 175mA @ 120Hz 175mA @ 100kHz Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) 0.551" (14.00mm) Surface Mount Land Size - Mounting Type Through Hole	Operating Temperature	-25°C ~ 85°C
Ripple Current - Low Frequency Ripple Current - High Frequency 175mA @ 100kHz Impedance Lead Spacing 0.197" (5.00mm) Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) 0.551" (14.00mm) Surface Mount Land Size Mounting Type Through Hole	Polarization	Polar
Ripple Current - High Frequency Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) 0.551" (14.00mm) Surface Mount Land Size - Mounting Type Through Hole	Applications	General Purpose
Impedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.551" (14.00mm)Surface Mount Land Size-Mounting TypeThrough Hole	Ripple Current - Low Frequency	70mA @ 120Hz
Lead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.551" (14.00mm)Surface Mount Land Size-Mounting TypeThrough Hole	Ripple Current - High Frequency	175mA @ 100kHz
Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.551" (14.00mm)Surface Mount Land Size-Mounting TypeThrough Hole	Impedance	-
Height - Seated (Max) Surface Mount Land Size Mounting Type 0.551" (14.00mm) - Through Hole	Lead Spacing	0.197" (5.00mm)
Surface Mount Land Size - Mounting Type Through Hole	Size / Dimension	0.394" Dia (10.00mm)
Mounting Type Through Hole	Height - Seated (Max)	0.551" (14.00mm)
	Surface Mount Land Size	-
Package / Case Radial, Can	Mounting Type	Through Hole
	Package / Case	Radial, Can
Report errors?		Report errors?

475CKS450MLN Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

475CKS450MLN Payment Methods



















475CKS450MLN Shipping Methods













If you have any question about 475CKS450MLN, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com