



476CKE250M Information



For Reference Only

Part Number 476CKE250M Manufacturer Illinois Capacitor Category

Capacitors

Aluminum Electrolytic Capacitors

CAP ALUM 47UF 20% 250V RADIAL **Description**

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









476CKE250M Specifications

Manufacturer Part Number 476CKE250M Manufacturer Illinois Capacitor Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can Series CKE Capacitance 47µF Tolerance ±20% Voltage - Rated 250V ESR (Equivalent Series Resistance) 5.291 Ohm @ 120Hz Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -25°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 320mA @ 120Hz Ripple Current - High Frequency - Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.492" Dia (12.50mm) Height - Seated (Max) 1.043" (26.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	•	
Category Capacitors Package Radial, Can Series CKE Capacitance 47µF Tolerance ±20% Voltage - Rated 250V ESR (Equivalent Series Resistance) 5.291 Ohm @ 120Hz Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -25°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 320mA @ 120Hz Ripple Current - High Frequency - Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.492" Dia (12.50mm) Height - Seated (Max) 1.043" (26.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Manufacturer Part Number	476CKE250M
Package Radial, Can Series CKE Capacitance 47μF Tolerance ±20% Voltage - Rated 250V ESR (Equivalent Series Resistance) 5.291 Ohm @ 120Hz Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -25°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 320mA @ 120Hz Ripple Current - High Frequency - Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.492" Dia (12.50mm) Height - Seated (Max) 1.043" (26.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Manufacturer	Illinois Capacitor
Package Radial, Can Series CKE Capacitance 47μF Tolerance ±20% Voltage - Rated 250V ESR (Equivalent Series Resistance) 5.291 Ohm @ 120Hz Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -25°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 320mA @ 120Hz Ripple Current - High Frequency - Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.492" Dia (12.50mm) Height - Seated (Max) 1.043" (26.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Category	Capacitors
Series CKE Capacitance 47µF Tolerance ±20% Voltage - Rated 250V ESR (Equivalent Series Resistance) 5.291 Ohm @ 120Hz Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -25°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 320mA @ 120Hz Ripple Current - High Frequency - Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.492" Dia (12.50mm) Height - Seated (Max) 1.043" (26.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can		Aluminum Electrolytic Capacitors
Capacitance 47μF Tolerance ±20% Voltage - Rated 250V ESR (Equivalent Series Resistance) 5.291 Ohm @ 120Hz Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -25°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 320mA @ 120Hz Ripple Current - High Frequency - Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.492" Dia (12.50mm) Height - Seated (Max) 1.043" (26.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Package	Radial, Can
Tolerance ±20% Voltage - Rated 250V ESR (Equivalent Series Resistance) 5.291 Ohm @ 120Hz Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -25°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 320mA @ 120Hz Ripple Current - High Frequency - Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.492" Dia (12.50mm) Height - Seated (Max) 1.043" (26.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Series	CKE
Voltage - Rated250VESR (Equivalent Series Resistance)5.291 Ohm @ 120HzLifetime @ Temp.2000 Hrs @ 105°COperating Temperature-25°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency320mA @ 120HzRipple Current - High Frequency-Impedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)1.043" (26.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Capacitance	47μF
ESR (Equivalent Series Resistance) Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -25°C ~ 105°C Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Impedance Lead Spacing 0.197" (5.00mm) Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case 8.291 Ohm @ 120Hz 2000 Hrs @ 105°C -25°C ~ 105°C -25°C ~ 105°C -25°C ~ 105°C -25°C ~ 105°C -2105°C -	Tolerance	±20%
Lifetime @ Temp. Operating Temperature -25°C ~ 105°C Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Impedance Lead Spacing Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Polar -25°C ~ 105°C Folia (105°C General Purpose 320mA @ 120Hz 320mA @ 120Hz -320mA @ 12	Voltage - Rated	250V
Operating Temperature Polarization Polar Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Polar Ripple Current - High Frequency Ripple Current - High Frequency Polar Impedance Purpose Polar Impedance Purpose Polar	ESR (Equivalent Series Resistance)	5.291 Ohm @ 120Hz
Polarization Polar Applications General Purpose Ripple Current - Low Frequency 320mA @ 120Hz Ripple Current - High Frequency - Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.492" Dia (12.50mm) Height - Seated (Max) 1.043" (26.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Lifetime @ Temp.	2000 Hrs @ 105°C
Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency	Operating Temperature	-25°C ~ 105°C
Ripple Current - Low Frequency Ripple Current - High Frequency Impedance Lead Spacing 0.197" (5.00mm) Size / Dimension 0.492" Dia (12.50mm) Height - Seated (Max) 1.043" (26.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Polarization	Polar
Ripple Current - High Frequency - Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.492" Dia (12.50mm) Height - Seated (Max) 1.043" (26.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Applications	General Purpose
Impedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)1.043" (26.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - Low Frequency	320mA @ 120Hz
Lead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)1.043" (26.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - High Frequency	-
Size / Dimension 0.492" Dia (12.50mm) Height - Seated (Max) 1.043" (26.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Impedance	-
Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can	Lead Spacing	0.197" (5.00mm)
Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Size / Dimension	0.492" Dia (12.50mm)
Mounting Type Through Hole Package / Case Radial, Can	Height - Seated (Max)	1.043" (26.50mm)
Package / Case Radial, Can	Surface Mount Land Size	-
-	Mounting Type	Through Hole
Papart arrors?	Package / Case	Radial, Can
Report cross:		Report errors?

476CKE250M Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

476CKE250M Payment Methods



















476CKE250M Shipping Methods













If you have any question about 476CKE250M, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com