



476SVL016MEW Information



For Reference Only

Part Number 476SVL016MEW
Manufacturer Illinois Capacitor
Category Capacitors

ry Capacitors
Aluminum Electrolytic Capacitors

Description CAP ALUM 47UF 20% 16V SMD

Package Radial, Can - SMD

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









476SVL016MEW Specifications

Manufacturer Part Number 476SVL016MEW Manufacturer Illinois Capacitor Category Capacitors Package Radial, Can - SMD Series SVL Capacitance 47µF Tolerance ±20% Voltage - Rated 16V ESR (Equivalent Series Resistance) 7.05 Ohm @ 120Hz Lifetime @ Temp. 3000 Hrs @ 105°C Operating Temperature -55°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 60mA @ 120Hz Ripple Current - High Frequency 90mA @ 100kHz Impedance - Lead Spacing - Size / Dimension 0.248" Dia (6.30mm) Height - Seated (Max) 0.232" (5.90mm) Surface Mount Land Size 0.260" L x 0.260" W (6.60mm x 6.60mm) Mounting Type Surface Mount Package / Case Radial, Can - SMD	•	
Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can - SMD Series SVL Capacitance 47μF Tolerance ±20% Voltage - Rated 16V ESR (Equivalent Series Resistance) 7.05 Ohm @ 120Hz Lifetime @ Temp. 3000 Hrs @ 105°C Operating Temperature -55°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 60mA @ 120Hz Ripple Current - High Frequency 90mA @ 100kHz Impedance - Lead Spacing - Size / Dimension 0.248" Dia (6.30mm) Height - Seated (Max) 0.232" (5.90mm) Surface Mount Land Size 0.260" L x 0.260" W (6.60mm x 6.60mm) Mounting Type Surface Mount Package / Case Radial, Can - SMD	Manufacturer Part Number	476SVL016MEW
Package Radial, Can - SMD Series SVL Capacitance 47μF Tolerance ±20% Voltage - Rated 16V ESR (Equivalent Series Resistance) 7.05 Ohm @ 120Hz Lifetime @ Temp. 3000 Hrs @ 105°C Operating Temperature -55°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 60mA @ 120Hz Ripple Current - High Frequency 90mA @ 100kHz Impedance - Lead Spacing - Size / Dimension 0.248" Dia (6.30mm) Height - Seated (Max) 0.232" (5.90mm) Surface Mount Land Size 0.260" L x 0.260" W (6.60mm x 6.60mm) Mounting Type Surface Mount Package / Case Radial, Can - SMD	Manufacturer	Illinois Capacitor
Package Radial, Can - SMD Series SVL Capacitance 47μF Tolerance ±20% Voltage - Rated 16V ESR (Equivalent Series Resistance) 7.05 Ohm @ 120Hz Lifetime @ Temp. 3000 Hrs @ 105°C Operating Temperature -55°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 60mA @ 120Hz Ripple Current - High Frequency 90mA @ 100kHz Impedance - Lead Spacing - Size / Dimension 0.248" Dia (6.30mm) Height - Seated (Max) 0.232" (5.90mm) Surface Mount Land Size 0.260" L x 0.260" W (6.60mm x 6.60mm) Mounting Type Surface Mount Package / Case Radial, Can - SMD	Category	Capacitors
Series SVL Capacitance 47μF Tolerance ±20% Voltage - Rated 16V ESR (Equivalent Series Resistance) 7.05 Ohm @ 120Hz Lifetime @ Temp. 3000 Hrs @ 105°C Operating Temperature -55°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 60mA @ 120Hz Ripple Current - High Frequency 90mA @ 100kHz Impedance - Lead Spacing - Size / Dimension 0.248" Dia (6.30mm) Height - Seated (Max) 0.232" (5.90mm) Surface Mount Land Size 0.260" L x 0.260" W (6.60mm x 6.60mm) Mounting Type Surface Mount Package / Case Radial, Can - SMD		Aluminum Electrolytic Capacitors
Capacitance 47µF Tolerance ±20% Voltage - Rated 16V ESR (Equivalent Series Resistance) 7.05 Ohm @ 120Hz Lifetime @ Temp. 3000 Hrs @ 105°C Operating Temperature -55°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 60mA @ 120Hz Ripple Current - High Frequency 90mA @ 100kHz Impedance - Lead Spacing - Size / Dimension 0.248" Dia (6.30mm) Height - Seated (Max) 0.232" (5.90mm) Surface Mount Land Size 0.260" L x 0.260" W (6.60mm x 6.60mm) Mounting Type Surface Mount Package / Case Radial, Can - SMD	Package	Radial, Can - SMD
Tolerance ±20% Voltage - Rated 16V ESR (Equivalent Series Resistance) 7.05 Ohm @ 120Hz Lifetime @ Temp. 3000 Hrs @ 105°C Operating Temperature -55°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 60mA @ 120Hz Ripple Current - High Frequency 90mA @ 100kHz Impedance - Lead Spacing - Size / Dimension 0.248" Dia (6.30mm) Height - Seated (Max) 0.232" (5.90mm) Surface Mount Land Size 0.260" L x 0.260" W (6.60mm x 6.60mm) Mounting Type Surface Mount Package / Case Radial, Can - SMD	Series	SVL
Voltage - Rated ESR (Equivalent Series Resistance) 7.05 Ohm @ 120Hz Lifetime @ Temp. 3000 Hrs @ 105°C Operating Temperature -55°C ~ 105°C Polarization Applications General Purpose Ripple Current - Low Frequency 60mA @ 120Hz Ripple Current - High Frequency 90mA @ 100kHz Impedance - Lead Spacing - Size / Dimension 0.248" Dia (6.30mm) Height - Seated (Max) 0.232" (5.90mm) Surface Mount Land Size 0.260" L x 0.260" W (6.60mm x 6.60mm) Mounting Type Surface Mount Package / Case Radial, Can - SMD	Capacitance	47μF
ESR (Equivalent Series Resistance) Lifetime @ Temp. 3000 Hrs @ 105°C Operating Temperature -55°C ~ 105°C Polarization Applications General Purpose Ripple Current - Low Frequency 60mA @ 120Hz Ripple Current - High Frequency 90mA @ 100kHz Impedance - Lead Spacing - Size / Dimension Height - Seated (Max) Surface Mount Land Size 0.260" L x 0.260" W (6.60mm x 6.60mm) Mounting Type Surface Mount Package / Case Radial, Can - SMD	Tolerance	±20%
Lifetime @ Temp. Operating Temperature -55°C ~ 105°C Polarization Applications General Purpose Ripple Current - Low Frequency 60mA @ 120Hz Ripple Current - High Frequency 90mA @ 100kHz Impedance - Lead Spacing Size / Dimension 0.248" Dia (6.30mm) Height - Seated (Max) Surface Mount Land Size 0.260" L x 0.260" W (6.60mm x 6.60mm) Mounting Type Package / Case Radial, Can - SMD	Voltage - Rated	16V
Operating Temperature Polarization Polar Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency PomA @ 120Hz Rippedance Lead Spacing Size / Dimension Height - Seated (Max) Surface Mount Land Size Pockage / Case Polar Pola	ESR (Equivalent Series Resistance)	7.05 Ohm @ 120Hz
Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Rount End Species - Lead Spacing Size / Dimension - Size / Dimension Rount (6.30mm) Rounting Type Rount Land Size - Surface Mount Rount Rount Radial, Can - SMD	Lifetime @ Temp.	3000 Hrs @ 105°C
Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency 90mA @ 100kHz Impedance - Lead Spacing 5ize / Dimension 0.248" Dia (6.30mm) Height - Seated (Max) Surface Mount Land Size 0.260" L x 0.260" W (6.60mm x 6.60mm) Mounting Type Surface Mount Package / Case Radial, Can - SMD	Operating Temperature	-55°C ~ 105°C
Ripple Current - Low Frequency 60mA @ 120Hz Ripple Current - High Frequency 90mA @ 100kHz Impedance - Lead Spacing - Size / Dimension 0.248" Dia (6.30mm) Height - Seated (Max) 0.232" (5.90mm) Surface Mount Land Size 0.260" L x 0.260" W (6.60mm x 6.60mm) Mounting Type Surface Mount Package / Case Radial, Can - SMD	Polarization	Polar
Ripple Current - High Frequency 90mA @ 100kHz Impedance - Lead Spacing - Size / Dimension 0.248" Dia (6.30mm) Height - Seated (Max) 0.232" (5.90mm) Surface Mount Land Size 0.260" L x 0.260" W (6.60mm x 6.60mm) Mounting Type Surface Mount Package / Case Radial, Can - SMD	Applications	General Purpose
Impedance - Lead Spacing - Size / Dimension 0.248" Dia (6.30mm) Height - Seated (Max) 0.232" (5.90mm) Surface Mount Land Size 0.260" L x 0.260" W (6.60mm x 6.60mm) Mounting Type Surface Mount Package / Case Radial, Can - SMD	Ripple Current - Low Frequency	60mA @ 120Hz
Lead Spacing - O.248" Dia (6.30mm) Height - Seated (Max) O.232" (5.90mm) Surface Mount Land Size O.260" L x 0.260" W (6.60mm x 6.60mm) Mounting Type Surface Mount Package / Case Radial, Can - SMD	Ripple Current - High Frequency	90mA @ 100kHz
Size / Dimension0.248" Dia (6.30mm)Height - Seated (Max)0.232" (5.90mm)Surface Mount Land Size0.260" L x 0.260" W (6.60mm x 6.60mm)Mounting TypeSurface MountPackage / CaseRadial, Can - SMD	Impedance	-
Height - Seated (Max) Surface Mount Land Size 0.260" L x 0.260" W (6.60mm x 6.60mm) Mounting Type Surface Mount Package / Case Radial, Can - SMD	Lead Spacing	-
Surface Mount Land Size 0.260" L x 0.260" W (6.60mm x 6.60mm) Mounting Type Surface Mount Package / Case Radial, Can - SMD	Size / Dimension	0.248" Dia (6.30mm)
Mounting Type Surface Mount Package / Case Radial, Can - SMD	Height - Seated (Max)	0.232" (5.90mm)
Package / Case Radial, Can - SMD	Surface Mount Land Size	0.260" L x 0.260" W (6.60mm x 6.60mm)
	Mounting Type	Surface Mount
	Package / Case	Radial, Can - SMD
Report errors?		Report errors?

476SVL016MEW Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

476SVL016MEW Payment Methods





















476SVL016MEW Shipping Methods













If you have any question about 476SVL016MEW, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com