



477ULR010MFF Information



For Reference Only

Part Number 477ULR010MFF
Manufacturer Illinois Capacitor
Category Capacitors

Aluminum - Polymer Capacitors

Description CAP ALUM POLY 470UF 20% 10V T/H

Package Radial, Car

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









477ULR010MFF Specifications

Manufacturer Part Number 477ULR010MFF Manufacturer Illinois Capacitor Category Capacitors Aluminum - Polymer Capacitors Package Radial, Can Series ULR Type Polymer Capacitance 470μF Tolerance ±20% Voltage - Rated 10V ESR (Equivalent Series Resistance) 350 mOhm Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -55°C ~ 105°C Applications Decoupling Ripple Current - Low Frequency 250mA @ 120Hz Ripple Current - High Frequency 5A @ 100kHz Impedance - Lead Spacing 0.138" (3.50mm) Size / Dimension 0.315" Dia (8.00mm) Height - Seated (Max) 0.354" (9.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	_	
Category Capacitors Package Radial, Can Series ULR Type Polymer Capacitance 470µF Tolerance ±20% Voltage - Rated 10V ESR (Equivalent Series Resistance) 350 mOhm Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -55°C ~ 105°C Applications Decoupling Ripple Current - Low Frequency 250mA @ 120Hz Ripple Current - High Frequency 5A @ 100kHz Impedance - Lead Spacing 0.138" (3.50mm) Size / Dimension 0.315" Dia (8.00mm) Height - Seated (Max) 0.354" (9.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Manufacturer Part Number	477ULR010MFF
PackageAluminum - Polymer CapacitorsPackageRadial, CanSeriesULRTypePolymerCapacitance470μFTolerance±20%Voltage - Rated10VESR (Equivalent Series Resistance)350 mOhmLifetime @ Temp.2000 Hrs @ 105°COperating Temperature-55°C ~ 105°CApplicationsDecouplingRipple Current - Low Frequency250mA @ 120HzRipple Current - High Frequency5A @ 100kHzImpedance-Lead Spacing0.138" (3.50mm)Size / Dimension0.315" Dia (8.00mm)Height - Seated (Max)0.354" (9.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Manufacturer	Illinois Capacitor
PackageRadial, CanSeriesULRTypePolymerCapacitance470μFTolerance±20%Voltage - Rated10VESR (Equivalent Series Resistance)350 mOhmLifetime @ Temp.2000 Hrs @ 105°COperating Temperature-55°C ~ 105°CApplicationsDecouplingRipple Current - Low Frequency250mA @ 120HzRipple Current - High Frequency5A @ 100kHzImpedance-Lead Spacing0.138" (3.50mm)Size / Dimension0.315" Dia (8.00mm)Height - Seated (Max)0.354" (9.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Category	Capacitors
Series ULR Type Polymer Capacitance 470μF Tolerance ±20% Voltage - Rated 10V ESR (Equivalent Series Resistance) 350 mOhm Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -55°C ~ 105°C Applications Decoupling Ripple Current - Low Frequency 250mA @ 120Hz Ripple Current - High Frequency 5A @ 100kHz Impedance - Lead Spacing 0.138" (3.50mm) Size / Dimension 0.315" Dia (8.00mm) Height - Seated (Max) 0.354" (9.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can		Aluminum - Polymer Capacitors
Type Polymer Capacitance 470μF Tolerance ±20% Voltage - Rated 10V ESR (Equivalent Series Resistance) 350 mOhm Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -55°C ~ 105°C Applications Decoupling Ripple Current - Low Frequency 250mA @ 120Hz Ripple Current - High Frequency 5A @ 100kHz Impedance - Lead Spacing 0.138" (3.50mm) Size / Dimension 0.315" Dia (8.00mm) Height - Seated (Max) 0.354" (9.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Package	Radial, Can
Capacitance 470μF Tolerance ±20% Voltage - Rated 10V ESR (Equivalent Series Resistance) 350 mOhm Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -55°C ~ 105°C Applications Decoupling Ripple Current - Low Frequency 250mA @ 120Hz Ripple Current - High Frequency 5A @ 100kHz Impedance - Lead Spacing 0.138" (3.50mm) Size / Dimension 0.315" Dia (8.00mm) Height - Seated (Max) 0.354" (9.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Series	ULR
Tolerance ±20% Voltage - Rated 10V ESR (Equivalent Series Resistance) 350 mOhm Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -55°C ~ 105°C Applications Decoupling Ripple Current - Low Frequency 250mA @ 120Hz Ripple Current - High Frequency 5A @ 100kHz Impedance - Lead Spacing 0.138" (3.50mm) Size / Dimension 0.315" Dia (8.00mm) Height - Seated (Max) 0.354" (9.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Туре	Polymer
Voltage - Rated10VESR (Equivalent Series Resistance)350 mOhmLifetime @ Temp.2000 Hrs @ 105°COperating Temperature-55°C ~ 105°CApplicationsDecouplingRipple Current - Low Frequency250mA @ 120HzRipple Current - High Frequency5A @ 100kHzImpedance-Lead Spacing0.138" (3.50mm)Size / Dimension0.315" Dia (8.00mm)Height - Seated (Max)0.354" (9.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Capacitance	470μF
ESR (Equivalent Series Resistance) Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -55°C ~ 105°C Applications Decoupling Ripple Current - Low Frequency 250mA @ 120Hz Ripple Current - High Frequency 5A @ 100kHz Impedance Lead Spacing 0.138" (3.50mm) Size / Dimension 0.315" Dia (8.00mm) Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can	Tolerance	±20%
Lifetime @ Temp. Operating Temperature -55°C ~ 105°C Applications Decoupling Ripple Current - Low Frequency SA @ 120Hz Ripple Current - High Frequency 5A @ 100kHz Impedance Lead Spacing 0.138" (3.50mm) Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case 2000 Hrs @ 105°C -55°C ~ 105°C -105°C	Voltage - Rated	10V
Operating Temperature -55°C ~ 105°C Applications Decoupling Ripple Current - Low Frequency 250mA @ 120Hz Ripple Current - High Frequency 5A @ 100kHz Impedance - Lead Spacing 0.138" (3.50mm) Size / Dimension 0.315" Dia (8.00mm) Height - Seated (Max) 0.354" (9.00mm) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can	ESR (Equivalent Series Resistance)	350 mOhm
Applications Ripple Current - Low Frequency Ripple Current - High Frequency SA @ 100kHz Impedance Lead Spacing O.138" (3.50mm) Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case Decoupling D	Lifetime @ Temp.	2000 Hrs @ 105°C
Ripple Current - Low Frequency Ripple Current - High Frequency 5A @ 100kHz Impedance - Lead Spacing 0.138" (3.50mm) Size / Dimension 0.315" Dia (8.00mm) Height - Seated (Max) 0.354" (9.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Operating Temperature	-55°C ~ 105°C
Ripple Current - High Frequency Impedance Lead Spacing Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case SA @ 100kHz	Applications	Decoupling
Impedance - Lead Spacing 0.138" (3.50mm) Size / Dimension 0.315" Dia (8.00mm) Height - Seated (Max) 0.354" (9.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Ripple Current - Low Frequency	250mA @ 120Hz
Lead Spacing0.138" (3.50mm)Size / Dimension0.315" Dia (8.00mm)Height - Seated (Max)0.354" (9.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - High Frequency	5A @ 100kHz
Size / Dimension 0.315" Dia (8.00mm) Height - Seated (Max) 0.354" (9.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Impedance	-
Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can	Lead Spacing	0.138" (3.50mm)
Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Size / Dimension	0.315" Dia (8.00mm)
Mounting Type Through Hole Package / Case Radial, Can	Height - Seated (Max)	0.354" (9.00mm)
Package / Case Radial, Can	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can
*		Report errors?

477ULR010MFF Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

477ULR010MFF Payment Methods



















477ULR010MFF Shipping Methods













If you have any question about 477ULR010MFF, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com