

4850.2410 Information

Heisener.com

Part Number 4850.2410 Manufacturer Schurter Inc.

Category Connectors, Interconnects

Circular Connectors

Description CONN DIN 4POS FEMALE PCB RT ANG

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com

ept@heisener.com

Request a Quote



Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









4850.2410 Specifications

Manufacturer Part Number4850.2410ManufacturerSchurter Inc.CategoryConnectors, InterconnectsPackage-Series4850Connector TypeReceptacle, Female SocketsNumber of Positions4Shell Size - InsertMini DINShell Size, MIL-Mounting TypeThrough Hole, Right AngleTerminationSolderFastening TypePush-PullOrientationKeyedIngress Protection-Shell Material, FinishPolybutylene Terephthalate (PBT)Contact Finish-FeaturesBoard LockVoltage - Rated12VAC/DC		
CategoryConnectors, Interconnects Circular ConnectorsPackage-Series4850Connector TypeReceptacle, Female SocketsNumber of Positions4Shell Size - InsertMini DINShell Size, MIL-Mounting TypeThrough Hole, Right AngleTerminationSolderFastening TypePush-PullOrientationKeyedIngress Protection-Shell Material, FinishPolybutylene Terephthalate (PBT)Contact Finish-FeaturesBoard LockVoltage - Rated12VAC/DC	Manufacturer Part Number	4850.2410
Circular Connectors Package - Series 4850 Connector Type Receptacle, Female Sockets Number of Positions 4 Shell Size - Insert Mini DIN Shell Size, MIL - Mounting Type Through Hole, Right Angle Termination Solder Fastening Type Push-Pull Orientation Keyed Ingress Protection Shell Material, Finish Polybutylene Terephthalate (PBT) Contact Finish - Features Board Lock Voltage - Rated	Manufacturer	Schurter Inc.
Package-Series4850Connector TypeReceptacle, Female SocketsNumber of Positions4Shell Size - InsertMini DINShell Size, MIL-Mounting TypeThrough Hole, Right AngleTerminationSolderFastening TypePush-PullOrientationKeyedIngress Protection-Shell Material, FinishPolybutylene Terephthalate (PBT)Contact Finish-FeaturesBoard LockVoltage - Rated12VAC/DC	Category	Connectors, Interconnects
Series 4850 Connector Type Receptacle, Female Sockets Number of Positions 4 Shell Size - Insert Mini DIN Shell Size, MIL - Mounting Type Through Hole, Right Angle Termination Solder Fastening Type Push-Pull Orientation Keyed Ingress Protection - Shell Material, Finish Polybutylene Terephthalate (PBT) Contact Finish - Features Board Lock Voltage - Rated 12VAC/DC		Circular Connectors
Connector Type Receptacle, Female Sockets Number of Positions 4 Shell Size - Insert Mini DIN Shell Size, MIL - Mounting Type Through Hole, Right Angle Termination Solder Fastening Type Push-Pull Orientation Keyed Ingress Protection - Shell Material, Finish Polybutylene Terephthalate (PBT) Contact Finish - Features Voltage - Rated 12VAC/DC	Package	-
Number of Positions Shell Size - Insert Mini DIN Shell Size, MIL Mounting Type Through Hole, Right Angle Solder Fastening Type Push-Pull Orientation Keyed Ingress Protection Shell Material, Finish Polybutylene Terephthalate (PBT) Contact Finish - Features Board Lock Voltage - Rated	Series	4850
Shell Size - Insert Shell Size, MIL - Mounting Type Through Hole, Right Angle Termination Solder Fastening Type Push-Pull Orientation Keyed Ingress Protection Shell Material, Finish Polybutylene Terephthalate (PBT) Contact Finish - Features Board Lock Voltage - Rated	Connector Type	Receptacle, Female Sockets
Shell Size, MIL Mounting Type Through Hole, Right Angle Termination Solder Fastening Type Push-Pull Orientation Keyed Ingress Protection - Shell Material, Finish Polybutylene Terephthalate (PBT) Contact Finish - Features Board Lock Voltage - Rated 12VAC/DC	Number of Positions	4
Mounting TypeThrough Hole, Right AngleTerminationSolderFastening TypePush-PullOrientationKeyedIngress Protection-Shell Material, FinishPolybutylene Terephthalate (PBT)Contact Finish-FeaturesBoard LockVoltage - Rated12VAC/DC	Shell Size - Insert	Mini DIN
Termination Solder Fastening Type Push-Pull Orientation Keyed Ingress Protection - Shell Material, Finish Polybutylene Terephthalate (PBT) Contact Finish - Features Board Lock Voltage - Rated 12VAC/DC	Shell Size, MIL	-
Fastening Type Push-Pull Orientation Keyed Ingress Protection - Shell Material, Finish Polybutylene Terephthalate (PBT) Contact Finish - Features Board Lock Voltage - Rated 12VAC/DC	Mounting Type	Through Hole, Right Angle
Orientation Keyed Ingress Protection - Shell Material, Finish Polybutylene Terephthalate (PBT) Contact Finish - Features Board Lock Voltage - Rated 12VAC/DC	Termination	Solder
Ingress Protection - Shell Material, Finish Polybutylene Terephthalate (PBT) Contact Finish - Features Board Lock Voltage - Rated 12VAC/DC	Fastening Type	Push-Pull
Shell Material, Finish Contact Finish Features Board Lock Voltage - Rated Polybutylene Terephthalate (PBT) - Board Lock 12VAC/DC	Orientation	Keyed
Contact Finish - Features Board Lock Voltage - Rated 12VAC/DC	Ingress Protection	-
Features Board Lock Voltage - Rated 12VAC/DC	Shell Material, Finish	Polybutylene Terephthalate (PBT)
Voltage - Rated 12VAC/DC	Contact Finish	-
	Features	Board Lock
	Voltage - Rated	12VAC/DC
Current Rating 2A	Current Rating	2A
Report errors?		Report errors?

4850.2410 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

4850.2410 Payment Methods





















4850.2410 Shipping Methods













If you have any question about 4850.2410, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com