

4MA133330Z3BACTGI

4MA133330Z3BACTGI Information

Heisener.com	 4MA133330Z3BACTGI IDT, Integrated Device Technology Inc Crystals, Oscillators, Resonators Oscillators OSC MEMS 133.33MHZ LVPECL SMD 6-SMD, No Lead For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



4MA133330Z3BACTGI Specifications

ManufacturerIDT, Integrated Device Technology IncCategoryCrystals, Oscillators, ResonatorsOscillatorsOscillatorsPackage6-SMD, No LeadSeries4MATypeMEMS (Silicon)Frequency133.33MHzFunctionEnable/DisableOutputLVPECLVoltage - Supply2.5VFrequency Stability50ppmOperating Temperature40°C ~ 85°CCurrent - Supply (Max)Surface MountRatings-Package / Case6-SMD, No LeadSize / Dimension0.197" L x 0.126" W (5.00mm x 3.20mm)		
CategoryCrystals, Oscillators, ResonatorsOscillatorsPackage6-SMD, No LeadSeries4MATypeMEMS (Silicon)Frequency133.33MHzFunctionEnable/DisableOutputLVPECLVoltage - Supply2.5VFrequency Stability±50ppmOperating Temperature-40°C ~ 85°CCurrent - Supply (Max)-Ratings-Mounting TypeSurface MountPackage / Case6-SMD, No LeadSize / Dimension0.035" (0.90mm)	Manufacturer Part Number	4MA133330Z3BACTGI
OscillatorsPackage6-SMD, No LeadSeries4MATypeMEMS (Silicon)Frequency133.33MHzFunctionEnable/DisableOutputLVPECLVoltage - Supply2.5VFrequency Stability±50pmOperating Temperature44°C ~ 85°CCurrent - Supply (Max)-Ratings-Package / Case6-SMD, No LeadSize / Dimension0.197" L x 0.126" W (5.00mm x 3.20mm)Height - Seated (Max)0.035" (0.90mm)	Manufacturer	IDT, Integrated Device Technology Inc
Package 6-SMD, No Lead Series 4MA Type MEMS (Silicon) Frequency 133.33MHz Function Enable/Disable Output LVPECL Voltage - Supply 2.5V Frequency Stability 40°C ~ 85°C Ourput -40°C ~ 85°C Current - Supply (Max) - Ratings - Mounting Type Surface Mount Package / Case 6-SMD, No Lead Size / Dimension 0.197" L x 0.126" W (5.00mm x 3.20mm) Height - Seated (Max) 0.035" (0.90mm)	Category	Crystals, Oscillators, Resonators
Administry 4MA Type MEMS (Silicon) Frequency 133.33MHz Function Enable/Disable Output LVPECL Voltage - Supply 2.5V Frequency Stability ±50ppm Operating Temperature -40°C ~ 85°C Current - Supply (Max) - Ratings - Mounting Type Surface Mount Package / Case 6-SMD, No Lead Size / Dimension 0.035" (0.90mm)		Oscillators
TypeMEMS (Silicon)Frequency133.33MHzFunctionEnable/DisableOutputLVPECLVoltage - Supply2.5VFrequency Stability±50ppmOperating Temperature-40°C ~ 85°CCurrent - Supply (Max)-Mounting TypeSurface MountPackage / Case6-SMD, No LeadSize / Dimension0.035" (0.90mm)	Package	6-SMD, No Lead
Frequency133.33 MHzFunctionEnable/DisableOutputLVPECLVoltage - Supply2.5VFrequency Stability±50ppmOperating Temperature-40°C ~ 85°CCurrent - Supply (Max)-Ratings-Mounting TypeSurface MountPackage / Case6-SMD, No LeadSize / Dimension0.035" (0.90mm)	Series	4MA
FunctionEnable/DisableOutputLVPECLVoltage - Supply2.5VFrequency Stability±50ppmOperating Temperature-40°C ~ 85°CCurrent - Supply (Max)-Ratings-Mounting TypeSurface MountPackage / Case6-SMD, No LeadSize / Dimension0.035" (0.90mm)	Туре	MEMS (Silicon)
OutputLVPECLVoltage - Supply2.5VFrequency Stability±50pmOperating Temperature-40°C ~ 85°CCurrent - Supply (Max)-Ratings-Mounting TypeSurface MountPackage / Case6-SMD, No LeadSize / Dimension0.197" L x 0.126" W (5.00mm x 3.20mm)	Frequency	133.33MHz
Voltage - Supply2.5VFrequency Stability±50ppmOperating Temperature-40°C ~ 85°CCurrent - Supply (Max)-Ratings-Mounting TypeSurface MountPackage / Case6-SMD, No LeadSize / Dimension0.197" L x 0.126" W (5.00mm x 3.20mm)Height - Seated (Max)0.035" (0.90mm)	Function	Enable/Disable
Frequency Stability±50ppmOperating Temperature-40°C ~ 85°CCurrent - Supply (Max)-Ratings-Mounting TypeSurface MountPackage / Case6-SMD, No LeadSize / Dimension0.197" L x 0.126" W (5.00mm x 3.20mm)Height - Seated (Max)0.035" (0.90mm)	Output	LVPECL
Operating Temperature-40°C ~ 85°CCurrent - Supply (Max)-Ratings-Mounting TypeSurface MountPackage / Case6-SMD, No LeadSize / Dimension0.197" L x 0.126" W (5.00mm x 3.20mm)Height - Seated (Max)0.035" (0.90mm)	Voltage - Supply	2.5V
Current - Supply (Max)-Ratings-Mounting TypeSurface MountPackage / Case6-SMD, No LeadSize / Dimension0.197" L x 0.126" W (5.00mm x 3.20mm)Height - Seated (Max)0.035" (0.90mm)	Frequency Stability	±50ppm
Ratings-Mounting TypeSurface MountPackage / Case6-SMD, No LeadSize / Dimension0.197" L x 0.126" W (5.00mm x 3.20mm)Height - Seated (Max)0.035" (0.90mm)	Operating Temperature	-40°C ~ 85°C
Mounting TypeSurface MountPackage / Case6-SMD, No LeadSize / Dimension0.197" L x 0.126" W (5.00mm x 3.20mm)Height - Seated (Max)0.035" (0.90mm)	Current - Supply (Max)	_
Package / Case6-SMD, No LeadSize / Dimension0.197" L x 0.126" W (5.00mm x 3.20mm)Height - Seated (Max)0.035" (0.90mm)	Ratings	-
Size / Dimension 0.197" L x 0.126" W (5.00mm x 3.20mm) Height - Seated (Max) 0.035" (0.90mm)	Mounting Type	Surface Mount
Height - Seated (Max) 0.035" (0.90mm)	Package / Case	6-SMD, No Lead
•	Size / Dimension	0.197" L x 0.126" W (5.00mm x 3.20mm)
Report errors?	Height - Seated (Max)	0.035" (0.90mm)
		Report errors?

4MA133330Z3BACTGI Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

4MA133330Z3BACTGI Payment Methods



If you have any question about 4MA133330Z3BACTGI, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com