

4MA159375Z3BACTGI

4MA159375Z3BACTGI Information

Heisener.com	 4MA159375Z3BACTGI IDT, Integrated Device Technology Inc Crystals, Oscillators, Resonators Oscillators OSC MEMS 159.375MHZ LVPECL SMD 6-SMD, No Lead For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



4MA159375Z3BACTGI Specifications

Annufacturer Part Number4MA159375Z3BACTGIAnnufacturerIDT, Integrated Device Technology IncCategoryCrystals, Oscillators, ResonatorsOscillatorsOscillatorsVackage6-SMD, No Leaderies4MA'ypeMEMS (Silicon)requency159.375MHzbutputEnable/DisableOutput2.5V'requency Stability±50ppmOperating Temperature-40°C ~ 85°CCurrent - Supply (Max)100mA
CategoryCrystals, Oscillators, ResonatorsOscillatorsOscillatorsAckage6-SMD, No Leaderies4MASypeMEMS (Silicon)Yope159.375MHzNunctionEnable/DisableOutputLVPECLVoltage - Supply2.5VYequency Stability±50ppmOperating Temperature-40°C ~ 85°C
AckageOscillatorsPackage6-SMD, No Leaderies4MASypeMEMS (Silicon)Prequency159.375MHzPunctionEnable/DisableDutputLVPECLVoltage - Supply2.5VPrequency Stability±50ppmPuerating Temperature-40°C ~ 85°C
Package6-SMD, No Leaderies4MA'ypeMEMS (Silicon)requency159.375MHzburntionEnable/DisablebutputLVPECL'oltage - Supply2.5V'requency Stability±50ppmoperating Temperature-40°C ~ 85°C
Administration Administration eries 4MA Sype MEMS (Silicon) eriequency 159.375MHz Function Enable/Disable Dutput LVPECL Voltage - Supply 2.5V Frequency Stability ±50ppm Operating Temperature -40°C ~ 85°C
Ype MEMS (Silicon) Yrequency 159.375MHz Yunction Enable/Disable Dutput LVPECL Yoltage - Supply 2.5V Yrequency Stability ±50ppm Operating Temperature -40°C ~ 85°C
Prequency159.375MHzFunctionEnable/DisableOutputLVPECLVoltage - Supply2.5VPrequency Stability±50ppmOperating Temperature-40°C ~ 85°C
Punction Enable/Disable Dutput LVPECL Voltage - Supply 2.5V Prequency Stability ±50ppm Operating Temperature -40°C ~ 85°C
DutputLVPECLYoltage - Supply2.5VYrequency Stability±50ppmOperating Temperature-40°C ~ 85°C
Yoltage - Supply 2.5V Srequency Stability ±50ppm Operating Temperature -40°C ~ 85°C
Prequency Stability ± 50 ppmOperating Temperature -40° C ~ 85° C
Operating Temperature $-40^{\circ}C \sim 85^{\circ}C$
Summer Summer (Max)
Current - Supply (Max) 100mA
Aounting Type Surface Mount
Package / Case 6-SMD, No Lead
ize / Dimension 0.197" L x 0.126" W (5.00mm x 3.20mm)
Height - Seated (Max) 0.035" (0.90mm)
Report errors?

4MA159375Z3BACTGI Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

4MA159375Z3BACTGI Payment Methods



If you have any question about 4MA159375Z3BACTGI, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com