

4MA200000Z4BACUGI

4MA200000Z4BACUGI Information

Heisener.com	4MA200000Z4BACUGI IDT, Integrated Device Technology Inc Crystals, Oscillators, Resonators Oscillators OSC MEMS 200.000MHZ LVDS SMD 6-SMD, No Lead For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



4MA200000Z4BACUGI Specifications

MandacturerIDT, Integrated Device Technology IncCategoryCrystals, Oscillators, ResonatorsOscillatorsOscillatorsPackage6-SMD, No LeadPackage4MAFypeMEMS (Silicon)Frequency200MHzDutputEnable/DisableOutput2.5VFrequency Stability±50pmOperating Temperature40°C ~ 85°CCurrent - Supply (Max)10mA (Typ)Ratings-Package / Case6-SMD, No Lead		
CategoryCrystals, Oscillators, ResonatorsOscillatorsOscillatorsOscillatorsOscillatorsOscillatorsOscillatorsOscillatorsOscillatorsOscillatorsOscillatorsOscillatorsSeriesMATypeMEMS (Silicon)SerieuencySerieuencySerieuencySupplySupplyCrystals, Oscillators, ResonatorsSerieuency StabilitySerieuency StabilitySerieuency StabilitySerieuency StabilitySupplyOperating Temperature-40°C ~ 85°CCurrent - Supply (Max)Nounting TypeSerieuency CaseSerieuency CaseSerieuency CaseSerieuency StabilitySerieuency Stability<	Manufacturer Part Number	4MA200000Z4BACUGI
OscillatorsPackage6-SMD, No LeadPackage4MATypeMEMS (Silicon)Frequency200MHzFunctionEnable/DisableDutputLVDSVoltage - Supply2.5VFrequency Stability±50ppmOperating Temperature-40°C ~ 85°CCurrent - Supply (Max)100mA (Typ)Ratings-Package / Case6-SMD, No Lead	Manufacturer	IDT, Integrated Device Technology Inc
Package6-SMD, No LeadSeries4MATypeMEMS (Silicon)Frequency200MHzFunctionEnable/DisableDutputLVDSVoltage - Supply2.5VFrequency Stability±50ppmOperating Temperature-40°C ~ 85°CCurrent - Supply (Max)100mA (Typ)Ratings-Package / Case6-SMD, No Lead	Category	Crystals, Oscillators, Resonators
Series4MAFypeMEMS (Silicon)Frequency200MHzFunctionEnable/DisableDutputLVDSVoltage - Supply2.5VFrequency Stability±50ppmOperating Temperature-40°C ~ 85°CCurrent - Supply (Max)100mA (Typ)Ratings-Package / Case6-SMD, No Lead		Oscillators
Fype MEMS (Silicon) Frequency 200MHz Function Enable/Disable Dutput LVDS Voltage - Supply 2.5V Frequency Stability ±50ppm Operating Temperature -40°C ~ 85°C Current - Supply (Max) 100mA (Typ) Ratings - Package / Case 6-SMD, No Lead	Package	6-SMD, No Lead
Frequency200MHzFunctionEnable/DisableDutputLVDSVoltage - Supply2.5VFrequency Stability±50ppmOperating Temperature-40°C ~ 85°CCurrent - Supply (Max)100mA (Typ)Ratings-Package / Case6-SMD, No Lead	Series	4MA
FunctionEnable/DisableDutputLVDSVoltage - Supply2.5VFrequency Stability±50ppmOperating Temperature-40°C ~ 85°CCurrent - Supply (Max)100mA (Typ)Ratings-Mounting TypeSurface MountPackage / Case6-SMD, No Lead	Туре	MEMS (Silicon)
Dutput LVDS Voltage - Supply 2.5V Frequency Stability ±50ppm Operating Temperature -40°C ~ 85°C Current - Supply (Max) 100mA (Typ) Ratings - Mounting Type Surface Mount Package / Case 6-SMD, No Lead	Frequency	200MHz
Yoltage - Supply2.5VFrequency Stability±50ppmOperating Temperature-40°C ~ 85°CCurrent - Supply (Max)100mA (Typ)Ratings-Mounting TypeSurface MountPackage / Case6-SMD, No Lead	Function	Enable/Disable
Frequency Stability±50ppmOperating Temperature-40°C ~ 85°CCurrent - Supply (Max)100mA (Typ)Ratings-Mounting TypeSurface MountPackage / Case6-SMD, No Lead	Output	LVDS
Operating Temperature-40°C ~ 85°CCurrent - Supply (Max)100mA (Typ)Ratings-Mounting TypeSurface MountPackage / Case6-SMD, No Lead	Voltage - Supply	2.5V
Current - Supply (Max) 100mA (Typ) Ratings - Mounting Type Surface Mount Package / Case 6-SMD, No Lead	Frequency Stability	±50ppm
Ratings - Mounting Type Surface Mount Package / Case 6-SMD, No Lead	Operating Temperature	$-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$
Mounting Type Surface Mount Package / Case 6-SMD, No Lead	Current - Supply (Max)	100mA (Typ)
Package / Case 6-SMD, No Lead	Ratings	-
	Mounting Type	Surface Mount
	Package / Case	6-SMD, No Lead
Size / Dimension 0.276" L x 0.197" W (7.00mm x 5.00mm)	Size / Dimension	0.276" L x 0.197" W (7.00mm x 5.00mm)
Height - Seated (Max) 0.035" (0.90mm)	Height - Seated (Max)	0.035" (0.90mm)
Report errors?		Report errors?

4MA200000Z4BACUGI Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

4MA200000Z4BACUGI Payment Methods



If you have any question about 4MA200000Z4BACUGI, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com