

4TPB330ML

4TPB330ML Information

www.meisener.com	Part Number Manufacturer Category Description Package	4TPB330ML Panasonic Electronic Components Capacitors Tantalum - Polymer Capacitors CAP TANT POLY 330UF 4V 2917 2917 (7343 Metric) For the pricing/inventory/lead time, please contact us	
For Reference Only		Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



4TPB330ML Specifications

Manufacturer Part Number 4TPB330ML Manufacturer Panasonic Electronic Components Category Capacitors Tantalum - Polymer Capacitors Tantalum - Polymer Capacitors Package 2917 (7343 Metric) Series POSCAP? TPB Capacitance 330µF Tolerance ±20% Voltage - Rated 4V Type Molded Derating Temperature 40 mOhm Operating Temperature - Mounting Type Surface Mount Package / Case 2917 (7343 Metric) Size / Dimension - Height - Seated (Max) 0.18° (3.00mm) Liedaf Spacing 0.18° (3.00mm) Height - Seated (Max) 0.118° (3.00mm) Lead Spacing - Features General Purpose		
CategoryCapacitorsTantalum - Polymer CapacitorsPackage2917 (7343 Metric)SeriesPOSCAP? TPBCapacitance330µFTolerance±20%Voltage - Rated4VTypeMoldedESR (Equivalent Series Resistance)40 mOhmOperating Temperature-55°C ~ 105°CLifetime @ TempNoutring TypeSurface MountSize / Dimension0.287" L x 0.169" W (7.30mm x 4.30mm)Height - Seated (Max)0.118" (3.00mm)Lead Spacing-Manufacturer Size CodeD3LFeaturesGeneral Purpose	Manufacturer Part Number	4TPB330ML
Tantalum - Polymer CapacitorsPackage2917 (7343 Metric)SeriesPOSCAP? TPBCapacitance330µFTolerance±20%Voltage - Rated4VTypeMoldedESR (Equivalent Series Resistance)40 mOhmOperating Temperature-55°C ~ 105°CLifetime @ TempMounting TypeSurface MountSize / Dimension0.287" L x 0.169" W (7.30mm x 4.30mm)Height - Seated (Max)0.118" (3.00mm)Lead Spacing53LFeaturesGeneral Purpose	Manufacturer	Panasonic Electronic Components
Package2917 (7343 Metric)SeriesPOSCAP? TPBCapacitance330µFTolerance±20%Voltage - Rated4VTypeMoldedESR (Equivalent Series Resistance)40 mOhmOperating Temperature-55°C ~ 105°CLifetime @ TempMounting TypeSurface MountPackage / Case2917 (7343 Metric)Size / Dimension0.287" L x 0.169" W (7.30mm x 4.30mm)Height - Seated (Max)0.118" (3.00mm)Lead Spacing-FeaturesDSLFeaturesGeneral Purpose	Category	Capacitors
Series POSCAP? TPB Capacitance 330µF Tolerance ±20% Voltage - Rated 4V Type Molded ESR (Equivalent Series Resistance) 40 mOhm Operating Temperature -55°C ~ 105°C Lifetime @ Temp. - Mounting Type Surface Mount Package / Case 2917 (7343 Metric) Size / Dimension 0.188" (3.00mm) x 4.30mm) Height - Seated (Max) 0.118" (3.00mm) Lead Spacing - Fatures OBL		Tantalum - Polymer Capacitors
Capacitance 330µF Capacitance 330µF Tolerance ±20% Voltage - Rated 4V Type Molded ESR (Equivalent Series Resistance) 40 mOhm Operating Temperature -55°C ~ 105°C Lifetime @ Temp. - Mounting Type Surface Mount Package / Case 2917 (7343 Metric) Size / Dimension 0.287" L x 0.169" W (7.30mm x 4.30mm) Height - Seated (Max) 0.118" (3.00mm) Lead Spacing - Manufacturer Size Code D3L Features General Purpose	Package	2917 (7343 Metric)
Tolerance±20%Yoltage - Rated4VYopeMoldedESR (Equivalent Series Resistance)40 mOhmOperating Temperature-55°C ~ 105°CLifetime @ TempMounting TypeSurface MountPackage / Case2917 (7343 Metric)Size / Dimension0.18" (3.00mm)Height - Seated (Max)-Lead Spacing-Features53°CGeneral Purpose-	Series	POSCAP? TPB
Voltage - Rated4VYopeMoldedESR (Equivalent Series Resistance)40 mOhmOperating Temperature-55°C ~ 105°CLifetime @ TempMounting TypeSurface MountPackage / Case2917 (7343 Metric)Size / Dimension0.287" L x 0.169" W (7.30mm x 4.30mm)Height - Seated (Max)-Lead Spacing-Manufacturer Size CodeD3LFeaturesGeneral Purpose	Capacitance	330µF
TypeMoldedESR (Equivalent Series Resistance)40 mOhmOperating Temperature-55°C ~ 105°CLifetime @ TempMounting TypeSurface MountPackage / Case2917 (7343 Metric)Size / Dimension0.287" L x 0.169" W (7.30mm x 4.30mm)Height - Seated (Max)0.118" (3.00mm)Lead Spacing-Mountage Code502FeaturesSocial Metric)General PurposeSocial Metric)	Tolerance	±20%
FyreInterferESR (Equivalent Series Resistance)40 mOhmOperating Temperature-55°C ~ 105°CLifetime @ TempMounting TypeSurface MountPackage / Case2917 (7343 Metric)Size / Dimension0.287" L x 0.169" W (7.30mm x 4.30mm)Height - Seated (Max)0.118" (3.00mm)Lead Spacing-Manufacturer Size CodeD3LFeaturesGeneral Purpose	Voltage - Rated	4V
Note-55°C ~ 105°CLifetime @ TempMounting TypeSurface MountPackage / Case2917 (7343 Metric)Size / Dimension0.287" L x 0.169" W (7.30mm x 4.30mm)Height - Seated (Max)0.118" (3.00mm)Lead Spacing-Manufacturer Size CodeD3LFeaturesGeneral Purpose	Туре	Molded
Lifetime @ TempMounting TypeSurface MountPackage / Case2917 (7343 Metric)Size / Dimension0.287" L x 0.169" W (7.30mm x 4.30mm)Height - Seated (Max)0.118" (3.00mm)Lead Spacing-Manufacturer Size CodeD3LFeaturesGeneral Purpose	ESR (Equivalent Series Resistance)	40 mOhm
Mounting TypeSurface MountPackage / Case2917 (7343 Metric)Size / Dimension0.287" L x 0.169" W (7.30mm x 4.30mm)Height - Seated (Max)0.118" (3.00mm)Lead Spacing-Manufacturer Size CodeD3LFeaturesGeneral Purpose	Operating Temperature	-55°C ~ 105°C
Package / Case2917 (7343 Metric)Size / Dimension0.287" L x 0.169" W (7.30mm x 4.30mm)Height - Seated (Max)0.118" (3.00mm)Lead Spacing-Manufacturer Size CodeD3LFeaturesGeneral Purpose	Lifetime @ Temp.	-
Size / Dimension0.287" L x 0.169" W (7.30mm x 4.30mm)Height - Seated (Max)0.118" (3.00mm)Lead Spacing-Manufacturer Size CodeD3LFeaturesGeneral Purpose	Mounting Type	Surface Mount
Height - Seated (Max)0.118" (3.00mm)Lead Spacing-Manufacturer Size CodeD3LFeaturesGeneral Purpose	Package / Case	2917 (7343 Metric)
Lead Spacing-Manufacturer Size CodeD3LFeaturesGeneral Purpose	Size / Dimension	0.287" L x 0.169" W (7.30mm x 4.30mm)
Manufacturer Size CodeD3LFeaturesGeneral Purpose	Height - Seated (Max)	0.118" (3.00mm)
Features General Purpose	Lead Spacing	-
-	Manufacturer Size Code	D3L
Report errors?	Features	General Purpose
		Report errors?

4TPB330ML Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

4TPB330ML Payment Methods



4TPB330ML Shipping Methods



If you have any question about 4TPB330ML, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com