

5-1393818-2 Information

Heisener.com

Part Number 5-1393818-2

Manufacturer TE Connectivity Potter & Brumfield Relays

Category Relays

Signal Relays, Up to 2 Amps

Description RELAY GEN PURPOSE DPDT 200MA 48V

Package

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com





Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









5-1393818-2 Specifications

Manufacturer 5-1393818-2 Manufacturer TE Connectivity Potter & Brumfield Relays Category Relays Signal Relays, Up to 2 Amps Package - Series V23162, AXICOM Relay Type General Purpose Coil Type Non Latching Coil Current 15mA Coil Voltage 48VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 200mA Switching Voltage 30VAC, 36VDC - Max Turn On Voltage (Max) 23 VDC Turn Off Voltage (Min) - Operate Time 7.5ms Release Time 3ms Features Sealed - Hermetically Mounting Type Socketable Termination Style Plug In		
CategoryRelaysPackage-SeriesV23162, AXICOMRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current15mACoil Voltage48VDCContact FormDPDT (2 Form C)Contact Rating (Current)200mASwitching Voltage30VAC, 36VDC - MaxTurn On Voltage (Max)23 VDCTurn Off Voltage (Min)-Operate Time7.5msRelease Time3msFeaturesSealed - HermeticallyMounting TypeSocketableTermination StylePlug In	Manufacturer Part Number	5-1393818-2
Package-SeriesV23162, AXICOMRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current15mACoil Voltage48VDCContact FormDPDT (2 Form C)Contact Rating (Current)200mASwitching Voltage30VAC, 36VDC - MaxTurn On Voltage (Max)23 VDCTurn Off Voltage (Min)-Operate Time7.5msRelease Time3msFeaturesSealed - HermeticallyMounting TypeSocketableTermination StylePlug In	Manufacturer	TE Connectivity Potter & Brumfield Relays
Package - Series V23162, AXICOM Relay Type General Purpose Coil Type Non Latching Coil Current 15mA Coil Voltage 48VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 200mA Switching Voltage 30VAC, 36VDC - Max Turn On Voltage (Max) 23 VDC Turn Off Voltage (Min) - Operate Time 7.5ms Release Time 3ms Features Sealed - Hermetically Mounting Type Socketable Termination Style Plug In	Category	Relays
SeriesV23162, AXICOMRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current15mACoil Voltage48VDCContact FormDPDT (2 Form C)Contact Rating (Current)200mASwitching Voltage30VAC, 36VDC - MaxTurn On Voltage (Max)23 VDCTurn Off Voltage (Min)-Operate Time7.5msRelease Time3msFeaturesSealed - HermeticallyMounting TypeSocketableTermination StylePlug In		Signal Relays, Up to 2 Amps
Relay TypeGeneral PurposeCoil TypeNon LatchingCoil Current15mACoil Voltage48VDCContact FormDPDT (2 Form C)Contact Rating (Current)200mASwitching Voltage30VAC, 36VDC - MaxTurn On Voltage (Max)23 VDCTurn Off Voltage (Min)-Operate Time7.5msRelease Time3msFeaturesSealed - HermeticallyMounting TypeSocketableTermination StylePlug In	Package	-
Coil Type Non Latching Coil Current 15mA Coil Voltage 48VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 200mA Switching Voltage 30VAC, 36VDC - Max Turn On Voltage (Max) 23 VDC Turn Off Voltage (Min) - Operate Time 7.5ms Release Time 3ms Features Sealed - Hermetically Mounting Type Socketable Termination Style Plug In	Series	V23162, AXICOM
Coil Current Coil Voltage 48VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 200mA Switching Voltage 30VAC, 36VDC - Max Turn On Voltage (Max) 23 VDC Turn Off Voltage (Min) - Operate Time 7.5ms Release Time 3ms Features Sealed - Hermetically Mounting Type Socketable Termination Style Plug In	Relay Type	General Purpose
Coil Voltage 48VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 200mA Switching Voltage 30VAC, 36VDC - Max Turn On Voltage (Max) 23 VDC Turn Off Voltage (Min) - Operate Time 7.5ms Release Time 3ms Features Sealed - Hermetically Mounting Type Socketable Termination Style Plug In	Coil Type	Non Latching
Contact Form DPDT (2 Form C) Contact Rating (Current) 200mA Switching Voltage 30VAC, 36VDC - Max Turn On Voltage (Max) 23 VDC Turn Off Voltage (Min) - Operate Time 7.5ms Release Time 3ms Features Sealed - Hermetically Mounting Type Socketable Termination Style Plug In	Coil Current	15mA
Contact Rating (Current) Switching Voltage 30VAC, 36VDC - Max Turn On Voltage (Max) 23 VDC Turn Off Voltage (Min) Operate Time 7.5ms Release Time 3ms Features Sealed - Hermetically Mounting Type Socketable Termination Style Plug In	Coil Voltage	48VDC
Switching Voltage 30VAC, 36VDC - Max Turn On Voltage (Max) 23 VDC Turn Off Voltage (Min) - Operate Time 7.5ms Release Time 3ms Features Sealed - Hermetically Mounting Type Socketable Termination Style Plug In	Contact Form	DPDT (2 Form C)
Turn On Voltage (Max) 23 VDC Turn Off Voltage (Min) Operate Time 7.5ms Release Time 3ms Features Sealed - Hermetically Mounting Type Socketable Termination Style Plug In	Contact Rating (Current)	200mA
Turn Off Voltage (Min) Operate Time 7.5ms Release Time 3ms Features Sealed - Hermetically Mounting Type Socketable Termination Style Plug In	Switching Voltage	30VAC, 36VDC - Max
Operate Time 7.5ms Release Time 3ms Features Sealed - Hermetically Mounting Type Socketable Termination Style Plug In	Turn On Voltage (Max)	23 VDC
Release Time 3ms Features Sealed - Hermetically Mounting Type Socketable Termination Style Plug In	Turn Off Voltage (Min)	-
Features Sealed - Hermetically Mounting Type Socketable Termination Style Plug In	Operate Time	7.5ms
Mounting Type Socketable Termination Style Plug In	Release Time	3ms
Termination Style Plug In	Features	Sealed - Hermetically
	Mounting Type	Socketable
Papart arrors?	Termination Style	Plug In
Report errors:		Report errors?

5-1393818-2 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

5-1393818-2 Payment Methods





















5-1393818-2 Shipping Methods













If you have any question about 5-1393818-2, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com