

## 5-1415390-1 Information

Heisener.com

**Part Number** 5-1415390-1

Manufacturer TE Connectivity Potter & Brumfield Relays

Category

Power Relays, Over 2 Amps

**Description** RELAY GEN PURPOSE SPDT 5A 24V

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **5-1415390-1 Specifications**

Manufacturer Part Number     5-1415390-1       Manufacturer     TE Connectivity Potter & Brumfield Relays       Category     Relays       Power Relays, Over 2 Amps       Package     -       Series     PE Bistable, SCHRACK       Relay Type     General Purpose       Coil Type     Latching, Single Coil       Coil Current     8.7mA       Coil Voltage     24VDC       Contact Form     SPDT (1 Form C)       Contact Rating (Current)     5A       Switching Voltage     400VAC - Max       Turn On Voltage (Max)     18 VDC       Turn Off Voltage (Min)     -       Operate Time     8ms       Release Time     8ms       Features     Sealed - Flux Protection       Mounting Type     Through Hole       Termination Style     PC Pin		
CategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesPE Bistable, SCHRACKRelay TypeGeneral PurposeCoil TypeLatching, Single CoilCoil Current8.7mACoil Voltage24VDCContact FormSPDT (1 Form C)Contact Rating (Current)5ASwitching Voltage400VAC - MaxTurn On Voltage (Max)18 VDCTurn Off Voltage (Min)-Operate Time8msRelease Time8msFeaturesSealed - Flux ProtectionMounting TypeThrough HoleTermination StylePC Pin	Manufacturer Part Number	5-1415390-1
Package-SeriesPE Bistable, SCHRACKRelay TypeGeneral PurposeCoil TypeLatching, Single CoilCoil Current8.7mACoil Voltage24VDCContact FormSPDT (1 Form C)Contact Rating (Current)5ASwitching Voltage400VAC - MaxTurn On Voltage (Max)18 VDCTurn Off Voltage (Min)-Operate Time8msRelease Time8msFeaturesSealed - Flux ProtectionMounting TypeThrough HoleTermination StylePC Pin	Manufacturer	TE Connectivity Potter & Brumfield Relays
Package-SeriesPE Bistable, SCHRACKRelay TypeGeneral PurposeCoil TypeLatching, Single CoilCoil Current8.7mACoil Voltage24VDCContact FormSPDT (1 Form C)Contact Rating (Current)5ASwitching Voltage400VAC - MaxTurn On Voltage (Max)18 VDCTurn Off Voltage (Min)-Operate Time8msRelease Time8msFeaturesSealed - Flux ProtectionMounting TypeThrough HoleTermination StylePC Pin	Category	Relays
SeriesPE Bistable, SCHRACKRelay TypeGeneral PurposeCoil TypeLatching, Single CoilCoil Current8.7mACoil Voltage24VDCContact FormSPDT (1 Form C)Contact Rating (Current)5ASwitching Voltage400VAC - MaxTurn On Voltage (Max)18 VDCTurn Off Voltage (Min)-Operate Time8msRelease Time8msFeaturesSealed - Flux ProtectionMounting TypeThrough HoleTermination StylePC Pin		Power Relays, Over 2 Amps
Relay Type General Purpose Coil Type Latching, Single Coil Coil Current 8.7mA Coil Voltage 24VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 5A Switching Voltage 400VAC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) - Operate Time 8ms Release Time 8ms Release Time 8ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Package	-
Coil Type	Series	PE Bistable, SCHRACK
Coil Current8.7mACoil Voltage24VDCContact FormSPDT (1 Form C)Contact Rating (Current)5ASwitching Voltage400VAC - MaxTurn On Voltage (Max)18 VDCTurn Off Voltage (Min)-Operate Time8msRelease Time8msFeaturesSealed - Flux ProtectionMounting TypeThrough HoleTermination StylePC Pin	Relay Type	General Purpose
Coil Voltage 24VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 5A Switching Voltage 400VAC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) - Operate Time 8ms Release Time 8ms Release Time 8ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Coil Type	Latching, Single Coil
Contact Form SPDT (1 Form C)  Contact Rating (Current)  5A  Switching Voltage 400VAC - Max  Turn On Voltage (Max)  18 VDC  Turn Off Voltage (Min)  Operate Time 8ms  Release Time 8ms  Release Time 8ms  Features Sealed - Flux Protection  Mounting Type Through Hole  Termination Style PC Pin	Coil Current	8.7mA
Contact Rating (Current)  Switching Voltage  400VAC - Max  Turn On Voltage (Max)  18 VDC  Turn Off Voltage (Min)  Operate Time  8ms  Release Time  8ms  Features  Sealed - Flux Protection  Mounting Type  Through Hole  Termination Style  PC Pin	Coil Voltage	24VDC
Switching Voltage 400VAC - Max  Turn On Voltage (Max) 18 VDC  Turn Off Voltage (Min) - Operate Time 8ms  Release Time 8ms  Features Sealed - Flux Protection  Mounting Type Through Hole  Termination Style PC Pin	Contact Form	SPDT (1 Form C)
Turn On Voltage (Max)  18 VDC  Turn Off Voltage (Min)  Operate Time  8ms  Release Time  8ms  Features  Sealed - Flux Protection  Mounting Type  Through Hole  Termination Style  PC Pin	Contact Rating (Current)	5A
Turn Off Voltage (Min)  Operate Time  8ms  Release Time  8ms  Features  Sealed - Flux Protection  Mounting Type  Through Hole  Termination Style  PC Pin	Switching Voltage	400VAC - Max
Operate Time 8ms Release Time 8ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Turn On Voltage (Max)	18 VDC
Release Time 8ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Turn Off Voltage (Min)	-
Features Sealed - Flux Protection  Mounting Type Through Hole  Termination Style PC Pin	Operate Time	8ms
Mounting Type Through Hole Termination Style PC Pin	Release Time	8ms
Termination Style PC Pin	Features	Sealed - Flux Protection
•	Mounting Type	Through Hole
Report errors?	Termination Style	PC Pin
		Report errors?

#### 5-1415390-1 Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

# **5-1415390-1 Payment Methods**





















## **5-1415390-1 Shipping Methods**













If you have any question about 5-1415390-1, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com