

5-1415520-1 Information

Heisener.com

Part Number 5-1415520-1

Manufacturer TE Connectivity AMP Connectors

Category

Power Relays, Over 2 Amps

Description RELAY GEN PURPOSE SPST 16A 12V

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









5-1415520-1 Specifications

Manufacturer Part Number5-1415520-1ManufacturerTE Connectivity AMP ConnectorsCategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesRF, SCHRACKRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current33.3mACoil Voltage12VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)16ASwitching Voltage400VAC - MaxTurn On Voltage (Max)8.4 VDCTurn Off Voltage (Min)1.2 VDCOperate Time11msRelease Time7msFeaturesInsulation - Class F, Sealed - Flux ProtectionMounting TypeThrough HoleTermination StylePC Pin, Quick Connect - 0.250" (6.3mm)		
CategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesRF, SCHRACKRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current33.3mACoil Voltage12VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)16ASwitching Voltage400VAC - MaxTurn On Voltage (Max)8.4 VDCTurn Off Voltage (Min)1.2 VDCOperate Time11msRelease Time7msFeaturesInsulation - Class F, Sealed - Flux ProtectionMounting TypeThrough HoleTermination StylePC Pin, Quick Connect - 0.250" (6.3mm)	Manufacturer Part Number	5-1415520-1
Package - Series RF, SCHRACK Relay Type General Purpose Coil Type Non Latching Coil Current 33.3mA Coil Voltage 12VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 16A Switching Voltage 400VAC - Max Turn On Voltage (Max) 8.4 VDC Turn Off Voltage (Min) 1.2 VDC Operate Time 11ms Release Time 7ms Features Insulation - Class F, Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin, Quick Connect - 0.250" (6.3mm)	Manufacturer	TE Connectivity AMP Connectors
Package - RF, SCHRACK Relay Type General Purpose Coil Type Non Latching Coil Current 33.3mA Coil Voltage 12VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 16A Switching Voltage 400VAC - Max Turn On Voltage (Max) 8.4 VDC Turn Off Voltage (Min) 1.2 VDC Operate Time 11ms Release Time 7ms Features Insulation - Class F, Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin, Quick Connect - 0.250" (6.3mm)	Category	Relays
SeriesRF, SCHRACKRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current33.3mACoil Voltage12VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)16ASwitching Voltage400VAC - MaxTurn On Voltage (Max)8.4 VDCTurn Off Voltage (Min)1.2 VDCOperate Time11msRelease Time7msFeaturesInsulation - Class F, Sealed - Flux ProtectionMounting TypeThrough HoleTermination StylePC Pin, Quick Connect - 0.250" (6.3mm)		Power Relays, Over 2 Amps
Relay TypeGeneral PurposeCoil TypeNon LatchingCoil Current33.3mACoil Voltage12VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)16ASwitching Voltage400VAC - MaxTurn On Voltage (Max)8.4 VDCTurn Off Voltage (Min)1.2 VDCOperate Time11msRelease Time7msFeaturesInsulation - Class F, Sealed - Flux ProtectionMounting TypeThrough HoleTermination StylePC Pin, Quick Connect - 0.250" (6.3mm)	Package	-
Coil Type Non Latching Coil Current 33.3mA Coil Voltage 12VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 16A Switching Voltage 400VAC - Max Turn On Voltage (Max) 8.4 VDC Turn Off Voltage (Min) 1.2 VDC Operate Time 11ms Release Time 7ms Features Insulation - Class F, Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin, Quick Connect - 0.250" (6.3mm)	Series	RF, SCHRACK
Coil Current Coil Voltage 12VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 16A Switching Voltage 400VAC - Max Turn On Voltage (Max) 8.4 VDC Turn Off Voltage (Min) 1.2 VDC Operate Time 11ms Release Time 7ms Features Insulation - Class F, Sealed - Flux Protection Mounting Type Termination Style PC Pin, Quick Connect - 0.250" (6.3mm)	Relay Type	General Purpose
Coil Voltage 12VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 16A Switching Voltage 400VAC - Max Turn On Voltage (Max) 8.4 VDC Turn Off Voltage (Min) 1.2 VDC Operate Time 11ms Release Time 7ms Features Insulation - Class F, Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin, Quick Connect - 0.250" (6.3mm)	Coil Type	Non Latching
Contact Form SPST-NO (1 Form A) Contact Rating (Current) 16A Switching Voltage 400VAC - Max Turn On Voltage (Max) 8.4 VDC Turn Off Voltage (Min) 1.2 VDC Operate Time 11ms Release Time 7ms Features Insulation - Class F, Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin, Quick Connect - 0.250" (6.3mm)	Coil Current	33.3mA
Contact Rating (Current) Switching Voltage 400VAC - Max Turn On Voltage (Max) 8.4 VDC Turn Off Voltage (Min) 1.2 VDC Operate Time 11ms Release Time 7ms Features Insulation - Class F, Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin, Quick Connect - 0.250" (6.3mm)	Coil Voltage	12VDC
Switching Voltage 400VAC - Max Turn On Voltage (Max) 8.4 VDC Turn Off Voltage (Min) 1.2 VDC Operate Time 11ms Release Time 7ms Features Insulation - Class F, Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin, Quick Connect - 0.250" (6.3mm)	Contact Form	SPST-NO (1 Form A)
Turn On Voltage (Max) Turn Off Voltage (Min) 1.2 VDC Operate Time 11ms Release Time 7ms Features Insulation - Class F, Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin, Quick Connect - 0.250" (6.3mm)	Contact Rating (Current)	16A
Turn Off Voltage (Min) 1.2 VDC Operate Time 11ms Release Time 7ms Features Insulation - Class F, Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin, Quick Connect - 0.250" (6.3mm)	Switching Voltage	400VAC - Max
Operate Time 11ms Release Time 7ms Features Insulation - Class F, Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin, Quick Connect - 0.250" (6.3mm)	Turn On Voltage (Max)	8.4 VDC
Release Time 7ms Features Insulation - Class F, Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin, Quick Connect - 0.250" (6.3mm)	Turn Off Voltage (Min)	1.2 VDC
Features Insulation - Class F, Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin, Quick Connect - 0.250" (6.3mm)	Operate Time	11ms
Mounting Type Through Hole Termination Style PC Pin, Quick Connect - 0.250" (6.3mm)	Release Time	7ms
Termination Style PC Pin, Quick Connect - 0.250" (6.3mm)	Features	Insulation - Class F, Sealed - Flux Protection
	Mounting Type	Through Hole
Report errors?	Termination Style	PC Pin, Quick Connect - 0.250" (6.3mm)
		Report errors?

5-1415520-1 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

5-1415520-1 Payment Methods



















5-1415520-1 Shipping Methods













If you have any question about 5-1415520-1, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com