

5 PSI-G-4V-PRIME

5 PSI-G-4V-PRIME Information



| Part Number | 5 PSI-G-4V-PRIME | |
|--------------|--|--|
| Manufacturer | All Sensors Corporation | |
| Category | Sensors, Transducers Pressure Sensors, Transducers | |
| Description | SENSOR 5PSIG 4V DUAL | |
| Package | 4-SIP Module | |
| | For the pricing/inventory/lead time, please contact us Website: https://www.heisener.com | |
| | E-mail: salesdept@heisener.com | |



Request a Quote

For Reference Only

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



5 PSI-G-4V-PRIME Specifications

| Manufacturer Part Number 5 PSI-G-4V-PRIME Manufacturer All Sensors Corporation Category Sensors, Transducers Package 4.SIP Module Series AXCA Pressure Support Vented Gauge Operating Pressure 5.PSI (34.47 kPa) Output Type Analog Voltage Output Type Analog Voltage Output Quartication 2.5 V ~ 4.25 V Accuracy 4.5 V ~ 5.5 V Port Size Manufied Output, Temperature Compensated Port Size Amplified Output, Temperature Compensated Port Size 15 PSI (103.42 kPa) Operating Temperature 4.0°C ~ 125°C Package / Case 4.SIP Module | | |
|---|--------------------------|---|
| CategorySensors, TransducersPressure Sensors, TransducersPackage4-SIP ModuleSeriesAXCAPressure TypeVented GaugeOperating Pressure5 PSI (34.47 kPa)Output TypeAnalog VoltageOutput0.25 V ~ 4.25 VAccuracy±0.5%Voltage - Supply4.5 V ~ 5.5 VPort SizeMale - 0.19" (4.8mm) TubePort StyleBarblessFeaturesAmplified Output, Temperature CompensatedMaximum Pressure15 PSI (103.42 kPa)Operating Temperature-40°C ~ 125°CPackage / Case-Supplier Device Package- | Manufacturer Part Number | 5 PSI-G-4V-PRIME |
| PackagePressure Sensors, TransducersPackage4-SIP ModuleSeriesAXCAPressure TypeVented GaugeOperating Pressure5 PSI (34.47 kPa)Output TypeAnalog VoltageOutput0.25 V ~ 4.25 VAccuracy±0.5%Voltage - Supply4.5 V ~ 5.5 VPort SizeMale - 0.19" (4.8mm) TubePort StyleBarblessFeaturesAmplified Output, Temperature CompensatedMaximum Pressure15 PSI (103.42 kPa)Operating Temperature-40°C ~ 125°CPackage / Case-Supplier Device Package- | Manufacturer | All Sensors Corporation |
| Package4-SIP ModuleSeriesAXCAPressure TypeVented GaugeOperating Pressure5 PSI (34.47 kPa)Output TypeAnalog VoltageOutput 10.25 V ~ 4.25 VAccuracy4.05%Voltage - SupplyAlael - 0.19" (4.8mm) TubePort SizeMale - 0.19" (4.8mm) TubePort StyleSarblessFeaturesMalfield Output, Temperature CompensatedMaximum Pressure15 PSI (103.42 kPa)Operating Temperature4.0°C ~ 125°CPackage / Case- 4.0°C ~ 125°CSupplier Device Package- 4.0°C ~ 125°C | Category | Sensors, Transducers |
| SeriesAXCAPressure TypeVented GaugeOperating Pressure5 PSI (34.47 kPa)Output TypeAnalog VoltageOutput Output0.25 V ~ 4.25 VAccuracy±0.5%Voltage - Supply4.5 V ~ 5.5 VPort SizeMale - 0.19" (4.8mm) TubePort StyleBarblessFeaturesMplified Output, Temperature CompensatedMaximum Pressure15 PSI (103.42 kPa)Operating Temperature-40°C ~ 125°CPackage / Case-Supplier Device Package- | | Pressure Sensors, Transducers |
| Pressure TypeVented GaugeOperating Pressure5 PSI (34.47 kPa)Output TypeAnalog VoltageOutput0.25 V ~ 4.25 VAccuracy±0.5%Voltage - Supply4.5 V ~ 5.5 VPort SizeMale - 0.19" (4.8mm) TubePort StyleBarblessFeaturesMaplified Output, Temperature CompensatedPressure15 PSI (103.42 kPa)Operating Temperature4.5 V ~ 125°CPackage / Case4.5 IP ModuleSupplier Device Package- | Package | 4-SIP Module |
| Operating Pressure5 PSI (34.47 kPa)Output TypeAnalog VoltageOutput0.25 V ~ 4.25 VAccuracy±0.5%Voltage - Supply4.5 V ~ 5.5 VPort SizeMale - 0.19" (4.8mm) TubePort StyleBarblessFeaturesAmplified Output, Temperature CompensatedTermination Style15 PSI (103.42 kPa)Operating Temperature-40°C ~ 125°CPackage / Case4.SIP ModuleSupplier Device Package- | Series | AXCA |
| Output TypeAnalog VoltageOutput0.25 V ~ 4.25 VAccuracy±0.5%Voltage - Supply4.5 V ~ 5.5 VPort SizeMale - 0.19" (4.8mm) TubePort StyleBarblessFeaturesAmplified Output, Temperature CompensatedTermination StylePCBMaximum Pressure15 PSI (103.42 kPa)Operating Temperature-40°C ~ 125°CPackage / Case4-SIP ModuleSupplier Device Package- | Pressure Type | Vented Gauge |
| Output0.25 V ~ 4.25 VAccuracy±0.5%Voltage - Supply4.5 V ~ 5.5 VPort SizeMale - 0.19" (4.8mm) TubePort StyleBarblessFeaturesAmplified Output, Temperature CompensatedTermination StylePCBMaximum Pressure15 PSI (103.42 kPa)Operating Temperature-40°C ~ 125°CPackage / Case4.SIP ModuleSupplier Device Package- | Operating Pressure | 5 PSI (34.47 kPa) |
| Accuracy±0.5%Voltage - Supply4.5 V ~ 5.5 VPort SizeMale - 0.19" (4.8mm) TubePort StyleBarblessFeaturesAmplified Output, Temperature CompensatedTermination StylePCBMaximum Pressure15 PSI (103.42 kPa)Operating Temperature-40°C ~ 125°CPackage / Case4-SIP ModuleSupplier Device Package- | Output Type | Analog Voltage |
| Voltage - Supply4.5 V ~ 5.5 VPort SizeMale - 0.19" (4.8mm) TubePort StyleBarblessFeaturesAmplified Output, Temperature CompensatedTermination StylePCBMaximum Pressure15 PSI (103.42 kPa)Operating Temperature-40°C ~ 125°CPackage / Case4-SIP ModuleSupplier Device Package- | Output | 0.25 V ~ 4.25 V |
| Port SizeMale - 0.19" (4.8mm) TubePort StyleBarblessFeaturesAmplified Output, Temperature CompensatedTermination StylePCBMaximum Pressure15 PSI (103.42 kPa)Operating Temperature-40°C ~ 125°CPackage / Case4-SIP ModuleSupplier Device Package- | Accuracy | $\pm 0.5\%$ |
| Port StyleBarblessFeaturesAmplified Output, Temperature CompensatedTermination StylePCBMaximum Pressure15 PSI (103.42 kPa)Operating Temperature-40°C ~ 125°CPackage / Case4-SIP ModuleSupplier Device Package- | Voltage - Supply | 4.5 V ~ 5.5 V |
| FeaturesAmplified Output, Temperature CompensatedTermination StylePCBMaximum Pressure15 PSI (103.42 kPa)Operating Temperature-40°C ~ 125°CPackage / Case4-SIP ModuleSupplier Device Package- | Port Size | Male - 0.19" (4.8mm) Tube |
| Termination StylePCBMaximum Pressure15 PSI (103.42 kPa)Operating Temperature-40°C ~ 125°CPackage / Case4-SIP ModuleSupplier Device Package- | Port Style | Barbless |
| Maximum Pressure15 PSI (103.42 kPa)Operating Temperature-40°C ~ 125°CPackage / Case4-SIP ModuleSupplier Device Package- | Features | Amplified Output, Temperature Compensated |
| Operating Temperature-40°C ~ 125°CPackage / Case4-SIP ModuleSupplier Device Package- | Termination Style | PCB |
| Package / Case 4-SIP Module Supplier Device Package - | Maximum Pressure | 15 PSI (103.42 kPa) |
| Supplier Device Package - | Operating Temperature | -40°C ~ 125°C |
| | Package / Case | 4-SIP Module |
| Report errors | Supplier Device Package | - |
| | | Report errors? |

5 PSI-G-4V-PRIME Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

5 PSI-G-4V-PRIME Payment Methods



5 PSI-G-4V-PRIME Shipping Methods



If you have any question about 5 PSI-G-4V-PRIME, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com