

50-00025 Information



For Reference Only

Part Number 50-00025

Manufacturer Tensility International Corp

Category Connectors, Interconnects
Barrel - Power Connectors

Description CONN PWR JACK 2.1X5.5MM SOLDER

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









50-00025 Specifications

Manufacturer Part Number 50-00025 Manufacturer Tensility International Corp Category Connectors, Interconnects Barrel - Power Connectors Package - Series - Connector Type Jack Gender Male Industry Recognized Mating Diameter 2.10mm ID (0.083"), 5.50mm OD (0.217") Actual Diameter 0.083" (2.10mm ID), 0.217" (5.50mm OD) Number of Positions/Contacts 2 Conductors, 2 Contacts Internal Switch(s) Does Not Contain Switch Mounting Type Free Hanging (In-Line) Mounting Feature - Termination Solder Cup Shielding Unshielded Features - Insulation Color - Voltage - Rated 20VDC Current Rating 7A		
Category Connectors, Interconnects Barrel - Power Connectors Package - Series - Connector Type Jack Gender Male Industry Recognized Mating Diameter Actual Diameter 0.083" (2.10mm ID) (0.083"), 5.50mm OD (0.217") Actual Diameter 0.083" (2.10mm ID), 0.217" (5.50mm OD) Number of Positions/Contacts 1 Conductors, 2 Contacts Internal Switch(s) Does Not Contain Switch Mounting Type Free Hanging (In-Line) Mounting Feature - Termination Solder Cup Shielding Unshielded Features - Insulation Color - Voltage - Rated 20VDC Current Rating	Manufacturer Part Number	50-00025
Package-Series-Connector TypeJackGenderMaleIndustry Recognized Mating Diameter2.10mm ID (0.083"), 5.50mm OD (0.217")Actual Diameter0.083" (2.10mm ID), 0.217" (5.50mm OD)Number of Positions/Contacts2 Conductors, 2 ContactsInternal Switch(s)Does Not Contain SwitchMounting TypeFree Hanging (In-Line)Mounting Feature-TerminationSolder CupShieldingUnshieldedFeatures-Insulation Color-Voltage - Rated20VDCCurrent Rating7A	Manufacturer	Tensility International Corp
Package - Series - Connector Type Jack Gender Male Industry Recognized Mating Diameter 2.10mm ID (0.083"), 5.50mm OD (0.217") Actual Diameter 0.083" (2.10mm ID), 0.217" (5.50mm OD) Number of Positions/Contacts 2 Conductors, 2 Contacts Internal Switch(s) Does Not Contain Switch Mounting Type Free Hanging (In-Line) Mounting Feature - Free Hanging (In-Line) Shielding Unshielded Features - Insulation Color - Voltage - Rated 20VDC Current Rating 7A	Category	Connectors, Interconnects
Series - Connector Type Jack Gender Male Industry Recognized Mating Diameter 2.10mm ID (0.083"), 5.50mm OD (0.217") Actual Diameter 0.083" (2.10mm ID), 0.217" (5.50mm OD) Number of Positions/Contacts 2 Conductors, 2 Contacts Internal Switch(s) Does Not Contain Switch Mounting Type Free Hanging (In-Line) Mounting Feature - Cremination Solder Cup Shielding Unshielded Features - Insulation Color - Voltage - Rated 20VDC Current Rating 7A		Barrel - Power Connectors
Connector Type Gender Male Industry Recognized Mating Diameter 2.10mm ID (0.083"), 5.50mm OD (0.217") Actual Diameter 0.083" (2.10mm ID), 0.217" (5.50mm OD) Number of Positions/Contacts 2 Conductors, 2 Contacts Internal Switch(s) Does Not Contain Switch Mounting Type Free Hanging (In-Line) Mounting Feature - Termination Solder Cup Shielding Unshielded Features - Insulation Color Voltage - Rated 20VDC Current Rating 7A	Package	-
Gender Male Industry Recognized Mating Diameter 2.10mm ID (0.083"), 5.50mm OD (0.217") Actual Diameter 0.083" (2.10mm ID), 0.217" (5.50mm OD) Number of Positions/Contacts 2 Conductors, 2 Contacts Internal Switch(s) Does Not Contain Switch Mounting Type Free Hanging (In-Line) Mounting Feature - Termination Solder Cup Shielding Unshielded Features - Insulation Color - Voltage - Rated 20VDC Current Rating 7A	Series	-
Industry Recognized Mating Diameter 2.10mm ID (0.083"), 5.50mm OD (0.217") Actual Diameter 0.083" (2.10mm ID), 0.217" (5.50mm OD) Number of Positions/Contacts 2 Conductors, 2 Contacts Internal Switch(s) Does Not Contain Switch Mounting Type Free Hanging (In-Line) Mounting Feature - Termination Solder Cup Shielding Unshielded Features - Insulation Color Voltage - Rated 20VDC Current Rating 7A	Connector Type	Jack
Actual Diameter 0.083" (2.10mm ID), 0.217" (5.50mm OD) Number of Positions/Contacts 2 Conductors, 2 Contacts Internal Switch(s) Does Not Contain Switch Mounting Type Free Hanging (In-Line) Mounting Feature - Termination Solder Cup Shielding Unshielded Features - Insulation Color - Voltage - Rated 20VDC Current Rating 7A	Gender	Male
Number of Positions/Contacts2 Conductors, 2 ContactsInternal Switch(s)Does Not Contain SwitchMounting TypeFree Hanging (In-Line)Mounting Feature-TerminationSolder CupShieldingUnshieldedFeatures-Insulation Color-Voltage - Rated20VDCCurrent Rating7A	Industry Recognized Mating Diameter	2.10mm ID (0.083"), 5.50mm OD (0.217")
Internal Switch(s) Mounting Type Free Hanging (In-Line) Mounting Feature - Termination Solder Cup Shielding Unshielded Features - Insulation Color Voltage - Rated Current Rating Does Not Contain Switch Free Hanging (In-Line) - Unshielded - Unshielded	Actual Diameter	0.083" (2.10mm ID), 0.217" (5.50mm OD)
Mounting Type Free Hanging (In-Line) Mounting Feature - Termination Solder Cup Shielding Unshielded Features - Insulation Color Voltage - Rated Current Rating Free Hanging (In-Line) - Current Rating Free Hanging (In-Line) - Solder Cup Unshielded To a color - A	Number of Positions/Contacts	2 Conductors, 2 Contacts
Mounting Feature Termination Solder Cup Unshielded Features - Insulation Color Voltage - Rated Current Rating Solder Cup Unshielded Touring Touring	Internal Switch(s)	Does Not Contain Switch
Termination Solder Cup Shielding Unshielded Features - Insulation Color - Voltage - Rated 20VDC Current Rating 7A	Mounting Type	Free Hanging (In-Line)
Shielding Unshielded Features - Insulation Color - Voltage - Rated 20VDC Current Rating 7A	Mounting Feature	-
Features - Insulation Color - Voltage - Rated 20VDC Current Rating 7A	Termination	Solder Cup
Insulation Color - Voltage - Rated 20VDC Current Rating 7A	Shielding	Unshielded
Voltage - Rated 20VDC Current Rating 7A	Features	-
Current Rating 7A	Insulation Color	-
	Voltage - Rated	20VDC
Report errors?	Current Rating	7A
		Report errors?

50-00025 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

50-00025 Payment Methods





















50-00025 Shipping Methods













If you have any question about 50-00025, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com