



50/100MNJ10R0DE Information

Heisener.com

Part Number 50/100MNJ10R0DE

Manufacturer Ohmite
Category Resistors

Chassis Mount Resistors

Description RES CHAS MNT 10 OHM 5% 100W

Package Modular

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com

salesdept@heisener.com

Request a Quote



Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









50/100MNJ10R0DE Specifications

Manufacturer Part Number 50/100MNJ10R0DE Manufacturer Ohmite Category Resistors Package Modular Series Metalohm Resistance 10 Ohms Tolerance ±5% Power (Watts) 100W Composition Wirewound Temperature Coefficient ±50ppm/°C Operating Temperature -55°C ~ 275°C Features Flame Proof, Non-Inductive, Pulse Withstanding, Safety Coating, Housing Type Steel Mounting Feature Flanges Size / Dimension 3.688" L x 0.750" W (93.68mm x 19.05mm) Height - Seated (Max) 0.750" (19.05mm) Lead Style Quick Connects, 0.250" (6.35mm) Package / Case Modular Failure Rate -			
CategoryResistorsPackageModularSeriesMetalohmResistance10 OhmsTolerance±5%Power (Watts)100WCompositionWirewoundTemperature Coefficient±50ppm/°COperating Temperature-55°C ~ 275°CFeaturesFlame Proof, Non-Inductive, Pulse Withstanding, SafetyCoating, Housing TypeSteelMounting FeatureFlangesSize / Dimension3.688" L x 0.750" W (93.68mm x 19.05mm)Height - Seated (Max)0.750" (19.05mm)Lead StyleQuick Connects, 0.250" (6.35mm)Package / CaseModularFailure Rate-	Manufacturer Part Number	50/100MNJ10R0DE	
Chassis Mount Resistors Package Modular Series Metalohm Resistance 10 Ohms Tolerance ±5% Power (Watts) 100W Composition Wirewound Temperature Coefficient ±50ppm/°C Operating Temperature -55°C ~ 275°C Features Flame Proof, Non-Inductive, Pulse Withstanding, Safety Coating, Housing Type Steel Mounting Feature Flanges Size / Dimension 3.688" L x 0.750" W (93.68mm x 19.05mm) Height - Seated (Max) 0.750" (19.05mm) Lead Style Quick Connects, 0.250" (6.35mm) Package / Case Modular Failure Rate -	Manufacturer	Ohmite	
PackageModularSeriesMetalohmResistance10 OhmsTolerance±5%Power (Watts)100WCompositionWirewoundTemperature Coefficient±50ppm/°COperating Temperature-55°C ~ 275°CFeaturesFlame Proof, Non-Inductive, Pulse Withstanding, SafetyCoating, Housing TypeSteelMounting FeatureFlangesSize / Dimension3.688" L x 0.750" W (93.68mm x 19.05mm)Height - Seated (Max)0.750" (19.05mm)Lead StyleQuick Connects, 0.250" (6.35mm)Package / CaseModularFailure Rate-	Category	Resistors	
SeriesMetalohmResistance10 OhmsTolerance±5%Power (Watts)100WCompositionWirewoundTemperature Coefficient±50ppm/°COperating Temperature-55°C ~ 275°CFeaturesFlame Proof, Non-Inductive, Pulse Withstanding, SafetyCoating, Housing TypeSteelMounting FeatureFlangesSize / Dimension3.688" L x 0.750" W (93.68mm x 19.05mm)Height - Seated (Max)0.750" (19.05mm)Lead StyleQuick Connects, 0.250" (6.35mm)Package / CaseModularFailure Rate-		Chassis Mount Resistors	
Resistance10 OhmsTolerance±5%Power (Watts)100WCompositionWirewoundTemperature Coefficient±50ppm/°COperating Temperature-55°C ~ 275°CFeaturesFlame Proof, Non-Inductive, Pulse Withstanding, SafetyCoating, Housing TypeSteelMounting FeatureFlangesSize / Dimension3.688" L x 0.750" W (93.68mm x 19.05mm)Height - Seated (Max)0.750" (19.05mm)Lead StyleQuick Connects, 0.250" (6.35mm)Package / CaseModularFailure Rate-	Package	Modular	
Tolerance ±5% Power (Watts) 100W Composition Wirewound Temperature Coefficient ±50ppm/°C Operating Temperature -55°C ~ 275°C Features Flame Proof, Non-Inductive, Pulse Withstanding, Safety Coating, Housing Type Steel Mounting Feature Flanges Size / Dimension 3.688" L x 0.750" W (93.68mm x 19.05mm) Height - Seated (Max) 0.750" (19.05mm) Lead Style Quick Connects, 0.250" (6.35mm) Package / Case Modular Failure Rate -	Series	Metalohm	
Power (Watts) Composition Wirewound Temperature Coefficient ±50ppm/°C Operating Temperature -55°C ~ 275°C Features Flame Proof, Non-Inductive, Pulse Withstanding, Safety Coating, Housing Type Steel Mounting Feature Flanges Size / Dimension 3.688" L x 0.750" W (93.68mm x 19.05mm) Height - Seated (Max) 0.750" (19.05mm) Lead Style Quick Connects, 0.250" (6.35mm) Package / Case Modular Failure Rate -	Resistance	10 Ohms	
Composition Wirewound Temperature Coefficient ±50ppm/°C Operating Temperature -55°C ~ 275°C Features Flame Proof, Non-Inductive, Pulse Withstanding, Safety Coating, Housing Type Steel Mounting Feature Flanges Size / Dimension 3.688" L x 0.750" W (93.68mm x 19.05mm) Height - Seated (Max) 0.750" (19.05mm) Lead Style Quick Connects, 0.250" (6.35mm) Package / Case Modular Failure Rate -	Tolerance	±5%	
Temperature Coefficient ±50ppm/°C Operating Temperature -55°C ~ 275°C Features Flame Proof, Non-Inductive, Pulse Withstanding, Safety Coating, Housing Type Steel Mounting Feature Flanges Size / Dimension 3.688" L x 0.750" W (93.68mm x 19.05mm) Height - Seated (Max) 0.750" (19.05mm) Lead Style Quick Connects, 0.250" (6.35mm) Package / Case Modular Failure Rate -	Power (Watts)	100W	
Operating Temperature -55°C ~ 275°C Features Flame Proof, Non-Inductive, Pulse Withstanding, Safety Coating, Housing Type Steel Mounting Feature Flanges Size / Dimension 3.688" L x 0.750" W (93.68mm x 19.05mm) Height - Seated (Max) 0.750" (19.05mm) Lead Style Quick Connects, 0.250" (6.35mm) Package / Case Modular Failure Rate -	Composition	Wirewound	
Features Flame Proof, Non-Inductive, Pulse Withstanding, Safety Coating, Housing Type Steel Mounting Feature Flanges Size / Dimension 3.688" L x 0.750" W (93.68mm x 19.05mm) Height - Seated (Max) 0.750" (19.05mm) Lead Style Quick Connects, 0.250" (6.35mm) Package / Case Modular Failure Rate -	Temperature Coefficient	±50ppm/°C	
Coating, Housing Type Steel Mounting Feature Flanges Size / Dimension 3.688" L x 0.750" W (93.68mm x 19.05mm) Height - Seated (Max) 0.750" (19.05mm) Lead Style Quick Connects, 0.250" (6.35mm) Package / Case Modular Failure Rate -	Operating Temperature	-55°C ~ 275°C	
Mounting Feature Flanges Size / Dimension 3.688" L x 0.750" W (93.68mm x 19.05mm) Height - Seated (Max) 0.750" (19.05mm) Lead Style Quick Connects, 0.250" (6.35mm) Package / Case Modular Failure Rate -	Features	Flame Proof, Non-Inductive, Pulse Withstanding, Safety	
Size / Dimension 3.688" L x 0.750" W (93.68mm x 19.05mm) Height - Seated (Max) 0.750" (19.05mm) Lead Style Quick Connects, 0.250" (6.35mm) Package / Case Modular Failure Rate -	Coating, Housing Type	Steel	
Height - Seated (Max) Lead Style Quick Connects, 0.250" (6.35mm) Package / Case Modular Failure Rate -	Mounting Feature	Flanges	
Lead StyleQuick Connects, 0.250" (6.35mm)Package / CaseModularFailure Rate-	Size / Dimension	3.688" L x 0.750" W (93.68mm x 19.05mm)	
Package / Case Modular Failure Rate -	Height - Seated (Max)	0.750" (19.05mm)	
Failure Rate -	Lead Style	Quick Connects, 0.250" (6.35mm)	
	Package / Case	Modular	
Report errors?	Failure Rate	-	
			Report errors?

50/100MNJ10R0DE Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

50/100MNJ10R0DE Payment Methods



















50/100MNJ10R0DE Shipping Methods













If you have any question about 50/100MNJ10R0DE, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com