



## **501FCM-ABAF Information**



For Reference Only

**Part Number** 501FCM-ABAF **Manufacturer** Silicon Labs

Category Crystals, Oscillators, Resonators Programmable Oscillators

**Description** OSC PROG LVCMOS 1.7V-3.6V EN/DS

Package 4-SMD, No Lead

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **501FCM-ABAF Specifications**

Manufacturer Part Number         501FCM-ABAF           Manufacturer         Silicon Labs           Category         Crystals, Oscillators, Resonators           Package         4-SMD, No Lead           Scries         CMEMS? Si501           Type         CMEMS?           Programmable Type         Programmed as Request           Available Frequency Range         32kHz ~ 100MHz           Function         Enable/Disable           Output         LVCMOS           Voltage - Supply         1.7 V ~ 3.6 V           Frequency Stability         -           Frequency Stability (Total)         ±20ppm           Operating Temperature         -20°C ~ 70°C           Spread Spectrum Bandwidth         -           Current - Supply (Max)         6.5mA           Ratings         -           Mounting Type         Surface Mount           Package / Case         4-SMD, No Lead           Size / Dimension         0.157" Lx 0.126" W (4.00mm x 3.20mm)           Height         0.035" (0.90mm)			
Category         Crystals, Oscillators, Resonators           Package         4-SMD, No Lead           Series         CMEMS? Si501           Type         CMEMS?           Programmable Type         Programmed as Request           Available Frequency Range         32kHz ~ 100MHz           Function         Enable/Disable           Output         LVCMOS           Voltage - Supply         1.7 V ~ 3.6 V           Frequency Stability         -           Frequency Stability (Total)         ±20ppm           Operating Temperature         -20°C ~ 70°C           Spread Spectrum Bandwidth         -           Current - Supply (Max)         6.5mA           Ratings         -           Mounting Type         Surface Mount           Package / Case         4-SMD, No Lead           Size / Dimension         0.157" L x 0.126" W (4.00mm x 3.20mm)           Height         0.035" (0.90mm)	Manufacturer Part Number	501FCM-ABAF	
Package         4-SMD, No Lead           Series         CMEMS? Si501           Type         CMEMS?           Programmable Type         Programmed as Request           Available Frequency Range         32kHz ~ 100MHz           Function         Enable/Disable           Output         LVCMOS           Voltage - Supply         1.7 V ~ 3.6 V           Frequency Stability         -           Frequency Stability (Total)         ±20ppm           Operating Temperature         -20°C ~ 70°C           Spread Spectrum Bandwidth         -           Current - Supply (Max)         6.5mA           Ratings         -           Mounting Type         Surface Mount           Package / Case         4-SMD, No Lead           Size / Dimension         0.157" L x 0.126" W (4.00mm x 3.20mm)           Height         0.035" (0.90mm)	Manufacturer	Silicon Labs	
Package         4-SMD, No Lead           Series         CMEMS? Si501           Type         CMEMS?           Programmable Type         Programmed as Request           Available Frequency Range         32kHz ~ 100MHz           Function         Enable/Disable           Output         LVCMOS           Voltage - Supply         1.7 V ~ 3.6 V           Frequency Stability         ±20pm           Operating Temperature         -20°C ~ 70°C           Spread Spectrum Bandwidth         -           Current - Supply (Max)         6.5mA           Ratings         -           Mounting Type         Surface Mount           Package / Case         4-SMD, No Lead           Size / Dimension         0.157" L x 0.126" W (4.00mm x 3.20mm)           Height         0.035" (0.90mm)	Category	Crystals, Oscillators, Resonators	
Series         CMEMS? Si501           Type         CMEMS?           Programmable Type         Programmed as Request           Available Frequency Range         32kHz ~ 100MHz           Function         Enable/Disable           Output         LVCMOS           Voltage - Supply         1.7 V ~ 3.6 V           Frequency Stability         -           Frequency Stability (Total)         ±20ppm           Operating Temperature         -20°C ~ 70°C           Spread Spectrum Bandwidth         -           Current - Supply (Max)         6.5mA           Ratings         -           Mounting Type         Surface Mount           Package / Case         4-SMD, No Lead           Size / Dimension         0.157" L x 0.126" W (4.00mm x 3.20mm)           Height         0.035" (0.90mm)		Programmable Oscillators	
TypeCMEMS?Programmable TypeProgrammed as RequestAvailable Frequency Range32kHz ~ 100MHzFunctionEnable/DisableOutputLVCMOSVoltage - Supply1.7 V ~ 3.6 VFrequency Stability-Frequency Stability (Total)±20ppmOperating Temperature-20°C ~ 70°CSpread Spectrum Bandwidth-Current - Supply (Max)6.5mARatings-Mounting TypeSurface MountPackage / Case4-SMD, No LeadSize / Dimension0.157" L x 0.126" W (4.00mm x 3.20mm)Height0.035" (0.90mm)	Package	4-SMD, No Lead	
Programmable Type Available Frequency Range 32kHz ~ 100MHz Function Enable/Disable Output LVCMOS Voltage - Supply 1.7 V ~ 3.6 V Frequency Stability - Frequency Stability (Total) Operating Temperature 2-20°C ~ 70°C Spread Spectrum Bandwidth - Current - Supply (Max) Ratings - Mounting Type Surface Mount Package / Case Size / Dimension Height  Programmed as Request  32kHz ~ 100MHz Frequest 32kHz ~ 100MHz 6.5mA  -  LVCMOS  LVCMOS  1.7 V ~ 3.6 V  -  2-0°C ~ 70°C  - 0°C ~ 70°C  Spread Spectrum Bandwidth Current - Supply (Max) 6.5mA  Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.157" L x 0.126" W (4.00mm x 3.20mm) Height	Series	CMEMS? Si501	
Available Frequency Range  Function  Enable/Disable  Output  LVCMOS  Voltage - Supply  1.7 V ~ 3.6 V  Frequency Stability  - Frequency Stability (Total)  Operating Temperature  -20°C ~ 70°C  Spread Spectrum Bandwidth  -  Current - Supply (Max)  Ratings  -  Mounting Type  Surface Mount  Package / Case  Size / Dimension  0.0157" L x 0.126" W (4.00mm x 3.20mm)  Height	Туре	CMEMS?	
Function Enable/Disable Output LVCMOS Voltage - Supply 1.7 V ~ 3.6 V Frequency Stability - Frequency Stability (Total) ±20ppm Operating Temperature -20°C ~ 70°C Spread Spectrum Bandwidth - Current - Supply (Max) 6.5mA Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.157" L x 0.126" W (4.00mm x 3.20mm) Height 0.035" (0.90mm)	Programmable Type	Programmed as Request	
OutputLVCMOSVoltage - Supply1.7 V ~ 3.6 VFrequency Stability-Frequency Stability (Total)±20ppmOperating Temperature-20°C ~ 70°CSpread Spectrum Bandwidth-Current - Supply (Max)6.5mARatings-Mounting TypeSurface MountPackage / Case4-SMD, No LeadSize / Dimension0.157" L x 0.126" W (4.00mm x 3.20mm)Height0.035" (0.90mm)	Available Frequency Range	32kHz ~ 100MHz	
Voltage - Supply  Frequency Stability  Frequency Stability (Total)  Departing Temperature  Spread Spectrum Bandwidth  Current - Supply (Max)  Ratings  Mounting Type  Surface Mount  Package / Case  Size / Dimension  Height  1.7 V ~ 3.6 V  1.7 V ~ 3.6 V  1.7 V ~ 3.6 V  Supply  Supply	Function	Enable/Disable	
Frequency Stability (Total) ±20ppm  Operating Temperature -20°C ~ 70°C  Spread Spectrum Bandwidth -  Current - Supply (Max) 6.5mA  Ratings -  Mounting Type Surface Mount  Package / Case 4-SMD, No Lead  Size / Dimension 0.157" L x 0.126" W (4.00mm x 3.20mm)  Height 0.035" (0.90mm)	Output	LVCMOS	
Frequency Stability (Total) ±20ppm  Operating Temperature -20°C ~ 70°C  Spread Spectrum Bandwidth -  Current - Supply (Max) 6.5mA  Ratings -  Mounting Type Surface Mount  Package / Case 4-SMD, No Lead  Size / Dimension 0.157" L x 0.126" W (4.00mm x 3.20mm)  Height 0.035" (0.90mm)	Voltage - Supply	1.7 V ~ 3.6 V	
Operating Temperature -20°C ~ 70°C  Spread Spectrum Bandwidth - Current - Supply (Max)  Ratings - Mounting Type Surface Mount  Package / Case 4-SMD, No Lead  Size / Dimension 0.157" L x 0.126" W (4.00mm x 3.20mm)  Height 0.035" (0.90mm)	Frequency Stability	-	
Spread Spectrum Bandwidth  Current - Supply (Max)  Ratings  - Mounting Type Surface Mount  Package / Case 4-SMD, No Lead Size / Dimension 0.157" L x 0.126" W (4.00mm x 3.20mm)  Height 0.035" (0.90mm)	Frequency Stability (Total)	±20ppm	
Current - Supply (Max)  Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.157" L x 0.126" W (4.00mm x 3.20mm) Height 0.035" (0.90mm)	Operating Temperature	-20°C ~ 70°C	
Ratings Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.157" L x 0.126" W (4.00mm x 3.20mm) Height 0.035" (0.90mm)	Spread Spectrum Bandwidth	-	
Mounting Type Surface Mount  Package / Case 4-SMD, No Lead Size / Dimension 0.157" L x 0.126" W (4.00mm x 3.20mm)  Height 0.035" (0.90mm)	Current - Supply (Max)	6.5mA	
Package / Case       4-SMD, No Lead         Size / Dimension       0.157" L x 0.126" W (4.00mm x 3.20mm)         Height       0.035" (0.90mm)	Ratings	-	
Size / Dimension       0.157" L x 0.126" W (4.00mm x 3.20mm)         Height       0.035" (0.90mm)	Mounting Type	Surface Mount	
Height 0.035" (0.90mm)	Package / Case	4-SMD, No Lead	
	Size / Dimension	0.157" L x 0.126" W (4.00mm x 3.20mm)	
Report errors?	Height	0.035" (0.90mm)	
•			Report errors?

### **501FCM-ABAF Guarantees**



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### **501FCM-ABAF Payment Methods**





















### **501FCM-ABAF Shipping Methods**













If you have any question about 501FCM-ABAF, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com