



501JCB-ADAF Information



For Reference Only

Part Number 501JCB-ADAF Manufacturer Silicon Labs

Category Crystals, Oscillators, Resonators

Programmable Oscillators

Description OSC PROG LVCMOS 3.3V EN/DS 20PPM

Package 4-SMD, No Lead

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









501JCB-ADAF Specifications

Manufacturer Part Number 501/CB-ADAF Manufacturer Silicon Labs Category Crystals, Oscillators, Resonators Package 4-SMD, No Lead Series CMEMS? Si501 Type CMEMS? Programmable Type Programmed as Request Available Frequency Range 32kHz ~ 100MHz Function Enable/Disable Output LVCMOS Voltage - Supply 3.3V Frequency Stability - Frequency Stability (Total) ±20ppm Operating Temperature -20°C ~ 70°C Spread Spectrum Bandwidth - Current - Supply (Max) 8.9mA Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.098" L x 0.079" W (2.50mm x 2.00mm) Height 0.035" (0.90mm)		
Category Crystals, Oscillators, Resonators Package 4-SMD, No Lead Series CMEMS? Si501 Type CMEMS? Programmable Type Programmed as Request Available Frequency Range 32kHz ~ 100MHz Function Enable/Disable Output LVCMOS Voltage - Supply 3.3V Frequency Stability - Frequency Stability (Total) ±20ppm Operating Temperature -20°C ~ 70°C Spread Spectrum Bandwidth - Current - Supply (Max) 8.9mA Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.098" L x 0.079" W (2.50mm x 2.00mm) Height 0.035" (0.90mm)	Manufacturer Part Number	501JCB-ADAF
Package 4-SMD, No Lead Series CMEMS? Si501 Type CMEMS? Programmable Type Programmed as Request Available Frequency Range 32kHz ~ 100MHz Function Enable/Disable Output LVCMOS Voltage - Supply - Frequency Stability - Frequency Stability (Total) ±20ppm Operating Temperature -20°C ~ 70°C Spread Spectrum Bandwidth - Current - Supply (Max) 8.9mA Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.098" L x 0.079" W (2.50mm x 2.00mm) Height 0.035" (0.90mm)	Manufacturer	Silicon Labs
Package 4-SMD, No Lead Series CMEMS? Si501 Type CMEMS? Programmable Type Programmed as Request Available Frequency Range 32kHz ~ 100MHz Function Enable/Disable Output LVCMOS Voltage - Supply 3.3V Frequency Stability - Frequency Stability (Total) ±20ppm Operating Temperature -20°C ~ 70°C Spread Spectrum Bandwidth - Current - Supply (Max) 8.9mA Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.098" L x 0.079" W (2.50mm x 2.00mm) Height 0.035" (0.90mm)	Category	Crystals, Oscillators, Resonators
Series CMEMS? Type CMEMS? Programmable Type Programmed as Request Available Frequency Range 32kHz ~ 100MHz Function Enable/Disable Output LVCMOS Voltage - Supply 3.3V Frequency Stability - Frequency Stability (Total) ±20ppm Operating Temperature -20°C ~ 70°C Spread Spectrum Bandwidth - Current - Supply (Max) 8.9mA Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.098" L x 0.079" W (2.50mm x 2.00mm) Height 0.035" (0.90mm)		Programmable Oscillators
TypeCMEMS?Programmable TypeProgrammed as RequestAvailable Frequency Range32kHz ~ 100MHzFunctionEnable/DisableOutputLVCMOSVoltage - Supply3.3VFrequency Stability-Frequency Stability (Total)±20ppmOperating Temperature-20°C ~ 70°CSpread Spectrum Bandwidth-Current - Supply (Max)8.9mARatings-Mounting TypeSurface MountPackage / Case4-SMD, No LeadSize / Dimension0.098" L x 0.079" W (2.50mm x 2.00mm)Height0.035" (0.90mm)	Package	4-SMD, No Lead
Programmable Type Programmed as Request Available Frequency Range 32kHz ~ 100MHz Function Enable/Disable Output LVCMOS Voltage - Supply 3.3V Frequency Stability Frequency Stability (Total) ±20ppm Operating Temperature -20°C ~ 70°C Spread Spectrum Bandwidth - Current - Supply (Max) 8.9mA Ratings Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.098" L x 0.079" W (2.50mm x 2.00mm) Height 0.00000000000000000000000000000000000	Series	CMEMS? Si501
Available Frequency Range Function Enable/Disable Output LVCMOS Voltage - Supply 3.3V Frequency Stability	Туре	CMEMS?
Function Enable/Disable Output LVCMOS Voltage - Supply 3.3V Frequency Stability - Frequency Stability (Total) ±20ppm Operating Temperature -20°C ~ 70°C Spread Spectrum Bandwidth - Current - Supply (Max) 8.9mA Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.098" L x 0.079" W (2.50mm x 2.00mm) Height 0.035" (0.90mm)	Programmable Type	Programmed as Request
OutputLVCMOSVoltage - Supply3.3VFrequency Stability-Frequency Stability (Total)±20ppmOperating Temperature-20°C ~ 70°CSpread Spectrum Bandwidth-Current - Supply (Max)8.9mARatings-Mounting TypeSurface MountPackage / Case4-SMD, No LeadSize / Dimension0.098" L x 0.079" W (2.50mm x 2.00mm)Height0.035" (0.90mm)	Available Frequency Range	32kHz ~ 100MHz
Voltage - Supply Frequency Stability Frequency Stability (Total) Operating Temperature Spread Spectrum Bandwidth - Current - Supply (Max) Ratings Mounting Type Surface Mount Package / Case Size / Dimension Height 3.3V 3.3V 3.3V 3.3V 4.20pm 5.20pm 4.20pm 5.20pm 5.20°C ~ 70°C 8.9mA 8.9mA 8.9mA 8.9mA 8.9mA 8.9mA 8.9mA 8.1mgs - Mounting Type Surface Mount 9.0098" L x 0.079" W (2.50mm x 2.00mm) 1.20mm 1.20m	Function	Enable/Disable
Frequency Stability (Total) ±20ppm Operating Temperature -20°C ~ 70°C Spread Spectrum Bandwidth - Current - Supply (Max) 8.9mA Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.098" L x 0.079" W (2.50mm x 2.00mm) Height 0.035" (0.90mm)	Output	LVCMOS
Frequency Stability (Total) ±20ppm Operating Temperature -20°C ~ 70°C Spread Spectrum Bandwidth - Current - Supply (Max) 8.9mA Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.098" L x 0.079" W (2.50mm x 2.00mm) Height 0.035" (0.90mm)	Voltage - Supply	3.3V
Operating Temperature -20°C ~ 70°C Spread Spectrum Bandwidth - Current - Supply (Max) Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.098" L x 0.079" W (2.50mm x 2.00mm) Height 0.035" (0.90mm)	Frequency Stability	-
Spread Spectrum Bandwidth Current - Supply (Max) Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.098" L x 0.079" W (2.50mm x 2.00mm) Height 0.035" (0.90mm)	Frequency Stability (Total)	±20ppm
Current - Supply (Max) 8.9mA Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.098" L x 0.079" W (2.50mm x 2.00mm) Height 0.035" (0.90mm)	Operating Temperature	-20°C ~ 70°C
Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.098" L x 0.079" W (2.50mm x 2.00mm) Height 0.035" (0.90mm)	Spread Spectrum Bandwidth	-
Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.098" L x 0.079" W (2.50mm x 2.00mm) Height 0.035" (0.90mm)	Current - Supply (Max)	8.9mA
Package / Case 4-SMD, No Lead Size / Dimension 0.098" L x 0.079" W (2.50mm x 2.00mm) Height 0.035" (0.90mm)	Ratings	-
Size / Dimension 0.098" L x 0.079" W (2.50mm x 2.00mm) Height 0.035" (0.90mm)	Mounting Type	Surface Mount
Height 0.035" (0.90mm)	Package / Case	4-SMD, No Lead
-	Size / Dimension	0.098" L x 0.079" W (2.50mm x 2.00mm)
Report errors?	Height	0.035" (0.90mm)
		Report errors?

501JCB-ADAF Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

501JCB-ADAF Payment Methods



















501JCB-ADAF Shipping Methods













If you have any question about 501JCB-ADAF, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com