



501MAF-ADAF Information



For Reference Only

Part Number 501MAF-ADAF Manufacturer Silicon Labs

Category Crystals, Oscillators, Resonators

Programmable Oscillators

Description OSC PROG LVCMOS 1.7V-3.6V EN/DS

Package 4-SMD, No Lead

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









501MAF-ADAF Specifications

Manufacturer Part Number 501MAF-ADAF Manufacturer Silicon Labs Category Crystals, Oscillators, Resonators Package 4-SMD, No Lead Series CMEMS? Si501 Type CMEMS? Programmable Type Programmed as Request Available Frequency Range 32kHz ~ 100MHz Function Enable/Disable Output LVCMOS Voltage - Supply 1.7 V ~ 3.6 V Frequency Stability - Operating Temperature -20°C ~ 70°C Spread Spectrum Bandwidth - Current - Supply (Max) 8.9mA Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.098" L x 0.079" W (2.50mm x 2.00mm) Height 0.035" (0.90mm)		
Category Crystals, Oscillators, Resonators Package 4-SMD, No Lead Series CMEMS? Si501 Type CMEMS? Programmable Type Programmed as Request Available Frequency Range 32kHz ~ 100MHz Function Enable/Disable Output LVCMOS Voltage - Supply 1.7 V ~ 3.6 V Frequency Stability - Frequency Stability (Total) ±50ppm Operating Temperature -20°C ~ 70°C Spread Spectrum Bandwidth - Current - Supply (Max) 8.9mA Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.098" L x 0.079" W (2.50mm x 2.00mm) Height 0.035" (0.90mm)	Manufacturer Part Number	501MAF-ADAF
Package 4-SMD, No Lead Series CMEMS? Si501 Type CMEMS? Programmable Type Programmed as Request Available Frequency Range 32kHz ~ 100MHz Function Enable/Disable Output LVCMOS Voltage - Supply 1.7 V ~ 3.6 V Frequency Stability - Frequency Stability (Total) ±50ppm Operating Temperature -20°C ~ 70°C Spread Spectrum Bandwidth - Current - Supply (Max) 8.9mA Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.098" L x 0.079" W (2.50mm x 2.00mm) Height 0.035" (0.90mm)	Manufacturer	Silicon Labs
Package 4-SMD, No Lead Series CMEMS? Si501 Type CMEMS? Programmable Type Programmed as Request Available Frequency Range 32kHz ~ 100MHz Function Enable/Disable Output LVCMOS Voltage - Supply 1.7 V ~ 3.6 V Frequency Stability - Frequency Stability (Total) ±50ppm Operating Temperature -20°C ~ 70°C Spread Spectrum Bandwidth - Current - Supply (Max) 8.9mA Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.098" L x 0.079" W (2.50mm x 2.00mm) Height 0.035" (0.90mm)	Category	Crystals, Oscillators, Resonators
Series CMEMS? Type CMEMS? Programmable Type Programmed as Request Available Frequency Range 32kHz ~ 100MHz Function Enable/Disable Output LVCMOS Voltage - Supply 1.7 V ~ 3.6 V Frequency Stability - Frequency Stability (Total) ±50ppm Operating Temperature -20°C ~ 70°C Spread Spectrum Bandwidth - Current - Supply (Max) 8.9mA Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.098" L x 0.079" W (2.50mm x 2.00mm) Height 0.035" (0.90mm)		Programmable Oscillators
TypeCMEMS?Programmable TypeProgrammed as RequestAvailable Frequency Range32kHz ~ 100MHzFunctionEnable/DisableOutputLVCMOSVoltage - Supply1.7 V ~ 3.6 VFrequency Stability-Frequency Stability (Total)±50ppmOperating Temperature-20°C ~ 70°CSpread Spectrum Bandwidth-Current - Supply (Max)8.9mARatings-Mounting TypeSurface MountPackage / Case4-SMD, No LeadSize / Dimension0.098" L x 0.079" W (2.50mm x 2.00mm)Height0.035" (0.90mm)	Package	4-SMD, No Lead
Programmable Type Available Frequency Range 32kHz ~ 100MHz Function Enable/Disable Output LVCMOS Voltage - Supply 1.7 V ~ 3.6 V Frequency Stability - Frequency Stability (Total) Operating Temperature 2-20°C ~ 70°C Spread Spectrum Bandwidth - Current - Supply (Max) Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.035" (0.90mm) Programmed as Request 32kHz ~ 100MHz Frequency 32kHz ~ 100MHz Frequency 52kHz ~ 100MHz 4-SMD, No Lead 52kHz ~ 100MHz 52kHz ~ 100MHz 52kHz ~ 100MHz 64kHz ~ 100MHz 65kHz	Series	CMEMS? Si501
Available Frequency Range32kHz ~ 100MHzFunctionEnable/DisableOutputLVCMOSVoltage - Supply1.7 V ~ 3.6 VFrequency Stability-Frequency Stability (Total)±50ppmOperating Temperature-20°C ~ 70°CSpread Spectrum Bandwidth-Current - Supply (Max)8.9mARatings-Mounting TypeSurface MountPackage / Case4-SMD, No LeadSize / Dimension0.098" L x 0.079" W (2.50mm x 2.00mm)Height0.035" (0.90mm)	Туре	CMEMS?
Function Enable/Disable Output LVCMOS Voltage - Supply 1.7 V ~ 3.6 V Frequency Stability - Frequency Stability (Total) ±50ppm Operating Temperature -20°C ~ 70°C Spread Spectrum Bandwidth - Current - Supply (Max) 8.9mA Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.098" L x 0.079" W (2.50mm x 2.00mm) Height 0.035" (0.90mm)	Programmable Type	Programmed as Request
OutputLVCMOSVoltage - Supply1.7 V ~ 3.6 VFrequency Stability-Frequency Stability (Total)±50ppmOperating Temperature-20°C ~ 70°CSpread Spectrum Bandwidth-Current - Supply (Max)8.9mARatings-Mounting TypeSurface MountPackage / Case4-SMD, No LeadSize / Dimension0.098" L x 0.079" W (2.50mm x 2.00mm)Height0.035" (0.90mm)	Available Frequency Range	32kHz ~ 100MHz
Voltage - Supply Frequency Stability Frequency Stability (Total) Deprating Temperature Spread Spectrum Bandwidth Current - Supply (Max) Ratings Mounting Type Surface Mount Package / Case Size / Dimension Height 1.7 V ~ 3.6 V 1.7 V ~ 3.6 V 8.9mA -20°C ~ 70°C 8 - 90°C 9	Function	Enable/Disable
Frequency Stability (Total) ±50ppm Operating Temperature -20°C ~ 70°C Spread Spectrum Bandwidth - Current - Supply (Max) 8.9mA Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.098" L x 0.079" W (2.50mm x 2.00mm) Height 0.035" (0.90mm)	Output	LVCMOS
Frequency Stability (Total) ±50ppm Operating Temperature -20°C ~ 70°C Spread Spectrum Bandwidth - Current - Supply (Max) 8.9mA Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.098" L x 0.079" W (2.50mm x 2.00mm) Height 0.035" (0.90mm)	Voltage - Supply	1.7 V ~ 3.6 V
Operating Temperature -20°C ~ 70°C Spread Spectrum Bandwidth - Current - Supply (Max) Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.098" L x 0.079" W (2.50mm x 2.00mm) Height 0.035" (0.90mm)	Frequency Stability	-
Spread Spectrum Bandwidth Current - Supply (Max) Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.098" L x 0.079" W (2.50mm x 2.00mm) Height 0.035" (0.90mm)	Frequency Stability (Total)	±50ppm
Current - Supply (Max) 8.9mA Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.098" L x 0.079" W (2.50mm x 2.00mm) Height 0.035" (0.90mm)	Operating Temperature	-20°C ~ 70°C
Ratings Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.098" L x 0.079" W (2.50mm x 2.00mm) Height 0.035" (0.90mm)	Spread Spectrum Bandwidth	-
Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.098" L x 0.079" W (2.50mm x 2.00mm) Height 0.035" (0.90mm)	Current - Supply (Max)	8.9mA
Package / Case 4-SMD, No Lead Size / Dimension 0.098" L x 0.079" W (2.50mm x 2.00mm) Height 0.035" (0.90mm)	Ratings	-
Size / Dimension 0.098" L x 0.079" W (2.50mm x 2.00mm) Height 0.035" (0.90mm)	Mounting Type	Surface Mount
Height 0.035" (0.90mm)	Package / Case	4-SMD, No Lead
	Size / Dimension	0.098" L x 0.079" W (2.50mm x 2.00mm)
Report errors?	Height	0.035" (0.90mm)
		Report errors?

501MAF-ADAF Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

501MAF-ADAF Payment Methods



















501MAF-ADAF Shipping Methods













If you have any question about 501MAF-ADAF, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com