



502JAB-ABAF Information



For Reference Only

Part Number 502JAB-ABAF Manufacturer Silicon Labs

Category Crystals, Oscillators, Resonators

Programmable Oscillators

Description OSC PROG LVCMOS 3.3V EN/DS 50PPM

Package 4-SMD, No Lead

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









502JAB-ABAF Specifications

Category Crystals, Oscillators, Resonators Package 4-SMD, No Lead Series CMEMS? Si502 Type CMEMS? Programmable Type Programmed as Request Available Frequency Range 32kHz ~ 100MHz Function Enable/Disable Output LVCMOS Voltage - Supply 3.3V Frequency Stability - Frequency Stability (Total) ±50ppm Operating Temperature -20°C ~ 70°C Spread Spectrum Bandwidth - Current - Supply (Max) 8.9mA Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.157" L x 0.126" W (4.00mm x 3.20mm)		
Category Crystals, Oscillators, Resonators Programmable Oscillators Package 4-SMD, No Lead Series CMEMS? Si502 Type CMEMS? Programmable Type Programmed as Request Available Frequency Range 32kHz ~ 100MHz Function Enable/Disable Output LVCMOS Voltage - Supply 3.3V Frequency Stability - Frequency Stability (Total) ±50ppm Operating Temperature -20°C ~ 70°C Spread Spectrum Bandwidth - Current - Supply (Max) 8.9mA Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.157" L x 0.126" W (4.00mm x 3.20mm) Height 0.035" (0.90mm)	Manufacturer Part Number	502JAB-ABAF
Package 4-SMD, No Lead Series CMEMS? Si502 Type CMEMS? Programmable Type Programmed as Request Available Frequency Range 32kHz ~ 100MHz Function Enable/Disable Output LVCMOS Voltage - Supply - Frequency Stability - Frequency Stability (Total) ±50ppm Operating Temperature -20°C ~ 70°C Spread Spectrum Bandwidth - Current - Supply (Max) 8.9mA Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.157" L x 0.126" W (4.00mm x 3.20mm) Height 0.035" (0.90mm)	Manufacturer	Silicon Labs
Package 4-SMD, No Lead Series CMEMS? Si502 Type CMEMS? Programmable Type Programmed as Request Available Frequency Range 32kHz ~ 100MHz Function Enable/Disable Output LVCMOS Voltage - Supply 3.3V Frequency Stability - Frequency Stability (Total) ±50ppm Operating Temperature -20°C ~ 70°C Spread Spectrum Bandwidth - Current - Supply (Max) 8.9mA Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.157" L x 0.126" W (4.00mm x 3.20mm) Height 0.035" (0.90mm)	Category	Crystals, Oscillators, Resonators
Series CMEMS? Type CMEMS? Programmable Type Programmed as Request Available Frequency Range 32kHz ~ 100MHz Function Enable/Disable Output LVCMOS Voltage - Supply 3.3V Frequency Stability - Frequency Stability (Total) ±50ppm Operating Temperature -20°C ~ 70°C Spread Spectrum Bandwidth - Current - Supply (Max) 8.9mA Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.157" L x 0.126" W (4.00mm x 3.20mm) Height 0.035" (0.90mm)		Programmable Oscillators
Type CMEMS? Programmable Type Programmed as Request Available Frequency Range 32kHz ~ 100MHz Function Enable/Disable Output LVCMOS Voltage - Supply 3.3V Frequency Stability - Frequency Stability (Total) ±50ppm Operating Temperature -20°C ~ 70°C Spread Spectrum Bandwidth - Current - Supply (Max) 8.9mA Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.157" L x 0.126" W (4.00mm x 3.20mm) Height 0.00000000000000000000000000000000000	Package	4-SMD, No Lead
Programmable Type Programmed as Request Available Frequency Range 32kHz ~ 100MHz Function Enable/Disable Output LVCMOS Voltage - Supply 3.3V Frequency Stability - Frequency Stability (Total) ±50ppm Operating Temperature -20°C ~ 70°C Spread Spectrum Bandwidth - Current - Supply (Max) 8.9mA Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.157" L x 0.126" W (4.00mm x 3.20mm) Height 0.00000000000000000000000000000000000	Series	CMEMS? Si502
Available Frequency Range Function Enable/Disable Output LVCMOS Voltage - Supply 3.3V Frequency Stability - Frequency Stability (Total) Operating Temperature -20°C ~ 70°C Spread Spectrum Bandwidth - Current - Supply (Max) Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.035" (0.90mm)	Туре	CMEMS?
Function Enable/Disable Output LVCMOS Voltage - Supply 3.3V Frequency Stability - Frequency Stability (Total) ±50ppm Operating Temperature -20°C ~ 70°C Spread Spectrum Bandwidth - Current - Supply (Max) 8.9mA Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.035" (0.90mm)	Programmable Type	Programmed as Request
Output LVCMOS Voltage - Supply 3.3V Frequency Stability - Frequency Stability (Total) ±50ppm Operating Temperature -20°C ~ 70°C Spread Spectrum Bandwidth - Current - Supply (Max) 8.9mA Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.157" L x 0.126" W (4.00mm x 3.20mm) Height 0.035" (0.90mm)	Available Frequency Range	32kHz ~ 100MHz
Voltage - Supply 3.3V Frequency Stability - Frequency Stability (Total) Operating Temperature -20°C ~ 70°C Spread Spectrum Bandwidth - Current - Supply (Max) Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.035" (0.90mm) 3.3V 3.3V 3.3V - ### Common Comm	Function	Enable/Disable
Frequency Stability (Total) Frequency Stability (Total) Operating Temperature -20°C ~ 70°C Spread Spectrum Bandwidth - Current - Supply (Max) Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.035" (0.90mm)	Output	LVCMOS
Frequency Stability (Total) ±50ppm Operating Temperature -20°C ~ 70°C Spread Spectrum Bandwidth - Current - Supply (Max) 8.9mA Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.157" L x 0.126" W (4.00mm x 3.20mm) Height 0.035" (0.90mm)	Voltage - Supply	3.3V
Operating Temperature -20°C ~ 70°C Spread Spectrum Bandwidth - Current - Supply (Max) 8.9mA Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.157" L x 0.126" W (4.00mm x 3.20mm) Height 0.035" (0.90mm)	Frequency Stability	-
Spread Spectrum Bandwidth - Current - Supply (Max) 8.9mA Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.157" L x 0.126" W (4.00mm x 3.20mm) Height 0.035" (0.90mm)	Frequency Stability (Total)	±50ppm
Current - Supply (Max) 8.9mA Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.157" L x 0.126" W (4.00mm x 3.20mm) Height 0.035" (0.90mm)	Operating Temperature	-20°C ~ 70°C
Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.157" L x 0.126" W (4.00mm x 3.20mm) Height 0.035" (0.90mm)	Spread Spectrum Bandwidth	-
Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.157" L x 0.126" W (4.00mm x 3.20mm) Height 0.035" (0.90mm)	Current - Supply (Max)	8.9mA
Package / Case 4-SMD, No Lead Size / Dimension 0.157" L x 0.126" W (4.00mm x 3.20mm) Height 0.035" (0.90mm)	Ratings	-
Size / Dimension 0.157" L x 0.126" W (4.00mm x 3.20mm) Height 0.035" (0.90mm)	Mounting Type	Surface Mount
Height 0.035" (0.90mm)	Package / Case	4-SMD, No Lead
	Size / Dimension	0.157" L x 0.126" W (4.00mm x 3.20mm)
Report errors?	Height	0.035" (0.90mm)
		Report errors?

502JAB-ABAF Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

502JAB-ABAF Payment Methods





















502JAB-ABAF Shipping Methods













If you have any question about 502JAB-ABAF, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com