

50E1C2.75 Information

Heisener.com

Part Number 50E1C2.75

Manufacturer Littelfuse Inc.

Category Circuit Protection

Electrical, Specialty Fuses

Description FUSE CRTRDGE 50A 2.75KVAC NONSTD

Package Cartridge, Non-Standard

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









50E1C2.75 Specifications

Manufacturer Part Number50EIC2.75ManufacturerLittelfuse Inc.CategoryCircuit ProtectionPackageCartridge, Non-StandardSeriesPOWR-GARD?Fuse TypeCartridgeCurrent Rating50AVoltage Rating - AC2750V (2.75kV)Voltage Rating - DC-Response Time-ApplicationsTransformer ProtectionFeaturesIndicatingClassEApprovals-Operating Temperature-Breaking Capacity @ Rated Voltage80kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension3.000" Dia x 10.875" L (76.20mm x 276.23mm)Report errors?		
CategoryCircuit ProtectionElectrical, Specialty FusesPackageCartridge, Non-StandardSeriesPOWR-GARD?Fuse TypeCartridgeCurrent Rating50AVoltage Rating - AC2750V (2.75kV)Voltage Rating - DC-Response Time-ApplicationsTransformer ProtectionFeaturesIndicatingClassEApprovals-Operating Temperature-Breaking Capacity @ Rated Voltage80kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension3.000" Dia x 10.875" L (76.20mm x 276.23mm)	Manufacturer Part Number	50E1C2.75
Electrical, Specialty Fuses Package Cartridge, Non-Standard Series POWR-GARD? Fuse Type Cartridge Current Rating SoA Voltage Rating - AC Voltage Rating - DC Response Time Applications Transformer Protection Features Indicating Class E Approvals C- Specialty Fuses Breaking Capacity @ Rated Voltage Boka Mounting Type Holder Package / Case Size / Dimension Electrical, Specialty Fuses Cartridge, Non-Standard Size / Dimension Electrical, Specialty Fuses Lectridge, Non-Standard Size / Dimension Electrical, Specialty Fuses POWR-GARD? Cartridge, Non-Standard Size / Dimension Electrical, Specialty Fuses Landard	Manufacturer	Littelfuse Inc.
PackageCartridge, Non-StandardSeriesPOWR-GARD?Fuse TypeCartridgeCurrent Rating50AVoltage Rating - AC2750V (2.75kV)Voltage Rating - DC-Response Time-ApplicationsTransformer ProtectionFeaturesIndicatingClassEApprovals-Operating Temperature-Breaking Capacity @ Rated Voltage80kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension3.000" Dia x 10.875" L (76.20mm x 276.23mm)	Category	Circuit Protection
SeriesPOWR-GARD?Fuse TypeCartridgeCurrent Rating50AVoltage Rating - AC2750V (2.75kV)Voltage Rating - DC-Response Time-ApplicationsTransformer ProtectionFeaturesIndicatingClassEApprovals-Operating Temperature-Breaking Capacity @ Rated Voltage80kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension3.000" Dia x 10.875" L (76.20mm x 276.23mm)		Electrical, Specialty Fuses
Fuse TypeCartridgeCurrent Rating50AVoltage Rating - AC2750V (2.75kV)Voltage Rating - DC-Response Time-ApplicationsTransformer ProtectionFeaturesIndicatingClassEApprovals-Operating Temperature-Breaking Capacity @ Rated Voltage80kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension3.000" Dia x 10.875" L (76.20mm x 276.23mm)	Package	Cartridge, Non-Standard
Current Rating Voltage Rating - AC 2750V (2.75kV) Voltage Rating - DC Response Time - Applications Features Indicating Class E Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 50A 2750V (2.75kV) - 1	Series	POWR-GARD?
Voltage Rating - AC Voltage Rating - DC Response Time Applications Transformer Protection Features Indicating Class E Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 2750V (2.75kV)	Fuse Type	Cartridge
Voltage Rating - DC Response Time Applications Transformer Protection Features Indicating Class E Approvals - Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension - Case Size / Dimension - Case - Cartridge, Non-Standard 3.000" Dia x 10.875" L (76.20mm x 276.23mm)	Current Rating	50A
Response Time - Applications Transformer Protection Features Indicating Class E Approvals - Operating Temperature - Breaking Capacity @ Rated Voltage 80kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 3.000" Dia x 10.875" L (76.20mm x 276.23mm)	Voltage Rating - AC	2750V (2.75kV)
Applications Features Indicating Class E Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension Transformer Protection Indicating Beaking Capacity E Approvals - Capacity Approv	Voltage Rating - DC	-
Features Indicating Class E Approvals - Operating Temperature - Breaking Capacity @ Rated Voltage 80kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 3.000" Dia x 10.875" L (76.20mm x 276.23mm)	Response Time	-
Class E Approvals - Operating Temperature - Breaking Capacity @ Rated Voltage 80kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 3.000" Dia x 10.875" L (76.20mm x 276.23mm)	Applications	Transformer Protection
Approvals - Operating Temperature - Breaking Capacity @ Rated Voltage 80kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 3.000" Dia x 10.875" L (76.20mm x 276.23mm)	Features	Indicating
Operating Temperature Breaking Capacity @ Rated Voltage 80kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 3.000" Dia x 10.875" L (76.20mm x 276.23mm)	Class	E
Breaking Capacity @ Rated Voltage 80kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 3.000" Dia x 10.875" L (76.20mm x 276.23mm)	Approvals	-
Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 3.000" Dia x 10.875" L (76.20mm x 276.23mm)	Operating Temperature	-
Package / Case Cartridge, Non-Standard Size / Dimension 3.000" Dia x 10.875" L (76.20mm x 276.23mm)	Breaking Capacity @ Rated Voltage	80kA
Size / Dimension 3.000" Dia x 10.875" L (76.20mm x 276.23mm)	Mounting Type	Holder
	Package / Case	Cartridge, Non-Standard
Report errors?	Size / Dimension	3.000" Dia x 10.875" L (76.20mm x 276.23mm)
		Report errors?

50E1C2.75 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

50E1C2.75 Payment Methods



















50E1C2.75 Shipping Methods













If you have any question about 50E1C2.75, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com