



### 50HV26B123KC Information

Heisener.com

Part Number 50HV26B123KC

Manufacturer KEMET Category Capacitors

Ceramic Capacitors

**Description** CAP CER 0.012UF 5KV X7R RADIAL

Package Radia

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# 50HV26B123KC Specifications

Manufacturer         KEMET           Category         Capacitors           Package         Radial           Series         HV           Capacitance         0.012µF           Tolerance         ±10%           Voltage - Rated         5000V (5kV)           Temperature Coefficient         X7R           Operating Temperature         -55°C ~ 200°C           Features         High Voltage, High Temperature           Ratings         -           Applications         SMPS Filtering           Failure Rate         -           Mounting Type         Through Hole           Package / Case         Radial           Size / Dimension         0.770" L x 0.270" W (19.56mm x 6.86mm)           Height - Seated (Max)         0.720" (18.29mm)           Thickness (Max)         -           Lead Spacing         0.675" (17.14mm)           Lead Style         Straight		
Category         Capacitors           Package         Radial           Series         HV           Capacitance         0.012µF           Tolerance         ±10%           Voltage - Rated         5000V (5kV)           Temperature Coefficient         X7R           Operating Temperature         -55°C ~ 200°C           Features         High Voltage, High Temperature           Ratings         -           Applications         SMPS Filtering           Failure Rate         -           Mounting Type         Through Hole           Package / Case         Radial           Size / Dimension         0.770" L x 0.270" W (19.56mm x 6.86mm)           Height - Seated (Max)         0.720" (18.29mm)           Thickness (Max)         -           Lead Spacing         0.675" (17.14mm)           Lead Style         Straight	Manufacturer Part Number	50HV26B123KC
Package         Radial           Series         HV           Capacitance         0.012µF           Tolerance         ±10%           Voltage - Rated         5000V (5kV)           Temperature Coefficient         X7R           Operating Temperature         -55°C ~ 200°C           Features         High Voltage, High Temperature           Ratings         -           Applications         SMPS Filtering           Failure Rate         -           Mounting Type         Through Hole           Package / Case         Radial           Size / Dimension         0.770" L x 0.270" W (19.56mm x 6.86mm)           Height - Seated (Max)         0.720" (18.29mm)           Thickness (Max)         -           Lead Spacing         0.675" (17.14mm)           Lead Style         Straight	Manufacturer	KEMET
Package         Radial           Series         HV           Capacitance         0.012μF           Tolerance         ±10%           Voltage - Rated         5000V (5kV)           Temperature Coefficient         X7R           Operating Temperature         -55°C ~ 200°C           Features         High Voltage, High Temperature           Ratings         -           Applications         SMPS Filtering           Failure Rate         -           Mounting Type         Through Hole           Package / Case         Radial           Size / Dimension         0.770" L x 0.270" W (19.56mm x 6.86mm)           Height - Seated (Max)         0.720" (18.29mm)           Thickness (Max)         -           Lead Spacing         0.675" (17.14mm)           Lead Style         Straight	Category	Capacitors
Series         HV           Capacitance         0.012μF           Tolerance         ±10%           Voltage - Rated         5000V (5kV)           Temperature Coefficient         X7R           Operating Temperature         -55°C ~ 200°C           Features         High Voltage, High Temperature           Ratings         -           Applications         SMPS Filtering           Failure Rate         -           Mounting Type         Through Hole           Package / Case         Radial           Size / Dimension         0.770" L x 0.270" W (19.56mm x 6.86mm)           Height - Seated (Max)         0.720" (18.29mm)           Thickness (Max)         -           Lead Spacing         0.675" (17.14mm)           Lead Style         Straight		Ceramic Capacitors
Capacitance       0.012μF         Tolerance       ±10%         Voltage - Rated       5000V (5kV)         Temperature Coefficient       X7R         Operating Temperature       -55°C ~ 200°C         Features       High Voltage, High Temperature         Ratings       -         Applications       SMPS Filtering         Failure Rate       -         Mounting Type       Through Hole         Package / Case       Radial         Size / Dimension       0.770" L x 0.270" W (19.56mm x 6.86mm)         Height - Seated (Max)       0.720" (18.29mm)         Thickness (Max)       -         Lead Spacing       0.675" (17.14mm)         Lead Style       Straight	Package	Radial
Tolerance ±10%  Voltage - Rated 5000V (5kV)  Temperature Coefficient X7R  Operating Temperature -55°C ~ 200°C  Features High Voltage, High Temperature  Ratings -	Series	HV
Voltage - Rated  Temperature Coefficient  X7R  Operating Temperature  -55°C ~ 200°C  Features  High Voltage, High Temperature  Ratings  -  Applications  SMPS Filtering  Failure Rate  Mounting Type  Through Hole  Package / Case  Radial  Size / Dimension  0.770" L x 0.270" W (19.56mm x 6.86mm)  Height - Seated (Max)  Thickness (Max)  -  Lead Spacing  0.675" (17.14mm)  Lead Style  STRANG OPERATOR OF THE PROPERT	Capacitance	0.012μF
Temperature Coefficient  X7R  Operating Temperature  -55°C ~ 200°C  Features  High Voltage, High Temperature  Ratings  -  Applications  SMPS Filtering  Failure Rate  -  Mounting Type  Through Hole  Package / Case  Radial  Size / Dimension  0.770" L x 0.270" W (19.56mm x 6.86mm)  Height - Seated (Max)  Thickness (Max)  -  Lead Spacing  0.675" (17.14mm)  Lead Style	Tolerance	$\pm 10\%$
Operating Temperature-55°C ~ 200°CFeaturesHigh Voltage, High TemperatureRatings-ApplicationsSMPS FilteringFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.770" L x 0.270" W (19.56mm x 6.86mm)Height - Seated (Max)0.720" (18.29mm)Thickness (Max)-Lead Spacing0.675" (17.14mm)Lead StyleStraight	Voltage - Rated	5000V (5kV)
Features High Voltage, High Temperature  Ratings - Applications SMPS Filtering  Failure Rate - Mounting Type Through Hole  Package / Case Radial  Size / Dimension 0.770" L x 0.270" W (19.56mm x 6.86mm)  Height - Seated (Max) 0.720" (18.29mm)  Thickness (Max) - Lead Spacing 0.675" (17.14mm)  Lead Style Straight	Temperature Coefficient	X7R
Ratings - SMPS Filtering Failure Rate - Through Hole Package / Case Radial Size / Dimension 0.770" L x 0.270" W (19.56mm x 6.86mm) Height - Seated (Max) 0.720" (18.29mm) Thickness (Max) - Lead Spacing 0.675" (17.14mm) Lead Style Straight	Operating Temperature	-55°C ~ 200°C
Applications SMPS Filtering Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.770" L x 0.270" W (19.56mm x 6.86mm) Height - Seated (Max) 0.720" (18.29mm) Thickness (Max) - Lead Spacing 0.675" (17.14mm) Lead Style Straight	Features	High Voltage, High Temperature
Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.770" L x 0.270" W (19.56mm x 6.86mm) Height - Seated (Max) 0.720" (18.29mm) Thickness (Max) - Lead Spacing 0.675" (17.14mm) Lead Style Straight	Ratings	-
Mounting Type Through Hole  Package / Case Radial  Size / Dimension 0.770" L x 0.270" W (19.56mm x 6.86mm)  Height - Seated (Max) 0.720" (18.29mm)  Thickness (Max) -  Lead Spacing 0.675" (17.14mm)  Lead Style Straight	Applications	SMPS Filtering
Package / Case Radial Size / Dimension 0.770" L x 0.270" W (19.56mm x 6.86mm) Height - Seated (Max) 0.720" (18.29mm)  Thickness (Max) - Lead Spacing 0.675" (17.14mm) Lead Style Straight	Failure Rate	-
Size / Dimension       0.770" L x 0.270" W (19.56mm x 6.86mm)         Height - Seated (Max)       0.720" (18.29mm)         Thickness (Max)       -         Lead Spacing       0.675" (17.14mm)         Lead Style       Straight	Mounting Type	Through Hole
Height - Seated (Max)  Thickness (Max)  Lead Spacing  Lead Style  O.720" (18.29mm)  -  U.720" (18.29mm)  Straight	Package / Case	Radial
Thickness (Max)  Lead Spacing  0.675" (17.14mm)  Lead Style  Straight	Size / Dimension	0.770" L x 0.270" W (19.56mm x 6.86mm)
Lead Spacing 0.675" (17.14mm)  Lead Style Straight	Height - Seated (Max)	0.720" (18.29mm)
Lead Style Straight	Thickness (Max)	-
	Lead Spacing	0.675" (17.14mm)
Report errors?	Lead Style	Straight
Report cross:		Report errors?

#### 50HV26B123KC Guarantees



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## 50HV26B123KC Payment Methods



















### 50HV26B123KC Shipping Methods













If you have any question about 50HV26B123KC, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com