

50LET Information



For Reference Only

Part Number 50LET Manufacturer Eaton

Category Circuit Protection

Electrical, Specialty Fuses

Description FUSE CARTRIDGE 50A 240VAC/150VDC

Package Cylindrical, Blade Terminal (Bolt)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









50LET Specifications

Manufacturer Part Number50LETManufacturerEatonCategoryCircuit Protection Electrical, Specialty FusesPackageCylindrical, Blade Terminal (Bolt)SeriesLETFuse TypeCartridgeCurrent Rating50AVoltage Rating - AC240VVoltage Rating - DC150VResponse Time-ApplicationsElectrical, IndustrialFeatures-Class-ApprovalsCE, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension0.697" Dia x 1.032" L (17.70mm x 26.20mm)Report errors?		
CategoryCircuit Protection Electrical, Specialty FusesPackageCylindrical, Blade Terminal (Bolt)SeriesLETFuse TypeCartridgeCurrent Rating50AVoltage Rating - AC240VVoltage Rating - DC150VResponse Time-ApplicationsElectrical, IndustrialFeatures-Class-ApprovalsCE, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension0.697" Dia x 1.032" L (17.70mm x 26.20mm)	Manufacturer Part Number	50LET
Flectrical, Specialty FusesPackageCylindrical, Blade Terminal (Bolt)SeriesLETFuse TypeCartridgeCurrent Rating50AVoltage Rating - AC240VVoltage Rating - DC150VResponse Time-ApplicationsElectrical, IndustrialFeatures-Class-ApprovalsCE, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension0.697" Dia x 1.032" L (17.70mm x 26.20mm)	Manufacturer	Eaton
PackageCylindrical, Blade Terminal (Bolt)SeriesLETFuse TypeCartridgeCurrent Rating50AVoltage Rating - AC240VVoltage Rating - DC150VResponse Time-ApplicationsElectrical, IndustrialFeatures-Class-ApprovalsCE, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension0.697" Dia x 1.032" L (17.70mm x 26.20mm)	Category	Circuit Protection
SeriesLETFuse TypeCartridgeCurrent Rating50AVoltage Rating - AC240VVoltage Rating - DC150VResponse Time-ApplicationsElectrical, IndustrialFeatures-Class-ApprovalsCE, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension0.697" Dia x 1.032" L (17.70mm x 26.20mm)		Electrical, Specialty Fuses
Fuse TypeCartridgeCurrent Rating50AVoltage Rating - AC240VVoltage Rating - DC150VResponse Time-ApplicationsElectrical, IndustrialFeatures-Class-ApprovalsCE, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension0.697" Dia x 1.032" L (17.70mm x 26.20mm)	Package	Cylindrical, Blade Terminal (Bolt)
Current Rating Voltage Rating - AC 240V Voltage Rating - DC 150V Response Time - Applications Electrical, Industrial Features - Class - Approvals CE, UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Size / Dimension Size / Dimen	Series	LET
Voltage Rating - AC Voltage Rating - DC 150V Response Time - Applications Electrical, Industrial Features - Class - Approvals CE, UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 240V 240V 240V 240V 240V 240V 240V 240V 250V Beletrical, Industrial - CE, UR 200kA CE, UR 200kA Bolt Mount Cylindrical, Blade Terminal (Bolt) 0.697" Dia x 1.032" L (17.70mm x 26.20mm)	Fuse Type	Cartridge
Voltage Rating - DC Response Time - Applications Electrical, Industrial Features - Class - Approvals CE, UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 150V 150V 150V 150V 150V 150V 150V 150	Current Rating	50A
Response Time	Voltage Rating - AC	240V
Applications Electrical, Industrial Features - Class - Approvals CE, UR Operating Temperature - Breaking Capacity @ Rated Voltage 200kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.697" Dia x 1.032" L (17.70mm x 26.20mm)	Voltage Rating - DC	150V
Features - Class - Class - CE, UR Approvals CE, UR Operating Temperature - Streaking Capacity @ Rated Voltage 200kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.697" Dia x 1.032" L (17.70mm x 26.20mm)	Response Time	-
Class - CE, UR Operating Temperature - Streaking Capacity @ Rated Voltage 200kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.697" Dia x 1.032" L (17.70mm x 26.20mm)	Applications	Electrical, Industrial
Approvals CE, UR Operating Temperature - Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension O.697" Dia x 1.032" L (17.70mm x 26.20mm)	Features	-
Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.697" Dia x 1.032" L (17.70mm x 26.20mm)	Class	-
Breaking Capacity @ Rated Voltage 200kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.697" Dia x 1.032" L (17.70mm x 26.20mm)	Approvals	CE, UR
Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.697" Dia x 1.032" L (17.70mm x 26.20mm)	Operating Temperature	-
Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.697" Dia x 1.032" L (17.70mm x 26.20mm)	Breaking Capacity @ Rated Voltage	200kA
Size / Dimension 0.697" Dia x 1.032" L (17.70mm x 26.20mm)	Mounting Type	Bolt Mount
	Package / Case	Cylindrical, Blade Terminal (Bolt)
Report errors?	Size / Dimension	0.697" Dia x 1.032" L (17.70mm x 26.20mm)
		Report errors?

50LET Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

50LET Payment Methods



















50LET Shipping Methods













If you have any question about 50LET, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com